

## Secure Execution Of Enterprise Applications On Mobile Devices

---

**DOCUMENT ID**      **DATE**  
 US 10063595 B1      **PUBLISHED**  
                                  2018-08-28

### INVENTOR INFORMATION

NAME	CITY	STATE	ZIP CODE	COUNTRY
Qureshi; Waheed	Pleasanton	CA	N/A	US
DeBenning; Thomas H.	Mountain View	CA	N/A	US
Datoo; Ahmed	Palo Alto	CA	N/A	US
Andre; Olivier	Bry sur Marne	N/A	N/A	FR
Abdullah; Shafaq	San Mateo	CA	N/A	US
McGinty; John M.	Fremont	CA	N/A	US
Roach; Kelly Brian	Palo Alto	CA	N/A	US

### ASSIGNEE INFORMATION

NAME	CITY	STATE	ZIP CODE	COUNTRY
Citrix Systems, Inc.	Fort Lauderdale	FL	N/A	US
	<b>TYPE CODE</b>			
	02			

**APPLICATION NO**      **DATE FILED**  
 15/863853                      2018-01-05

### DOMESTIC PRIORITY (CONTINUITY DATA)

continuation parent-doc US 14875450 20151005 US 10044757 child-doc US 15863853  
 continuation parent-doc US 13649024 20121010 US 9183380 20151110 child-doc US 14875450  
 us-provisional-application US 61702671 20120918  
 us-provisional-application US 61649134 20120518  
 us-provisional-application US 61546922 20111013  
 us-provisional-application US 61546021 20111011

### US CLASS CURRENT:

1/1

**CPC CURRENT**

<b>TYPE</b>	<b>CPC</b>	<b>DATE</b>
CPCI	H 04 L 63/0471	2013-01-01
CPCI	G 06 F 21/6218	2013-01-01
CPCI	H 04 W 4/02	2013-01-01
CPCI	H 04 W 12/086	2021-01-01
CPCI	H 04 L 9/0825	2013-01-01
CPCI	H 04 L 63/105	2013-01-01
CPCI	H 04 W 12/37	2021-01-01
CPCI	H 04 W 12/64	2021-01-01
CPCI	H 04 L 63/0428	2013-01-01
CPCI	H 04 W 12/30	2021-01-01
CPCI	H 04 L 67/10	2013-01-01
CPCI	H 04 L 63/20	2013-01-01
CPCI	G 06 F 21/6209	2013-01-01
CPCI	H 04 L 9/0891	2013-01-01
CPCI	H 04 W 12/06	2013-01-01
CPCI	G 06 F 8/53	2013-01-01
CPCI	H 04 L 9/0822	2013-01-01
CPCI	G 06 F 21/14	2013-01-01
CPCI	G 06 F 21/53	2013-01-01
CPCI	H 04 W 4/029	2018-02-01
CPCI	G 06 F 21/12	2013-01-01
CPCA	G 06 F 2221/2113	2013-01-01
CPCA	G 06 F 21/62	2013-01-01
CPCA	H 04 L 2209/80	2013-01-01

**KWIC Hits**

---

**Abstract**

A system is disclosed that includes components and features for enabling enterprise users to securely access enterprise resources (documents, data, application servers, etc.) using their mobile devices. An enterprise can use some or all components of the system to, for example, securely but flexibly implement a BYOD (bring your own device) policy in which users can run both personal applications and secure enterprise applications on their mobile devices. The system may, for example, implement policies for controlling mobile device accesses to enterprise resources based on device attributes (e.g., what mobile applications are installed), user attributes (e.g., the user's position or department), behavioral attributes, and other criteria. Client-side code installed on the mobile devices may further enhance security by, for example, creating a secure container for locally storing enterprise data, creating a secure execution environment for running enterprise applications, and/or creating secure application tunnels for communicating with the enterprise system.

## Background/Summary

### INCORPORATION BY REFERENCE

(1) This application is a continuation of U.S. patent application Ser. No. 14/875,450, entitled “Secure Execution of Enterprise Applications on Mobile Devices”, filed Oct. 5, 2015, which is a continuation of U.S. patent application Ser. No. 13/649,024, filed Oct. 10, 2012, now U.S. Pat. No. 9,183,380, which claims the benefit of and priority to U.S. Provisional Patent Application No. 61/546,021; U.S. Provisional Patent Application No. 61/546,922; U.S. Provisional Patent Application No. 61/649,134; and U.S. Provisional Patent Application No. 61/702,671. U.S. patent application Ser. No. 13/649,024 also incorporates by reference the entire technical disclosure of U.S. Pat. No. 7,788,536 to Qureshi et al. (“Qureshi '526”). Each of the above-identified patents and patent applications is also incorporated by reference herein in its entirety.

### BACKGROUND

#### (1) Field

(2) The present application relates generally to mobile computing devices (smartphones, tablets, PDAs, etc.) and associated application programs, and to systems for automated or semi-automated management of devices used for accessing managed resources of an enterprise.

#### (3) Description of the Related Art

(4) Many enterprises (e.g., corporations, partnerships, academic institutions, etc.) maintain enterprise computer networks that allow enterprise users to access enterprise resources, such as hardware and software applications for email, customer relationship management (CRM), document management, enterprise resource planning (ERP), and the like. Also, many enterprises allow users to access the enterprise network via mobile devices, such as smartphones, tablet computers, and the like. In some cases, software applications running on the mobile devices exchange data with the enterprise network, some of which can become saved on the memory hardware (e.g., hard drives, SD cards) of the mobile devices.

(5) A growing trend among businesses is to allow employees to use their personally owned mobile devices both to access company resources and the use and access their personal applications and data. This trend, known as BYOD (bring your own device) or BYOT (bring your own technology), significantly complicates the task of protecting enterprise resources, including confidential and/or sensitive information.

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a schematic illustration of an embodiment of an enterprise computer system and mobile computing devices associated with the enterprise.

(2) FIG. 1B is an embodiment similar to FIG. 1A, with the mobile device management system located in a cloud computing system (“the cloud”).

- (3) FIG. 1C is an embodiment similar to FIG. 1A, with the meta-application located in the cloud.
- (4) FIG. 1D is an embodiment similar to FIG. 1A, with the secure mobile gateway located in a firewall.
- (5) FIG. 1E is an embodiment similar to FIG. 1A, with the secure mobile gateway located in an enterprise resource.
- (6) FIG. 1F illustrates a mobile device screen display which includes a selectable screen element for exposing a user interface for selecting and launching enterprise applications.
- (7) FIG. 1G illustrates the user interface for selecting and launching enterprise applications.
- (8) FIG. 2 is a schematic illustration of an embodiment of a mobile device management system of the enterprise computer system of FIG. 1A.
- (9) FIG. 3A is a schematic illustration of an embodiment of a mobile device.
- (10) FIG. 3B illustrates security-related components and application that may be installed on a mobile device.
- (11) FIG. 4 is a schematic illustration of an embodiment of a gateway for selectively allowing or denying requests from mobile devices to access an enterprise computer system.
- (12) FIG. 5 is a flowchart illustrating an embodiment of a method in which an enterprise agent of a mobile device redirects a mobile device application's communications to an enterprise resource through an application tunnel.
- (13) FIG. 6 is a flowchart illustrating an embodiment of a method in which an enterprise computer system participates in the formation of an application tunnel between a mobile device application and an enterprise resource.
- (14) FIG. 7 is a flowchart illustrating an embodiment of a method in which an enterprise computer system regulates access by mobile devices to an enterprise resource.
- (15) FIG. 8 is a schematic illustration of an embodiment of a partially cloud-based meta-application for managing an enterprise computer system, a mobile device management system, and/or a gateway for allowing or denying requests from mobile devices to access an enterprise computer system.
- (16) FIG. 9 is a flowchart illustrating an embodiment of a method in which a mobile device uses encoded rules and remedial actions to detect and address security-related or productivity-related problems.
- (17) FIG. 10 is a flowchart illustrating an embodiment of a method in which a mobile device caches data input by a user in response to a loss of a network connection to an enterprise computer system.
- (18) FIG. 11 is a flowchart illustrating an embodiment of a method in which an enterprise computer

system caches data to be sent to a mobile device when a network connection to the mobile device is lost.

(19) FIG. 12 is a schematic illustration of an embodiment of a controller computer for remotely controlling a mobile device.

(20) FIG. 13 is a flowchart illustrating an embodiment of a method in which a controller computer participates in a remote control session with a mobile device.

(21) FIG. 14 shows an embodiment of a screen display of a controller computer engaged in a remote control session with a mobile device, including system information of the mobile device.

(22) FIG. 15 shows an embodiment of a screen display of a controller computer engaged in a remote control session with a mobile device, including access to a task manager of the mobile device.

(23) FIG. 16 shows an embodiment of a screen display of a controller computer engaged in a remote control session with a mobile device, including an interface for file transfers between the controller computer and the mobile device.

(24) FIG. 17 shows an embodiment of a screen display of a controller computer engaged in a remote control session with a mobile device, including an interface for editing a registry of the mobile device.

(25) FIG. 18 is a flowchart illustrating an embodiment of a method in which a mobile device participates in a remote control session with a controller computer.

(26) FIG. 19A shows an embodiment of a screen display of a controller computer engaged in a remote control session with a mobile device, including a chat session interface.

(27) FIG. 19B shows an embodiment of a mobile device emulated in FIG. 19A.

(28) FIG. 20 shows an embodiment of a screen display of a controller computer engaged in a remote control session with a mobile device, including a shared whiteboard feature.

(29) FIG. 21 shows an example of data logged by a mobile device gateway, which can be provided to an analytics service, in accordance with one embodiment.

(30) FIG. 22 shows an example of an interface for configuring criteria under which an analytics service sends alerts based on data logged by a mobile device gateway.

(31) FIG. 23 illustrates an embodiment of a method by which an analytics or network intelligence service helps to authenticate a user associated with a mobile device access request.

(32) FIG. 24 illustrates an embodiment of a software development kit for embedding, e.g., enterprise-protective functionalities into a mobile device software application.

(33) FIG. 25 illustrates an embodiment in which an application tunnel is created using an agent that runs on a mobile device.

- (34) FIG. 26 illustrates a user interface (e.g., web page) for enabling an administrator to create a tunnel between a mobile device and an application server.
- (35) FIG. 27 illustrates, for the embodiment of FIG. 25, representative communications and events that occur when an application tunnel is created between a mobile device and an application server.
- (36) FIG. 28 illustrates additional communications and events that occur when the application tunnel is set up as a secure application tunnel.
- (37) FIG. 29 illustrates an application modification system that enables a mobile application's behaviors to be modified without the need for the application's source code, and without the need for a programmer or programming skills.
- (38) FIG. 30 illustrates one embodiment of a process that may be used by the system of FIG. 29 to modify a mobile application.
- (39) FIG. 31 illustrates representative communications and events that occur when a mobile device retrieves a message with an attachment from an enterprise resource according to an embodiment.
- (40) FIG. 32 illustrates communications and events that occur when a mobile device forwards a message with an attachment according to an embodiment.
- (41) FIG. 33 illustrates communications and events that occur when a mobile device forwards a message with an attachment according to another embodiment.
- (42) FIG. 34 is a flowchart illustrating an embodiment of a method of encrypting an attachment.
- (43) FIG. 35 is a flowchart illustrating an embodiment of a method of decrypting an attachment.
- (44) Reference numerals used in this specification are generally based on the first figure (in the above listing) in which the numeral appears. A reference numeral with a value between **100-199** first appears in FIG. 1, a reference numeral with a value between **200-299** first appears in FIG. 2, and so on.
- (45) Skilled artisans will appreciate that while certain figures of the present disclosure illustrate numerous items, these figures illustrate certain embodiments, and other embodiments may involve more or less than the items shown.

## DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

(46) Various inventions and inventive features will now be described with reference to the drawings. As will be recognized, many of the disclosed features and associated components can be used independently of others, and can be implemented differently than described herein. Thus, nothing in this detailed description (or in the preceding background section) is intended to imply that any particular feature, component or characteristic of the disclosed systems is essential. Moreover, it will be understood that headings are provided for convenience and do not necessarily affect the scope or meaning of the claims.

## (47) Introduction

(48) The architecture described in this specification can be used by a corporation or other enterprise to flexibly implement a policy, such as a corporate owned device, BYOD (bring your own device) policy, for allowing enterprise users to use their mobile devices to securely access enterprise resources (documents, confidential data, corporate application and database servers, etc). This is accomplished through various security features that, for example, enable the enterprise to specify and implement policies for controlling mobile device accesses to particular enterprise resources. The policies may, for example, control mobile device accesses to enterprise resources based on a variety of criteria, such as the role of the respective user (e.g., which department the user is in), the configuration of the mobile device (e.g., whether any blacklisted mobile applications are installed), the logged behaviors of the user, the location of the mobile device, and/or the time at which access to the enterprise resource is requested. The architecture further enhances security, in some embodiments, by creating application tunnels that enable enterprise mobile applications to securely communicate over a network with the enterprise system. The architecture may also enable IT staff to selectively (and remotely) wipe a user's mobile device of enterprise application(s) and corporate data when, for example, the user discontinues employment or violates a corporate policy (such as if they jailbreak their device or otherwise use it in a disallowed configuration).

(49) As described in the section titled "Protecting Attachment Data," the disclosed architecture may also implement an attachment encryption policy in which encryption is applied to email attachments (or attachments to other types of messages, such as SMS messages) that are sent to mobile devices of enterprise users. This feature reduces the likelihood that an unauthorized user who obtains access to an enterprise member's mobile device will be able to access sensitive enterprise documents that have been sent between enterprise users as attachments.

(50) The disclosed architecture, in some embodiments, advantageously enables end users to concurrently run both enterprise mobile applications (those configured or authorized to access enterprise resources) and personal (non-enterprise) mobile applications on the same mobile device, without compromising security. This may be accomplished in part through mobile device software that creates a secure environment or shell in which the enterprise mobile applications can run and store data. This secure environment or shell may, for example, prevent the personal applications installed on a mobile device from accessing the documents and other data stored on the mobile device by the enterprise applications. In some embodiments, a secure launcher that runs on the mobile devices augments the mobile operating system's UI with a UI for launching the enterprise mobile applications installed on the mobile device. When a user launches an enterprise mobile application, the user may, for example, be presented with an authentication screen for entering a personal passcode that is necessary for running the enterprise mobile applications.

(51) The use of passcodes (or other types of authentication information) for enterprise applications reduces the likelihood that enterprise resources will be improperly accessed when, for example, the mobile device is lost or stolen, or when the mobile device is used by an employee's children to play games. In some embodiments, the secure launcher (or another component installed on the mobile device) further reduces this risk by performing a selective wipe of the mobile device when, for example, the user attempts but fails to enter a valid passcode a threshold number of consecutive times (e.g., 5 or 10). The selective wipe operation deletes some or all of the enterprise applications and associated data from the mobile device, without deleting any personal applications or data. In some embodiments, the enterprise's IT department can initiate a selective wipe of a particular

mobile device by remotely issuing a wipe command to the device.

(52) The architecture may also support various other types of remedial actions for protecting enterprise resources. One such remedy is to lock the mobile device, or an enterprise container on the device that stores enterprise data, such that the mobile device or container can only be unlocked with a valid code provided by IT staff. In some embodiments, these and other types of remedies can be invoked automatically based on conditions detected on the mobile device, or can be remotely initiated by IT staff.

(53) This specification also discloses processes for creating or augmenting mobile applications to enable them to use various enterprise security features. One such approach is described below under the heading "Modifying Behaviors of Pre-Existing Mobile Applications." Using this approach, an organization can modify existing mobile applications to add various security features without, the need to access the source code of such applications. The mobile application being modified may, for example, be a custom enterprise application, or may be a commercially available mobile application that is being configured for use within the enterprise. Through this process, the preexisting mobile application may, for example, be configured to (a) use application tunnels to communicate with the enterprise system, (b) use an encryption library to encrypt the documents and other data it stores on the mobile device, (c) present users with a login or passcode screen when the mobile application is launched, (d) disable cut, copy and paste operations, (e) disable offline access, (f) use a particular type of user authentication method, such as posture based authentication, or any combination thereof. The ability to modify preexisting mobile applications through this process gives enterprises greater flexibility in selecting mobile applications to offer to their members; for example, rather than requiring employees to use a custom-developed enterprise application for accessing cloud-based storage, the enterprise can modify (or have modified) a popular, commercially-available mobile application with which users are already familiar. Further, different versions of a given application (with different authentication methods, encryption levels, etc.) can be created for different types of employees.

(54) Also disclosed are processes for effectively adding enterprise security features to mobile applications with little or no need to modify the application code of such applications. One such approach involves the use of a secure virtual machine that is separate from the virtual machine of the mobile device's operating system. The secure virtual machine implements or provides access to various enterprise security features (such as application tunnels, data encryption, passcode prompts, etc.), and these security features are effectively inherited by or imposed upon the mobile applications that run within the secure virtual machine. Enterprise mobile applications may be configured or forced to use the secure virtual machine, while non-enterprise mobile applications continue to run within the native virtual machine of the mobile operating system. This capability gives enterprises additional freedom to flexibly select mobile applications to use as enterprise applications; for example, through this approach, an enterprise can effectively configure the mobile devices of users to enable the users to use a popular/familiar mobile application to securely access enterprise resources.

(55) The use of a secure virtual machine can enable an enterprise to provide a higher level of security for running an enterprise application on BYOD devices. For example, by running the application within a secure execution environment created by the secure virtual machine, a corporation can enforce a separate set of policies for the application, including networking and storage policies.



(56) Another approach, which is described under the heading “Secure Web Browser,” involves the use of a mobile browser application that implements the various enterprise security features. Like the secure virtual machine approach, mobile applications (or web pages accessed by the browser) that are configured to run within the secure browser effectively inherit the security mechanisms implemented by the secure browser. The use of such a secure browser also enables an enterprise to implement a content filtering policy in which, for example, employees are blocked from accessing certain web sites from their mobile devices. The secure browser can be used, for example, to enable mobile device users to access a corporate intranet without the need for a virtual private network (VPN).

(57) The disclosed architecture can also include a meta-application or system that monitors the overall enterprise system, including the mobile devices of enterprise users. The meta-application can operate generally as described in Qureshi '526, and can be implemented as a cloud based meta-application. The data collected by the meta-application can include data collected and reported by enterprise agents running on the mobile devices. In some embodiments, the meta-application generates rules based on observed behaviors, including behaviors of mobile device users. These rules can include gateway rules that are used by a secure mobile gateway to grant and deny mobile device requests to access enterprise resources.

(58) These and other security features and components are described in detail in the following sections. As will be recognized, many of the disclosed features and components can be used independently of others. Thus, nothing in the following description should be taken to imply that certain security features and components must be used in combination.

#### (59) System Overview and Terminology

(60) In many cases, when a mobile computing device accesses an enterprise computer/IT system, sensitive data associated with the enterprise and/or enterprise-related software applications can become stored onto the mobile device. Enterprise-related data can comprise any data associated with the enterprise, such as, without limitation, product information, sales data, customer lists, business performance data, proprietary know-how, inventions, trade secrets, and the like. Since this information can be very sensitive, an enterprise may wish to safeguard such information.

(61) Further, enterprises may wish to regulate how users use their mobile devices. For example, enterprises may want some control over where the mobile devices are used, which mobile device features can be used, which software applications can be installed and/or run on the devices, and the like. Enterprises also have a need to control and implement remedial actions for users that violate their mobile device usage policies.

(62) When users in the field experience problems with their mobile devices or could benefit from information, data, software, or coaching on how to perform certain operations using the devices, it can be difficult for the enterprise's IT support to provide highly effective assistance. Accordingly, there is also a need for improved secure management and technical support of mobile devices associated with an enterprise.

(63) Embodiments described in the present application address these and other concerns. The present application discloses computer systems and methods for automated or semi-automated management of mobile computing devices that access an enterprise computer network, such as

access to computer-implemented resources of the enterprise. As used herein, an “enterprise” may comprise substantially any type of organisation, including, without limitation, a business, partnership, corporation, and the like. A “mobile computing device” can comprise any of a wide variety of devices, such as, without limitation, a mobile phone, smartphone, personal digital assistant, tablet computer, handheld computing device, and the like. The mobile devices managed by the disclosed system may, for example, include or consist of mobile devices that run the Android™, IOS, or Windows Mobile operating system (or some subset thereof). As will be recognized, however, the architecture disclosed herein may be used with other mobile device operating systems, including operating systems that may be developed in the future.

(64) Individuals, entities, or groups of users that use mobile computing devices to access the enterprise computer network are referred to herein as “users.” Users can comprise members of the enterprise, such as employees, partners, officers, etc. Alternatively, users can comprise individuals or entities that are not members of the enterprise, but nevertheless have a need or reason to access the enterprise computer network. For example, users can be enterprise customers, suppliers, etc.

(65) An “enterprise resource” may comprise a machine-accessible resource associated with the enterprise. Enterprise resources can comprise any of a wide variety of different types of resources, including resources that assist or enable users in the performance of the users' roles or duties associated with the enterprise. For example, enterprise resources can comprise raw data stored on non-transitory computer-readable storage, documents stored on non-transitory computer-readable storage, computer hardware (e.g., physical servers), software applications stored on non-transitory computer-readable storage, macros for software applications (e.g., word processor macros) stored on non-transitory computer-readable storage, electronic mail systems, workspaces, customer relationship management (CRM) systems, document management systems, enterprise resource planning (ERP) systems, accounting systems, inventory systems, engineering tools, forms, style sheets, and many other resources. Enterprise resources can be configured to be accessed and used by software applications installed and running on mobile computing devices.

(66) FIG. 1A is a schematic illustration of an embodiment of a computer system **110** associated with an enterprise, as well as one or more users **115** and mobile computing devices **120** associated with the enterprise. In this example, each mobile device **120** is assigned to one enterprise user **115**, but alternatives are possible (multiple users **115** assigned to one device, and/or a single user assigned to multiple devices **120**). The mobile devices **120** are preferably configured to communicate with the enterprise system **110** (also referred to herein as an “enterprise network”) over a communication network **125**. The communication network **125** can comprise a wireless carrier network, the Internet, a wide area network, a WIFI network, and the like. Hence, the network **125** can comprise, for example, one or more wireless networks, one or more wired networks, or a combination of wired and wireless networks. Additionally, an enterprise system **110** can be configured to be accessed by non-mobile computing devices, such as desktop computers.

(67) The enterprise system **110** preferably includes an external firewall **122** and an internal firewall **124**. Each firewall **122**, **124** can comprise a device or set of devices designed to permit or deny network transmissions based upon certain criteria. The firewalls **122** and **124** can comprise software stored on non-transitory computer-readable storage, hardware, firmware, or a combination thereof. The firewalls **122** and **124** can be configured to perform basic routing functions. Embodiments of the invention can cooperate with one or both of the firewalls **122** and **124** or other

devices of the enterprise system **110** to filter mobile devices' access requests based on a set of gateway rules, in order to protect the enterprise system **110** from unauthorized access while permitting legitimate communications to pass. As will be described in further detail below, such access rules can be used to regulate access based on, e.g., mobile device properties, user properties, the specific enterprise resources **130** for which access is requested, or any combination thereof.

(68) The physical or logical subnetwork between the two illustrated firewalls **122** and **124** can be referred to as the “demilitarized zone” (DMZ), or alternatively as a “perimeter network.” Typically, the DMZ contains and exposes the enterprise's external services to a larger untrusted network, usually the Internet. Ordinarily, the purpose of the DMZ is to add an additional layer of security to the enterprise's local area network (LAN); an external attacker only has access to equipment in the DMZ, rather than any other part of the enterprise network.

(69) The illustrated enterprise system **110** includes a mobile device management system **126**, a secure mobile gateway **128**, and a “meta-application” **150**, each of which is described in further detail below. The enterprise system **110** also includes enterprise resources **130** logically positioned behind the internal firewall **124**, illustrated as resources **1** to **N**. At least some of the enterprise resources **130** can be configured to be accessed and/or used by the mobile devices **120**, such as by software applications installed and running on the mobile devices.

(70) Referring still to FIG. 1A, the mobile devices **120** can communicate with the carrier network **125** via connections **142**, such as cellular network connections and/or WIFI connections that ultimately connect to carrier networks. A mobile device's enterprise access request can be sent to the secure mobile gateway **128** via a connection **146**, and the gateway **128** can send the request to an enterprise resource **1802** via an internal connection **154**. Further, the enterprise system **110** can use the connections **142**, **146** to send information back to the mobile device **120**, such as data responsive to the device's enterprise access request.

(71) In some embodiments, a software application on a mobile device **120** can communicate with an enterprise resource **130** through an application tunnel via connections **142**, **144**, and **152**. Application tunnels are described in further detail below. In the illustrated embodiment, the mobile device management system **126** acts as a “tunneling mediator” within an application tunnel between the mobile device **120** (and typically a specific application running on the mobile device) and the enterprise resource **130**.

(72) FIGS. 1B and 1C illustrate embodiments that are similar to FIG. 1A, except that the mobile device management system **126** and meta-application **150** are respectively located (completely or at least partially) in a cloud computing system or environment **156** (“the cloud”). (In a hybrid of these two approaches, both the mobile device management system **126** and meta-application **150** reside in the cloud.) A cloud computing system typically includes computing resources configured to implement a service over a network, such as the Internet. For example, a cloud computing system can include a plurality of distributed computing resources, such as physical servers or other computing devices. With a cloud computing system, computing resources can be located at any suitable location that is accessible via a network. A cloud computing system can store and process data received over a network, while being accessible from a remote location. Typically, a cloud computing system is operated by a service provider that charges the enterprise, and other users of the cloud based computing system, a usage fee for using the system. In certain embodiments, both

the mobile device management system **126** and the meta-application **150** are located at least partially in the cloud **156**. In the embodiment of FIG. 1B, the cloud-based device management system **126** can be configured to provide gateway rules to the secure mobile gateway **128** via a connection **158**, as described in further detail below. Further, a software application on a mobile device **120** can communicate with an enterprise resource **130** through an application tunnel via connections **142**, **160**, and **162**, with the mobile device management system **126** acting as a tunneling mediator. In the embodiment of FIG. 1C, the meta-application portion **151** located in the cloud **156** can be configured to provide gateway rules to the secure mobile gateway **128** via a connection **164**, as described in further detail below. The meta-application **151** (or its rules engine) may alternatively be incorporated into the mobile device management system **126**, in which case it may orchestrate the management of the mobile device management system **126**.

(73) FIG. 1D is an embodiment similar to FIG. 1A, with the secure mobile gateway **128** implemented in the firewall **122**. In the embodiment of FIG. 1D, the secure mobile gateway **128** can be implemented in a Threat Management Gateway (TMG) server. As illustrated in FIG. 1D, some embodiments of the enterprise system **110** can be implemented without an internal firewall **124**.

(74) FIG. 1E is an embodiment similar to FIG. 1A, with the secure mobile gateway **128** implemented in an enterprise resource **130**. In the embodiment of FIG. 1E, the secure mobile gateway **128** can be implemented in an Internet Information Services (IIS) server. Such an IIS can be configured as an enterprise resource **130** and/or an internal firewall **124**.

(75) It will be understood that any of the enterprise systems **110** can be implemented with any of the principles and advantages described herein, as appropriate. Moreover, it will also be understood that the enterprise systems illustrated in FIGS. 1A-1E are provided for illustrative purposes, and other suitable systems can be implemented in accordance with the principles and advantages described herein.

(76) FIG. 2 is a schematic illustration of an embodiment of the mobile device management system **126** of FIG. 1A. The mobile device management system **126** can comprise a system of one or more computers, computer servers, storage devices, and other components. As explained in greater detail below, the mobile device management system **126** can be configured to manage or co-manage the application of “mobile device rules” **214** to the mobile computing devices **120**, and/or to act as a “tunneling mediator” between the mobile devices **120** and the enterprise resources **130** during use of application tunnels therebetween. The mobile device management system **126** can also be configured to regulate mobile device access to the enterprise system **110**, such as during use of such application tunnels. The illustrated components of the system **126** are described below.

(77) FIG. 3A is a schematic illustration of an embodiment of a mobile computing device **120**. The mobile device **120** can include a number of ordinary or standard components of a mobile device, such as a power supply **301**, a processor **302**, a user interface **304**, a hard drive memory **306**, a memory card (e.g., Secure Digital (SD) card) port **307**, a random access memory **308**, a network interface **310**, a subscriber identification module (SIM) card port **312**, a camera **314**, and/or a GPS chip **316**. The implementation and use of these components is generally well known and is not discussed herein in significant detail. The power supply **301** can include a battery port, battery, and/or a port for receiving electrical power from an external source (e.g., a standard electrical outlet). The processor **302** can be configured to execute software applications and various other executable components. The user interface **304** can include any of various known components,

such as a keypad **324** (such as a set of physical buttons or, alternatively, a touchscreen keypad) for receiving test input, a screen or display **326** (which can be a touchscreen) for displaying text, images, and/or video, a speaker **328** or audio out port for producing audible output, and/or a microphone **330** for receiving audible input. The hard drive **306** can comprise any of a variety of different types of nonvolatile and/or non-transitory computer-readable storage. The memory card port **307** is configured to receive a memory card (e.g., an SD card) on which data can be stored. The random access memory **308** can be used to store data used during the running of various processes. The network interface **310** can be used to send and receive data over a network (e.g., the wireless network **125**, which can operate in accordance with a number of standards, such as Wi-Fi, 3G, 4G, etc.). The SIM card port **312** is configured to receive a SIM card, as known in the art. The camera **314** can be configured to capture images and/or video. The GPS chip **316** can be configured to process GPS signals. The mobile device **120** can further include one or more installed software applications **318**. The installed software applications **318** can be stored, for example, on the hard drive **306** or in non-volatile solid state storage. The installed applications can include both enterprise applications and personal applications. It will be appreciated that the mobile device **120** can include any other computer hardware components in place of or in addition to those illustrated in FIG. 3, such as an accelerometer, transceiver, battery charger, USB controller, baseband processor, audio codec, etc.

(78) In the illustrated embodiment, the mobile device **120** includes an enterprise agent **320**, which is preferably a software application or other executable program installed on the mobile device. The enterprise agent **320** is preferably separate from the operating system of the mobile device **120**. In some embodiments, however, the enterprise agent **320** can be a component of the operating system of the mobile device or partially/fully embedded into the operating system of the mobile device **120**. In various embodiments described in greater detail below, the enterprise agent **320** executes the mobile device rules **214** and cooperates with the enterprise system **110** to regulate the mobile device's access to the enterprise system **110**, including to the enterprise resources **130**. In some embodiments, an enterprise system **110** can prompt an enterprise agent **320** to connect to the system **110** (e.g., the mobile device management system **126**) by sending a text message (e.g., SMS) to the mobile device **120**, with a connection command.

(79) The enterprise agent **320** can be installed onto the mobile device **120** as a condition of the mobile device's enrollment with the mobile device management system **126**. The enterprise can employ an automated subsystem for installing enterprise agents **320** onto the mobile devices **120** associated (e.g., enrolled) with the enterprise. For example, a mobile device manager **202** can be configured to send the enterprise agents **320** to the mobile devices **120** for automated installation or manual installation by the users **115**. Alternatively, IT personnel can manually install the enterprise agents **320** onto the mobile devices **120**, or end users can download and install the enterprise agent **320** from commercially available application stores. Different types of enterprise agents **320** can be provided for different mobile device types, platforms, operating systems, etc. The mobile device manager **202** or another software component of the enterprise system **110** can be configured to select an appropriate enterprise agent **320** for each given mobile device **120**, based on such properties of the mobile devices **120** (e.g., mobile device properties **208** of FIG. 2).

(80) Enterprise Agent and Other Security Components Installed on Mobile Devices

(81) The enterprise agent **320** may implement a variety of security-related features, including features that control (or enable the control of) mobile device accesses to enterprise resources **130**.

For example, the enterprise agent **320** installed on a given mobile device **120** may perform (i.e., instruct or cause the mobile device **120** to perform) some or all of the following tasks: (1) maintain a data connection with the enterprise system **110**, which connection can be used both for application tunnels and for communications that do not involve application tunnels; (2) provide access to a public or private enterprise app store from which the user can download enterprise applications that have been approved by and configured for the particular enterprise; (3) create application tunnels for enabling enterprise applications installed on the mobile device to securely access certain enterprise resources, (4) collect, and transmit to the mobile device management system **126**, “inventory” data regarding the properties and configuration of the mobile device, such as its manufacturer, model, operating system, screen size, memory size, memory availability, GPS coordinates, and which personal and enterprise mobile applications are installed on the device; (5) implement a log-in or other authentication service that requests and verifies the user's authentication information (e.g., passeode) when, for example, the user launches an enterprise mobile application; (6) decrypt encrypted message attachments received from the secure mobile gateway **128**, such as encrypted attachments to email messages received from other members of the user's enterprise; (7) maintain a secure key store that is accessible by enterprise applications for obtaining keys for encrypting and decrypting data; (8) check for blacklisted mobile applications installed on the mobile device, and report any such applications to the mobile device management system; (9) perform precautionary actions, such as deleting decryption keys used for decrypting message attachments, when certain conditions are met, such as when a blacklisted mobile application is detected on the mobile device or the device is reported as stolen, (10) kill (terminate execution of) any blacklisted applications or other mobile applications determined to create a security risk, (11) provide one or more additional services for keeping enterprise applications and data on the device separate from personal application and data; and (12) wiping the device of all enterprise application and data (in response to a command received from the mobile device management system) when, for example, the user discontinues employment with the enterprise. As described below, some of these functions may alternatively be implemented in a separate mobile application or component that is distinct from the enterprise agent **320**.

(82) The enterprise agent **320** collects information about the mobile device's configuration using standard operating system APIs and mechanisms, and/or using its own APIs and mechanisms. For example, in implementations for the Android operating system, the enterprise agent may query the package manager to obtain a list of the applications installed on the device. The enterprise agent can similarly query the operating system for a list of mobile applications that are currently running, and can monitor broadcast messages to identify new applications that are being installed. The device configuration information collected by the enterprise agent through this process may be reported to the mobile device management system **126**, which may use the information to generate rules that are applied by the secure mobile gateway **128** to control the mobile device's accesses to enterprise resources **130**. The enterprise agent **320** may itself also use the collected device configuration information to take various precautionary actions, such as killing blacklisted mobile applications as mentioned above.

(83) In one embodiment, the enterprise agent **320** is (or is part of) a mobile application that can be downloaded from an application store and installed on a mobile device **120**. Once the enterprise agent has been installed and launched, the end user supplies configuration information, such as a corporate email address and email password, for enabling the agent to communicate with a particular enterprise system **110**. Once configured, the agent **320** provides the user access to a

secure application store from which the user can download and install enterprise mobile applications that have been approved by, and in some cases specifically configured for, the user's enterprise. The functionality for downloading and installing enterprise mobile applications may alternatively be embodied within a separate "secure launcher" mobile application that runs in conjunction with the enterprise agent.

(84) FIG. 3B illustrates some of the executable security-related components **350** that may be installed or implemented on a mobile device **120** with, or as part of, the enterprise agent **320**. As will be recognized, some of these components **350** can be installed without others, and the illustrated components can be combined in various ways. One component is a key store **350A** that stores one or more encryption keys. In one embodiment, the key store is implemented and managed by the enterprise agent **320**, which enables the enterprise applications to access the key store to obtain encryption keys. A given enterprise application may, for example, use the encryption keys to encrypt files and other data stored to memory **348**.

(85) With further reference to FIG. 3B, a secure launcher **350B** may also be installed on the mobile device **120** for launching enterprise applications. The secure launcher may be part of the enterprise agent **320**, or may be a separate mobile application. The secure launcher **350B** may implement or enforce various security policies, such as requiring user entry of a valid passcode when an enterprise application is launched. One embodiment of a user interface implemented by the secure launcher **350B** is shown in FIGS. 1F and 1G and is described below. As described below, enterprise applications may be modified or written to use the secure launcher rather than the general launcher included in the mobile device's operating system. In one embodiment, the secure launcher also includes functionality for wiping the mobile device **120** of all enterprise applications and data in response to a threshold number of consecutive invalid passcode entry attempts, or in response to a remotely issued command from the enterprise's IT department.

(86) As further shown in FIG. 3B, a secure virtual machine **350C** may be installed on the mobile device **120** in some embodiments to create or augment a secure execution environment for running some or all of the enterprise applications. This secure virtual machine (VM) supplements, and may run concurrently with, the mobile operating system's default VM. For example, one or more enterprise mobile applications may run within the secure VM while all other mobile applications, including all personal mobile applications, run on the same device in the operating system's default VM. As described below under the heading "Secure Virtual Machine," the secure VM **350C** implements a variety of policies and measures (such as security, management, storage, networking, and/or process execution policies) that are not implemented (or are implemented unsuitably for enterprise applications) in the mobile operating system's default VM. For example, the secure VM may be capable of establishing application tunnels for accessing the enterprise system, and may route requests from enterprise applications over corresponding application tunnels. The secure VM may also prevent an enterprise application from running unless and until the user enters a valid passcode or otherwise successfully authenticates. The secure VM may be installed on a mobile device together with a set of code libraries that are used by the secure VM in place of corresponding code libraries of the operating system.

(87) One benefit of using a secure VM **350C** is that it reduces or eliminates the need for the mobile applications to be specifically written or modified for use with an enterprise system **110**. For example, an enterprise may wish to make a particular commercially-available mobile application available to its employees for use in accessing company resources, but may not have permission

to modify the application to implement the various security features described herein (such as authentication, secure storage, and secure networking). In such a scenario, the enterprise may configure the mobile application or the mobile device to cause this particular application, when executed, to run only within the secure VM.

(88) The secure VM is preferably implemented as a separate mobile application, but may alternatively be part of another application or component (such as the enterprise agent **320** or the secure launcher **350B**). The secure VM may be invoked in various ways, for example, the enterprise agent may request that the secure VM run a particular application, or an application may, upon being launched, request or specify the secure VM as its execution environment. In some embodiments, the secure launcher **350B** and the secure VM **350C** are used in combination to create a secure space for running enterprise applications, although each can be used independently of the other. Additional details of the secure VM are described below in the section titled Secure Virtual Machine.

(89) As further shown in FIG. 3B, a secure container component **350D** may also be installed on the mobile device **120**, preferably as a separate mobile application or as part of the enterprise agent **320**. This component **350D** is responsible for creating a secure container on the mobile device for the enterprise applications to store documents and other information. One embodiment of this feature is described below under the heading Secure Document Containers. In some embodiments, when a selective wipe operation is performed, some or all of the documents and data stored in the secure container are deleted from the mobile device or are otherwise made inaccessible.

(90) FIG. 3B also shows two types of mobile applications **318** that may be installed on the mobile device **120**: enterprise applications **318A** and personal applications **318B**. As illustrated, an enterprise application **318** may include executable security code **360** (code libraries, etc.) for implementing some or all of the disclosed client-side security tactions (application tunnels, passcode verification, encryption of data, etc.) This security code **360** may be added via a special SDK, or may be added post-development via the application wrapping process described below in the section titled Modifying Behaviors of Pre-Existing Mobile Applications. As mentioned above, in some cases a given enterprise application may not include any security code **360**, but may instead run within either a secure VM **350C** or a secure browser that imposes a layer of security on the enterprise application.

(91) In addition to the components shown in FIG. 3B, one or more code libraries may be installed on the mobile device for implementing various security functions, such as data encryption and formation of application tunnels. As one example, a custom SSL library may be installed and used in place of the operating system's SSL library to create secure application tunnels, as described below in the section titled Application Tunnels.

## (92) User Interface for Launching Enterprise Applications

(93) In one embodiment, which is depicted in FIGS. 1F and 1G, the secure launcher **350B** displays a persistent display element **170** (FIG. 1F) at the edge of the mobile device's screen. This display element preferably remains visible across all of the device's home screens and when user is in an application. If the user taps on this display element **170** or swipes it to the left, a rotatable carousel or "wheel" (FIG. 1G) is displayed that includes respective icons **174** corresponding to specific



enterprise applications or groups (folders) of enterprise applications installed on the device. (The other icons **175** shown in FIGS. 1G and 1F typically correspond to personal mobile applications, and/or folders of such applications, installed on the device.) By rotating the wheel **174** via an upward or downward swipe gesture, the user can expose additional icons **174** corresponding to additional enterprise applications or folders. Tapping on an application icon **174** causes the associated enterprise application to be launched, and tapping on a folder icon **174** causes the enterprise applications stored in the folder to be displayed. The user can also swipe the wheel **172** to the right to cause it to return to the retracted position shown in FIG. 1F. In the illustrated embodiment, the enterprise applications can only be launched from the wheel (with the secure launcher), and cannot be launched using the general launcher of the device's operating system.

(94) In some embodiments, when the user launches an enterprise application via the wheel **172**, the user is prompted to enter a passcode, and the application is not launched unless the correct passcode is entered. The task of requesting and verifying the passcode may, for example, be performed by the enterprise agent **320** (FIG. 3A), by a separate secure launcher **350B** (FIG. 3B), by a secure virtual machine **350C** (FIG. 3C), or by code **360** that is added to the enterprise application via an SDK or an application wrapping process. These and other techniques for providing a secure execution environment for running enterprise mobile applications are described further below.

(95) In one embodiment, which is shown in FIG. 1F, the wheel **172** is displayed as a transparent or translucent overlay that enables the user to view and select the home screen icons **175** falling "behind" the wheel, such that the user can launch the personal applications corresponding to these icons **175**. In another embodiment, the wheel is opaque, and thus obstructs the view of any icons **175** falling behind it. In yet another embodiment, the home screen icons **175** disappear when the wheel is "pulled out," or is pulled out beyond a particular point.

(96) The secure launcher's user interface may also include features for enabling the user to, for example, arrange the icons **174** on the wheel **172**, control the position of the wheel (e.g., which screen edge it extends from), and control the extent to which the wheel is displayed. The selectable element **170** (FIG. 1F) for pulling out and retracting the wheel preferably remains persistent across all of the device's home screens, such that the enterprise applications can be easily accessed from any of these screens

#### (97) Overview of Mobile Device Management System

(98) Referring to FIGS. 1A and 2, embodiments of the mobile device management system (**26** are configured to create, edit, and provide gateway rules to the secure mobile gateway **128**, as discussed in detail below. The mobile device management system **126** can also act as a tunneling mediator for application tunnels between the mobile devices **120** and the enterprise resources **130** or other network resources within or even outside the enterprise system **110**. The components of the illustrated mobile device management system **126** are now described.

(99) The illustrated mobile device management system **126** includes a mobile device manager component **202** (FIG. 2), which preferably comprises a software application that runs on one or more physical machines. The mobile device manager **202** can be configured to both provision and maintain enrollments of the mobile devices **120** with the enterprise. Preferably, the mobile device manager **202** is configured to handle or participate in the provisioning and decommissioning of the

mobile devices **120** associated with the enterprise.

(100) In the illustrated embodiment of FIG. 2, the mobile device management system **126** includes mobile device information or attributes **204** stored in computer-readable or machine-readable storage. The mobile device information **204** preferably includes properties or attributes **208** of the mobile devices **120** enrolled with the mobile device manager **202**, such as device type or platform (e.g., platforms for iPhone™, Android™, Windows Mobile™, etc.), device model, operating system version, device capabilities and features, identifiers of installed applications, etc. In certain embodiments, the mobile device properties **208** are ones that are permanent (e.g., device type, platform). In some embodiments, the mobile device properties **208** can also be properties subject to regular or periodic change (e.g., software or operating system version, which mobile applications are installed, etc.) As mentioned above, the various properties of a given mobile device may be determined, and reported to the mobile device management system **126**, by the enterprise agent **320** installed on the mobile device **120**. Device property information may also be supplied by system administrators.

(101) The mobile device information **204** can also include user-device assignment records **210** that identify which users **115** or user accounts are assigned to the enrolled mobile devices **120**, as well as roles **206** of the users **115** within the enterprise. A user's role **206** typically associates the user **115** with the enterprise-related duties or activities in which the user engages. Roles **206** can have names and, optionally, associated definitions. The roles **206** (and role names) can mimic the enterprise's departments and positional hierarchy. For example, an enterprise can define roles with names such as Upper Management, Officer, Sales, Accounting, Engineering, Word Processing, Human Resources, etc. In this scheme, a salesperson can be given the role "Sales," an engineer can be given the role "Engineering," and so forth. Also, roles **206** can be defined as broadly or as narrowly as may suit the needs of the enterprise. For example, an enterprise can give all of its engineers the "Engineering" role. Alternatively or additionally, the enterprise may wish to define narrower roles such as "Computer Engineer," "Materials Engineer," "Semiconductor Processing Engineer," etc. particularly if the enterprise wishes to differentiate the mobile device authorizations of its different types of engineering personnel. Further, a user **115** can be assigned to multiple roles **206**, depending upon the user's duties or activities associated with the enterprise. In certain embodiments, an enterprise may use an RBAC (role-based access control) system to assist in the regulation of enterprise resources **130**, and the user roles **206** can relate to or be the same as the roles defined in the RBAC system.

(102) The enterprise agents **320** of the mobile devices **120** can be configured to send device-related data to the mobile device management system **126** periodically, and/or whenever the mobile devices **120** connect to the mobile device management system **126** (e.g., upon the formation of an application tunnel). For instance, the enterprise agents **320** can send data concerning software applications installed on the mobile devices **120**, software upgrades, system information, etc., as described above. In one embodiment, the agent **320** sends such device-properties information over the same connection that is used for application tunnels, but without the use of an application tunnel.

(103) With continued reference to FIGS. 1A and 2, the mobile device management system **126** can include one or more enterprise access policies **218** stored in computer storage. The access policies **218** preferably define conditions under which mobile device access to enterprise resources **130** will be granted or denied. In some embodiments, a single access policy **218** can apply to mobile

devices **120** of different makes, models, operating systems, or any combination thereof. Policies **218** can depend on user roles **206**, mobile device properties **208**, the specific enterprise resources **130** requested to be accessed by the mobile devices **120**, or any combination thereof. The mobile device management system **126** can use the access policies **218** to process mobile device access requests received directly by the mobile device management system **126**, including requests received via secure application tunnels. Additionally, as described below, the secure mobile gateway **128** can leverage the access policies **218** to grant or deny mobile device access requests received directly by the secure mobile gateway **128**.

(104) As shown in FIG. 2, the mobile device management system **126** can include a script-editing tool **220** for editing scripts that are executable on the mobile devices **120**, as described below. The mobile device management system **126** can also include a tool **221** for editing mobile device rules **214** and remedial actions **216**, as described below.

(105) The mobile device management system **126** can include a gateway rule generator **222** for creating, editing, and/or sending gateway rules to the secure mobile gateway **128**, as described below. These tools **220**, **221** may, for example, be used by IT administrators to implement various security-related features and policies, as described below.

(106) The mobile device management system **126** can include a tunneling mediator module **224** for mediating an application tunnel between a software application running on a mobile device **120** and another resource, such as an enterprise resource **130**, as described below. The tunneling mediator module **224** can also be configured to grant or deny access requests based on the access policies **218** and information **204**.

(107) The mobile device management system **126** can also include a remedy agent **226** for executing remedial actions provided by the meta-application **150** and/or **151**, as described below. The remedy agent **226** may execute various types of remedial actions based on conditions specified by roles, for example, as described generally in Qureshi '526.

(108) With further reference to FIG. 2, the above-described functional components **202**, **224**, **220**, **221**, **222**, **226** of the mobile device management system **126** may be implemented in executable program code modules that run on appropriate computer hardware, such as on one or more physical servers or other computing devices. These components may, for example, run on a single physical server or other machine, or may be distributed across multiple machines on a network. In some embodiments, some or all of these components may alternatively be implemented in firmware or in application-specific hardware (ASICs, FPGAs, etc.). The various data or data storage components **210**, **212**, **218**, **223** of the mobile device management system **126** may be implemented in any appropriate type or types of computer storage (e.g., hard disk drives, solid state memory arrays, optical storage devices, etc.) using databases, flat files, and/or other types of data storage arrangements.

(109) For example, an enterprise may wish to use multiple mobile device management systems **126**. An enterprise with multiple offices may use separate systems **126** for the separate offices. This may be useful if the enterprise has offices located in different geographical areas. For example, a large enterprise with offices in England, Japan, and the U.S. may use three different mobile device management systems **126** located within or near to those office locations. In such embodiments, each mobile device management system **126** can be responsible for managing

mobile devices **120** in a different geographical area, wherein such mobile device management can comprise sending rule packages to the mobile devices **120** (as described below) and/or regulating access to enterprise resources **130**. In such embodiments, the secure mobile gateway **128** is preferably configured to communicate with each of the mobile device management systems **126** for the purposes described herein. In some implementations, a console is provided that can be used to view the various systems **126** associated with a given enterprise.

#### (110) Use of Secure Mobile Gateway to Regulate Mobile Device Access to Enterprise System

(111) With reference to FIG. 1A, an enterprise may wish to regulate how its mobile device users **115** access the enterprise resources **130** via the mobile devices **120**. Any given enterprise user **115** typically only has a need to access a subset of the enterprise resources **130**, ordinarily based upon the user's duties or role within the enterprise. Therefore, since there is no need to provide the user **115** with mobile device access to many of the resources **130**, doing so can expose the enterprise to unnecessary security risks. For example, an enterprise may wish to prevent many of the users **115** from using their mobile devices **120** to access highly sensitive, confidential information of the enterprise, particularly if the users do not need to access such information to perform their duties toward or associated with the enterprise. This can prevent, for example, a disgruntled employee from harming the enterprise by accessing and perhaps disseminating sensitive enterprise-related information. Also, applications and files installed on the mobile devices **120** can have malware or viruses that can get transferred to the enterprise's computer system **110** or that can upload or steal sensitive information. Limiting mobile device access to specific enterprise resources **130** can prevent the malware and viruses from infecting other enterprise resources **130**. As discussed below, the mobile device management system **126** and secure mobile gateway **128** preferably address these issues by enabling an enterprise to restrict mobile device access only to authorized enterprise resources **130**, in a way that is customizable based on user properties, mobile device properties, and/or the enterprise resources **130** for which mobile device access is requested.

(112) With the proliferation of mobile devices and the desire to use existing applications for the mobile devices, a need exists to take action at a network level to provide controlled access to enterprise resources. Moreover, as enterprises implement BYOD (bring your own device) or BYOT (bring your own technology) policies, a need exists for flexibility while addressing the increasingly complex task of protecting enterprise resources and sensitive enterprise data. Such flexibility can include allowing a number of different mobile devices and/or applications running on such mobile devices to access enterprise resources while providing a desired level of control over such access to enterprise resources. As one example, it can be desirable to allow mobile devices **120** having a variety of different email clients to access enterprise resources and to enable the enterprise to implement certain protections, such as denying some access requests in certain circumstances configurable by the enterprise and/or encrypting at least a portion of data provided to email clients of a mobile device based on enterprise policies, when allowing the various email clients to access enterprise data. Allowing a variety of existing mobile applications to access enterprise resources can eliminate the need to develop proprietary applications and/or modify existing applications in order to access enterprise resources. At the same time, implementing a desired level of control over access to enterprise data can allow an enterprise to strike a balance between protecting enterprise data and enabling users to access the enterprise data on a mobile device **120**.

(113) A secure mobile gateway **128** can assist in flexibly protecting sensitive enterprise data accessed by mobile devices **120**. The secure mobile gateway **128** can monitor and log traffic

between one or more enterprise resources **130** and a mobile device **120**. The secure mobile gateway **128** can apply rules to implement enterprise policies applied to a selected mobile device **120**. Based on a particular protocol, the secure mobile gateway **128** can take actions to implement enterprise policies as applied to the selected mobile device **120** that is requesting access to an enterprise resource **130**. Thus, in the context of a mobile device **120** communicating with an enterprise computing system **110**, the secure mobile gateway **128** can take actions associated with a protocol and certain conditions to provide access to enterprise resources **130**. It will be understood that the secure mobile gateway **125** can control traffic associated with any suitable protocol, for example, the protocols described herein. Any combination of the policies, rules, and remedial action described herein can be implemented by the secure mobile gateway **128**. Moreover, the secure mobile gateway **128** can implement a variety of other policies, rules, remediation actions, or any combination thereof in accordance with the principles and advantages described herein.

(114) The secure mobile gateway **128** can include a gateway filter that functions as a protocol analyzer and a rules remediator. The gateway filter can detect a defined protocol, such as ActiveSync or HTTP(s), associated with enterprise traffic. The gateway filter can implement gateway rules that take certain actions for a particular protocol and one or more conditions. For example, when a request from a mobile device **120** to access an enterprise resource **130** is an ActiveSync request, the gateway filter can implement rules specific to the ActiveSync protocol. In this example, the conditions can be that the mobile device **120** is associated with an executive of the enterprise that is likely to receive sensitive enterprise information. The gateway filter can then take the action of encrypting attachment data before sending the data to the mobile device of the executive. In another example, the gateway filter can deny a request by a mobile device **120** to access an enterprise resource **130** due to the mobile device **120** having a certain application installed thereon.

(115) FIG. 4 schematically illustrates the architecture and operation of an embodiment of the secure mobile gateway **128** of FIG. 1A. The secure mobile gateway **128** can be implemented at or control any junction in a computing system through which protocol traffic flows. For instance, the secure mobile gateway **128** can be implemented in a firewall, an enterprise server (such as an application server), or between a firewall and an enterprise server. As another example, a virtual secure mobile gateway **128** can communicate with an enterprise server (e.g., via a Power Shell interface) to implement enterprise access policies for requests from mobile devices. The secure mobile gateway **128** can be implemented as a plugin to a firewall server **400** of the enterprise network, such as the firewall **122** of FIG. 1A. For instance, most of the firewall products sold by Microsoft Corporation™ run Internet Information Services (IIS), which is a service that processes web server requests. IIS has plugin architecture that allows embodiments of the gateway **128** to be plugged into the firewall products. One particular API of IIS is the Internet Server Application Programming interface (ISAPI). Embodiments of the secure mobile gateway **128** can be integrated with various firewall technologies, such as Microsoft Forefront Threat Management Gateway (TMG), Microsoft Forefront Unified Access Gateway (UAG), Microsoft Forefront Identity Manager 2010 (FIM 2010), Microsoft ISA 2006, Barracuda firewalls, Sonic firewalls, Cisco firewalls, and others. When the secure mobile gateway **128** is integrated with certain firewalls, such as TMG, the secure mobile gateway **128** can be implemented by one or more enterprise resources **130** (FIG. 1E) or at least one device configured to control the one or more enterprise resources **130**. In certain embodiments, such as for enterprises that do not use a perimeter firewall **122** (FIG. 1A), the

secure mobile gateway **128** can be integrated with interior servers of the enterprise, such as Client Access Servers (“CAS servers”) that support ActiveSync. In some other embodiments, the secure mobile gateway **128** can be implemented by at least one computing device configured to communicate with a firewall server. In this way, the secure mobile gateway **128** can control some or all of the traffic through a firewall without the firewall server being modified. This can enable an enterprise to implement the secure mobile gateway **128** in combination with an unmodified third party firewall.

(116) Although the secure mobile gateways **128** of FIGS. 1A-1E are shown as controlling traffic related to a single enterprise system **110** for illustrative purposes; it will be understood that one secure mobile gateway **128** can be implemented to handle requests associated with two or more different enterprise systems **110**, including systems **110** of distinct companies or other enterprises. When handling requests associated with a plurality of different enterprise computing systems **110**, the secure mobile gateway **128** can implement different rules for each of the different enterprise computing systems **110**. For example, one secure mobile gateway **128** can be implemented for several different enterprise email systems each having different email policies. In some of these embodiments, the secure mobile gateway **128** can communicate with different mobile device management systems **126** of enterprise computing systems **110** of different companies.

(117) The illustrated secure mobile gateway **128** in FIG. 4 includes a gateway filter **401** that can be configured to receive and process enterprise access requests **402** from mobile devices **120**, each request being formatted according to a protocol supported by the secure mobile gateway **128**. The gateway filter **401** can be embedded into a firewall server **400**. In some other implementations, the gateway filter **401** can be implemented to control traffic through a separate firewall sever. The gateway filter **401** can be configured to allow the access request **402** to reach an enterprise resource **130**, or deny the request **402**. The gateway **128** can be configured to support one or more different request protocols, such as ActiveSync requests, SharePoint requests, EWS requests, SAP requests, and/or requests associated with various other web server applications. In one embodiment, blocks **401**, **404**, **406**, **410** and **412** in FIG. 4 represent components that can be added (e.g., as part of a firewall plug-in) to a commercially-available firewall or firewall server **400** to implement the secure mobile gateway **128**.

(118) Take for example the case of a secure mobile gateway **128** configured to process ActiveSync requests to synchronize enterprise system data with mobile devices **120**. ActiveSync is a well-known mobile data synchronization technology and protocol developed by Microsoft™. One implementation of ActiveSync, commonly known as Exchange ActiveSync (or EAS), provides push synchronization of contacts, calendars, tasks, and email between ActiveSync-enabled servers and mobile devices. The gateway filter **401** can be configured to intercept every incoming request **402**, determine if it is an ActiveSync request, and consult a database of gateway rules **404** to determine if the gateway filter **401** should allow or deny the request. The request can be, for example, an HTTP request. The database of gateway rules **404** can be a local database stored on the enterprise firewall server **400**. In the case of an allowed ActiveSync request **402**, the gateway filter **401** can send the request to the enterprise resource **130**, which can comprise a Microsoft Exchange server.

(119) The gateway filter **401** can detect whether the request **402** is an ActiveSync request by inspecting the request's header and possibly body to detect indicia of the ActiveSync protocol. Each ActiveSync command typically comprises a web Uniform Resource Locator (URL) issued by

the mobile device **120**. After the URL, the request typically includes query parameters and an ActiveSync command. To illustrate, consider the following ActiveSync request:  
 http://myDomain.com/Microsoft-Server-ActiveSync?  
 User=XXX&DeviceId=XXX&DeviceType=XXX&Cmd=Ping

The secure mobile gateway **128** can obtain the DeviceId and DeviceType from the URL, the UserAgent parameter from the HTTP header, the authenticated User parameter from the HTTP session, and the Cmd parameter. The secure mobile gateway **128** can be configured to filter the requests **402** based on one or more of these properties. Note that the ActiveSync protocol also allows for the URL parameters to be encoded in an alternate form using a base64 encoded representation. In the above example, the gateway **128** can determine that the request is on ActiveSync request from the string “Microsoft-Server-ActiveSync.”

(120) A gateway rule **404** can include one or more values of properties of a mobile device request **402** formatted according to a protocol supported by the secure mobile gateway **128**. Such properties can comprise URL parameters, header values, commands, etc. The gateway filter **401** can be configured to filter the requests **402** based at least partly on these properties. In the case of ActiveSync, the request properties can include DeviceID and Device Type (taken from the request URL), the User and UserAgent parameters (taken from the HTTP headers), and one or more ActiveSync command parameters (ActiveSync defines numerous different commands, such as sync mailbox, send mail, get attachment, etc.). A gateway rule **404** can specify conditions under which a request is to be granted or denied by the gateway filter **401**. Such a condition can involve a logical expression and/or combination of one or more values of the request properties of a protocol supported by the secure mobile gateway **128**. For example, a gateway rule **404** can cause the gateway filter **401** to block all ActiveSync requests having any one of a particular group of DeviceID values, and which issue the get attachment command (for downloading an email attachment). As this example illustrates, a gateway rule **404** can identify one or more mobile devices **120** and/or users **115**. As this example also illustrates, a gateway rule **404** can allow or deny access based on what a mobile device **120** is attempting to do or achieve by issuing an access request **402** to the enterprise system **110**. Through the secure mobile gateway **128**, an operator of the secure mobile gateway **128** can customize gateway rules **404** for a particular enterprise computing system **110**.

(121) In some embodiments, the secure mobile gateway **128** can be configured to inspect the body or “payload” of a request **402** to access an enterprise resource **130**, in order to detect additional information that may be useful in evaluating whether to grant or deny the request. The payload may provide information about the specific data being requested, how the mobile device application will use the requested data, and so on. Access policies **218** of the device management system **126** can be created to regulate or restrict access based on such information. For example, the secure mobile gateway **128** may inspect the payloads of messages that are formatted according to selected protocols such as ActiveSync, SharePoint, SAP, and/or those based on HTTP. The secure mobile gateway may also modify protocol metadata in these messages to implement various security-related features. For instance, as described below under the heading “protecting attachment data,” the secure mobile gateway may be configured to inspect the payloads of ActiveSync or other requests **402** to determine whether they are associated with messages that include attachments (such as email attachments); the secure mobile gateway **128** may also encrypt some or all of the identified attachments to prevent them from being stored in an unencrypted format on the associated mobile devices **120**.

(122) The gateway rules **404** can be based on data provided by the mobile device management system **126** and/or data provided by an operator of the secure mobile gateway **128**. The mobile device management system **126** can convert high level rules into relatively simple (lower level) rules and provide the relatively simple rules to the secure mobile gateway **128** for application to monitored traffic. The secure mobile gateway can also implement rules provided by or based on inputs from an inference engine of a meta-application **150** and/or a meta-application portion **151** in the cloud **156** (such as the inference engine **824** of FIG. 8) The rules may, in some embodiments, be generated using the methods and components (including symptom logic) described in Qureshi '526.

(123) The gateway rules **404** can take many different forms and can be written in a variety of programming languages, such as XML. In one embodiment, a gateway rule **404** includes a list of “groups” plus an indication of a default “action” (e.g., grant or denial of the access request or whether to encrypt attachment data). In this context, a group is a collection of “group members” plus a corresponding action for the group. A group member can be a set of values of one, some, or all of the properties of a mobile device request **402**. Each group member can match an incoming mobile device access request **402** by any value of a property of a request protocol supported by the secure mobile gateway **128**. The gateway filter **401** can match an inbound request **402** with a group member by matching all of the property values of the group member to the corresponding property values of the request **402**. If a group member does not include any values for one or more possible request properties, the gateway filter **401** can determine that it does not matter what are request's values for those particular properties, in other words, a group member can effectively specify “any” or “don't care” for one or more request properties. Hence, different group members can correspond to the same mobile device **120** or user **115**. For example, for a secure mobile gateway **128** that supports ActiveSync, the group members can match inbound HTTP requests **402** by any combination of DeviceID, User, User Agent, and DeviceType, as well ActiveSync Cmd values.

(124) Here is one example of a gateway rule **404**: `<Policy id="Static+ZDM Rules:Block Mode" default-action="Deny" missing-param-action="Allow"> <GroupRef id="StaticAllow" action="Allow"/> <GroupRef id="StaticDeny" action="Deny"/> <GroupRef id="ZdmDeny" action="Deny"/> <GroupRef id="ZdmAllow" action="Allow"/>`

This gateway rule specifies a default action as a denial of an inbound access request received by the secure mobile gateway **128** from a mobile device **120**. This gateway rule also specifies a “StaticAllow” group whose action is “Allow,” a “StaticDeny” group whose action is “Deny,” a “ZdmDeny” group whose action is “Deny,” and a “ZdmAllow” group whose action is “Allow.” Together a group and an action can be a subrule. The StaticAllow and StaticDeny groups and their associated action are examples of subrules that are local to the secure mobile gateway **128**. Such subrules can be modified by an operator of the secure mobile gateway independent of the mobile device management system **126**. The ZdmDeny and ZdmAllow groups and their associated actions are examples of subrules received from the mobile device management system **126**. The priorities of the rules can be set in any suitable order. In the example above, the StaticAllow and StaticDeny groups and their associated actions are prioritized over the ZdmDeny and ZdmAllow groups and their associated actions. In this way, an operator of the secure mobile gateway **128** can override subrules provided by the mobile device management system **126**.

(125) A number of other sub-rules from various sources can be implemented with or in place of the above example subrules provided above. A gateway rule **404** can alternatively or additionally define



a number of other actions for the secure mobile gateway **128** to take for various groups, such as encrypting attachments for certain groups, modifying a body of a message (such as an email) for certain groups, blocking a mobile device **120** from certain groups from receiving messages in certain locations, etc.

(126) To enforce the example gateway rule **404** provided above, the secure mobile gateway **128** can access all of the group members of these four groups. Here is an example of a “group list” that can be provided to the secure mobile gateway **128** (e.g., by a provider **408** as described below):

```
<GroupList> <Group id="StaticAllow"> <ExternalMemberList path="allow.xml"/> </Group> <Group id="StaticDeny"> <ExternalMemberList path="deny.xml"/> </Group> <Group id="ZdmAllow"> <ManagedMemberList path="zdm.xml" groupId="allow"/> </Group> <Group id="ZdmDeny"> <ManagedMemberList path="zdm.xml" groupId="deny"/> </Group> </GroupList>
```

This group list defines locations of files containing lists of group members, where each group member is identifiable by one or more values of properties of an access request **402** of a protocol supported by the gateway **128**. For the ActiveSync protocol, each group member can include values of DeviceID, User, UserAgent, DeviceType, and Cmd parameters.

(127) When the secure mobile gateway **128** receives an inbound mobile device request **402**, the gateway filter **401** can read the values of properties of the request **402** and match them against the corresponding property values of group members of the group list. If there is a match, the gateway filter **401** can enforce the action associated with the group. If there is no match, the gateway **128** performs the same analysis for the next group listed in the gateway rule **404**. If there are no matches with any of the groups of the gateway rule **404**, the gateway **128** enforces the default action. To the extent that there may be conflicts between the groups of the gateway rule **404**, the secure mobile gateway **128** can be configured to give priority to groups that appear earlier in the rule.

(128) Referring still to the above example of a gateway rule **404**, after the gateway filter **401** reads the values of the request properties, the gateway filter **401** reads the property values of the group members of the StaticAllow group and determines if any of them matches any property values of the request **402**. For example, for a gateway **128** supporting ActiveSync, the DeviceID of the request **402** could match the DeviceID of one of the group members. If there is such a match, the gateway filter **401** enforces the action associated with the StaticAllow group, which is to allow the request **402** to pass through the firewall. If there is no match with any property values of any group member of the StaticAllow group, then the gateway filter **401** reads the property values of the group members of the StaticDeny group and determines if any of them matches any property value of the request **402**. If there is a match, then the gateway filter **401** enforces the action associated with the StaticDeny group, which is to deny the request **402**. If there is no match with any property values of any group member of the StaticDeny group, then the gateway filter **401** reads the property values of the group members of the ZdmDeny group and determines if any of them matches any property value of the request **402**. If there is a match, then the gateway filter **401** enforces the action associated with the ZdmDeny group, which is to deny the request **402**. If there is no match with any property values of any group member of the ZdmDeny group, then the gateway filter **401** reads the property values of the group members of the Zdm Allow group and determines if any of them matches any property value of the request **402**. If there is a match, then the gateway filter **401** enforces the action associated with the ZdmAllow group, which is to allow the request **402**. If there is no match with any property values of any group member of the ZdmAllow group, then the

gateway filter **401** enforces the default action, which is to deny the request **402**.

(129) The secure mobile gateway **128** can include a gateway configuration service **406** that allows a user (e.g., administrators, IT personnel, etc.) to view, edit, and/or create gateway rules **404**, and then save them in the local database. The configuration service **406** can be configured to allow an administrator to set “static” gateway rules **404**. A static gateway rule can identify a mobile device **120** or groups of devices **120** that are always to be granted access or denied access. For example, the administrator can input a rule **404** that specifies that the mobile device **120** (e.g., identified by ActiveSync DeviceId) used by the CEO of the enterprise is always granted access to the enterprise network **110**. As another example, the administrator can input a gateway rule **404** that denies access to devices **120** that are known to have malware or incompatibilities with the enterprise network **110**. The configuration service **406** can also be configured to allow the user to adjust various other settings and features of the gateway **128**, including any of those described herein.

(130) The gateway configuration service **406** can allow for gateway rules **404** to be statically defined further, the secure mobile gateway **128** can be configured to receive gateway rules **404** from one or more external “providers” **408**. A provider **408** can be any entity authorized by the gateway **128** to provide gateway rules **404** for regulating access to the enterprise network **110**. The gateway **128** can have an open architecture that permits IT personnel of the enterprise to add, remove, and configure the providers **408**. Preferably, the gateway **128** supports any number of providers **408**. The mobile device management system **126** can be one of the providers **408**. Another provider **408** can be the meta-application **150** that manages some or all of the enterprise network **110**, such as the “backend” subnetwork behind the firewall **124** (FIG. 1A). Exemplary meta-application embodiments are described in Qureshi '536, and an at least partially cloud-based meta-application (which can be a provider **408**) is described below with reference to FIG. 8.

(131) Each provider **408** can be configured to create and send one or more gateway rules **404** to the gateway **128**. The providers **408** can be configured to query their own databases of information to create the rules **404**. Compared to the gateway **328**, a provider **408** can have significantly more data on which to grant or deny mobile device access requests **402**, such as information about the users **115** and/or mobile devices **120**. For instance, the illustrated mobile device management system **126** (FIG. 2) can include a gateway rule generator **222** configured to create and edit gateway rules **404** based on the enterprise access policies **218** and the mobile device information **204** (including the mobile device properties **208**, user-device assignment records **210**, and user roles **206**), and then send the rules **404** to the gateway configuration service **406** of the gateway **128**. The access policies **218** can comprise high level rules specifying whether mobile devices **120** can access the enterprise network or specific resources **130** thereof. The gateway rule generator **222** can be configured to read an access policy **218** and then query the mobile device information **204** to find specific devices **120** or users **115** that match the criteria of the access policy **218**. From the detected devices and users, the gateway rule generator **222** can generate device- or user-specific gateway rules **404** that enforce the policy **218**. The mobile device management system **126** can be configured to send lists of users **115** or devices **120** (e.g., in the form of “group members,” as discussed above) for which enterprise access is to be granted or denied, and send those lists to the gateway **128**. The gateway **128** can be configured to use the lists to enforce the gateway rules **404**.

(132) For example, if an access policy **218** requires that all Android™ mobile devices **120** having a Facebook™ application installed thereon are to be denied access to the enterprise network **110**,

the gateway rule generator **222** can query the mobile device information **204** to obtain a list of such devices **120**. The gateway rule generator **222** can create one or more gateway rules **404** that instruct the gateway filter **401** to deny access to the listed devices **120**, and then send the created rules to the gateway configuration service **406**. In the case of a gateway **128** that supports the ActiveSync protocol, the gateway rule generator **222** can, for example, generate a list of ActiveSync DeviceID's of Android™ mobile devices **120** having a Facebook™ application installed thereon, and then create one or more gateway rules **404** instructing denial of access for such devices.

(133) As the above example illustrates, an access policy **218** can comprise any logical combination of conditions that can be transformed into a gateway rule **404**. The policy **218** in the above example represents a conjunction (AND operator) of two conditions; (1) that the mobile device is an Android™ device, and (2) that the device has a Facebook™ application installed thereon. It will be understood that a logical combination of conditions can include OR operators, XOR operators, NOR operators, NAND operators, THEN operators, mathematical operators (including “less than” and “greater than”), and any other suitable operators.

(134) In addition to generating gateway rules **404** based at least partly on the mobile device information **204**, the gateway rule generator **222** can be configured to generate the rules based at least partly on a locally stored database of information received from the meta-application **150**, such as a model of the enterprise network **110** and mobile devices **120**, or detected “features,” “problems,” and “root causes” (see below discussion of meta-application). In an embodiment in which the meta-application **150** manages Microsoft Exchange™, the information received from the meta-application **150** can include ActiveSync partnership data.

(135) As noted above, the meta-application **150** (FIGS. 1A-C) can be a direct provider **408** of gateway rules **404** to the secure mobile gateway **128**. The meta-application **150** can generate gateway rules **404** based on various data associated with the enterprise network **110**, users **115**, mobile devices **120**, or any combination thereof. The meta-application **150** can have access to various information on which gateway rules **404** can be based. For example, in support of its management tasks, the meta-application **150** can be configured to conduct “discovery” of the enterprise network **110** and mobile devices **120** to create and maintain a queryable model thereof. Additionally, the meta-application **150** can be configured to predict or detect “features,” “problems,” and/or “root causes,” as these terms are used in Qureshi '536. New gateway rules **404** can be created based on the model, the detected features, problems, and root causes, and other information detected or computed by the meta-application **150**. The management and gateway control capabilities of embodiments of the meta-application **150** are described more fully below.

(136) The illustrated gateway configuration service **406** is configured to receive gateway rules **404** from the providers **408**, and save them in the local storage of rules **404**. The gateway configuration service **406** can be implemented as a web service and can have a list of all of the providers **408** associated with the gateway **128**. The gateway configuration service **406** can be configured to periodically (e.g., every 24 hours, hour, or few minutes, etc.) query the providers **408** for any new gateway rules **404** that are available. In this sense, the configuration service **406** acts as a collector of gateway rules **404** for the gateway **128**.

(137) Protecting Attachment Data

(138) Mobile devices are pervasively used to check emails, including emails associated with an enterprise email account. Some emails include attachments containing sensitive data. These attachments are often stored on a mobile device when a user checks email using the mobile device. The attachment data stored on the mobile device can be compromised in a number of ways. When the attachment data is compromised, sensitive data associated with the enterprise can be exposed. Accordingly, a need exists to protect attachment data associated with an enterprise that is stored on a mobile device. This need may vary depending upon the individual's position or role in an associated organization; for example, the need to protect the attachments to messages received by a corporation's executives may be greater than the need to protect the attachments received by the corporation's IT staff. In addition, if the company's enterprise supports the use of other messaging protocols (SMS, MMS, instant messaging, AS, EWS, OWA, proprietary messaging protocols, etc.) to send documents, this need may extend to such protocols.

(139) Aspects of certain embodiments relate to protecting enterprise attachments stored on a mobile device, such as enterprise email attachments, from being compromised. The attachments may include, for example, Word documents, Excel documents, PowerPoint presentations, text files, and documents and files created with other application programs. According to the principles and advantages described herein, attachment data can be protected on mobile devices with non-proprietary email applications, such as an email application that comes pre-installed on or is later installed on an iPhone or an Android device. As such, features related to protecting attachment data can be implemented with any suitable email client. Enterprise attachments can be protected prior to being stored on a mobile device such that the protected attachment data remains safe even when data stored on the mobile device is compromised. The attachment data can be securely stored in the general file system of a mobile device. Attachment data can be identified and stripped from an email message. The attachment data can be encrypted and then sent to the mobile device as encrypted attachment data. A secure mobile gateway can be configured to encrypt attachment data and provide the encrypted attachment data to the mobile device. According to some embodiments, an encrypted attachment key can also be sent with the encrypted attachment data. Secure, policy-based access to the protected attachment data can be provided. An enterprise agent can decrypt the encrypted attachment data. For example, the enterprise agent can decrypt the encrypted attachment key and then use the attachment key to decrypt the encrypted attachment data. When the mobile device is compromised, the enterprise agent can be configured such that the encrypted attachment data remains encrypted. For example, the enterprise agent can destroy and/or invalidate the attachment key. Without the device key to decrypt the encrypted attachment key, the encrypted attachment data can remain encrypted. When the encrypted attachment data is stored on removable memory, such as a secure digital (SD) card, the attachment data can remain secure when the removable memory is removed from the mobile device since the attachment data is encrypted.

(140) In one embodiment, enterprise users access their enterprise email accounts from their mobile devices using the enterprise agents installed on their mobile devices. The enterprise agent can operate transparently to an email client and an enterprise email server. The enterprise agent may require an end user to login before accessing the user's email account and/or before an opening encrypted attachment. The enterprise agent can register with a platform of the mobile to device. When the user opens an encrypted attachment, the enterprise agent can be invoked. An encrypted attachment can be identified by a particular file suffix. After being invoked, the enterprise agent can decrypt the attachment transparently to the user.

(141) Although the system is described herein primarily in the context of email attachments for illustrative purposes, it will be understood that the principles and advantages described herein may be applied to any other suitable communication protocol that can be used to send an attachment from an enterprise resource to a mobile device. For example, any combination of features of protecting email attachments can be applied to protecting an attachment to an instant message, text message (for example, an SMS), or the like. It will be understood that, in certain embodiments, the policy based encryption of attachment data described herein can be implemented in combination with other encryption applied to the attachment data. Moreover, although attachment data is described herein as being encrypted for illustrative purposes, it will be understood that the principles and advantages described herein may be applied to any other suitable way of protecting attachment data on a mobile device, such as scrambling and the like. Furthermore, the principles and advantages described herein with reference to attachment data can be applied to protecting some or all of a message, such as an email message.

(142) With reference to FIGS. 1A-1C, attachment data can be protected in any of the enterprise computing systems and mobile devices described herein. Attachment data can be protected in any system with a mobile device **120** in communication with a secure mobile gateway **128**, which is in communication with an enterprise resource **130**, such as an enterprise email server. Typically, a mobile device **120** communicates with the secure mobile gateway **128** via an external firewall **122** (FIG. 1A-C). In certain embodiments, the secure mobile gateway **128** can be implemented by an enterprise resource **130**. In one embodiment, as discussed above, the secure mobile gateway **128** can be deployed between an external firewall **122** and an internal firewall **124** of the enterprise system **110**. The mobile device **120** and/or the secure mobile gateway **128** can be in communication with a mobile device management system **126**. The mobile device management system **126** can be configured to implement functionalities related to encryption keys for encrypting attachment data, for example, as will be described in more detail below. According to certain embodiments, the secure mobile gateway **128** and/or agents of the mobile device **120** can be configured to decrypt attachments.

(143) The secure mobile gateway **128** can be configured to detect attachments in incoming and/or outgoing email messages. In some embodiments, the secure mobile gateway **128** can inspect and/or modify a data payload being transmitted to and/or from a mobile device **120**, such as an ActiveSync data payload. The incoming and/or outgoing data payload can be in WBXML, a binary version of XML optimized for low bandwidth environments. The secure mobile gateway **128** can include a parser and generator that operate on the data payload. For example, the parser and generator can process WBXML. In this example, the parser and generator can process data in accordance with the ActiveSync WBXML schema. The secure mobile gateway **128** can programmatically identify which character encoding schemes are being used. WBXML messages may include MIME payloads. The secure mobile gateway **128** can include a MIME parser and generator configured to construct and deconstruct this data. With a parser and generator, the secure mobile gateway **128** can identify an attachment so that the attachment can be separated from an email and secured.

(144) According to one embodiment, to intercept and/or modify incoming and/or outgoing data payloads, the secure mobile gateway **128** can register with an Internet Server Application Programming Interface (ISAPI) or other server to receive notifications. The received notifications can correspond to various processing stages. The secure mobile gateway **128** can maintain a

context state to track the various processing stages of a request. The secure mobile gateway **128** can chunk and de-chunk request and response data.

(145) The secure mobile gateway **128** can modify, or otherwise mark, an attachment and/or a reference to an attachment. For instance, the secure mobile gateway **128** can append a particular suffix, such as “.zendata” to the names of encrypted attachments to signify that they should be preprocessed by the enterprise agent **320**. As another example, the secure mobile gateway **128** can append a particular suffix, such as “.zendata” to the names of a reference to an attachment to signify that the attachment should later be encrypted prior to being delivered to a mobile device **120**. The secure mobile gateway **128** can adjust a header attribute (for example, in MIME data) to identify that attachment data is encrypted as an alternative to or in addition to appending a suffix to a file or a link. The secure mobile gateway **128** can encrypt and/or decrypt attachment data and/or attachment keys. The secure mobile gateway **128** can be configured to initiate communication with the mobile device management system **126** to obtain device properties, device policies, public device keys, the like, or any combination thereof.

(146) Device Agents, such as an operating system and/or the enterprise agent **320** (FIG. 3), of the mobile device **120** can be configured to register the mobile device **120** with the enterprise system **110** and to handle the encrypted data file type (for example, “.zendata”), decrypt the attachment data, and invoke the appropriate rendering and/or processing on the decrypted attachment data. The device agents of the mobile devices **120** can be configured to obtain and/or manage a private device key.

(147) The mobile device management system **126** can generate a device key. The mobile device management system **126** can distribute the device key or a portion thereof to a mobile device **120** and/or to a secure mobile gateway **128**. A suitable key can be used by the secure mobile gateway **128** to encrypt attachment data and another suitable key can be used by the mobile device **120** to decrypt the encrypted attachment data. For instance, the mobile device **120** can receive a private device key from the mobile device management system **126**, and the secure mobile gateway **128** can receive a public device key from the mobile device management system **126**. The secure mobile gateway **128** need not include special key management and/or key archiving, according to some embodiments. When an attachment is encrypted and a corresponding device key is subsequently destroyed, invalidated, and/or replaced, the encrypted attachment may be unrecoverable.

(148) A number of different rules and/or policies related to protecting attachments can be implemented by the enterprise system **110**. For example, features related to protecting attachments can be implemented based on one or more properties of a particular mobile device **120** that receives attachment data. In this example, certain mobile devices **120** with particular software applications installed thereon can enable attachment protection as a default. As another example, protecting attachments can be enabled and/or disabled based on one or more properties of a user of a mobile device **120** that is receiving the attachment data. For instance, an employee of the enterprise that is likely to receive attachments with sensitive and/or confidential information, such as an executive and/or a member of the legal team, can have attachments encrypted as a default. By contrast, an employee who is unlikely to receive attachments with sensitive and/or confidential data can have attachment protection disabled as a default. As yet another example, attachments can be protected based on one or more properties of the attachment itself such as file name, file type, data included in the attachment, or any combination thereof. For instance, the attachment can

be searched for one or more key words and phrases, such as “confidential,” “proprietary,” “attorney-client privileged,” etc., and if such a key word or phrase is found the attachment can be encrypted. It will be appreciated that rules and/or policies can allow the enterprise to configure features related to protecting attachments in a flexible way, based on mobile device properties, user properties, attachment properties, the like, or any combination thereof. Any of the rules and/or policies related to protecting attachments can be implemented in combination with any of the other rules described herein, rules packages described herein, policies described herein, the like or any combination thereof.

(149) Moreover, any of these rules and/or policies related to protecting attachments can be implemented by any suitable computer hardware described herein. For example, the secure mobile gateway **128** can be configured to enable and/or disable features related to protecting attachments, such as encrypting attachments, globally. The secure mobile gateway **128** can obtain policies from the mobile device management system **126** related to protecting attachments. The mobile device management system **126** can be configured to manage any selection policy related to protecting attachments, such as which mobile devices **120** receive encrypted attachments and/or what type of attachments are encrypted.

(150) In a typical use case scenario, a mobile device **120** can receive an email with an attachment from an enterprise email server, such as an Exchange server, in accordance with an ActiveSync protocol. The mobile device **120** can retrieve encrypted email attachments such that the attachment data saved on the mobile device **120** is protected with device-specific keys. The saved attachment data can only be decrypted using an enterprise agent **320** running on the mobile device **120**, according to certain embodiments. For instance, the enterprise agent **320** can control and manage the device-specific key used to decrypt the attachment data. A mobile device management system **126** can select or specify the mobile devices **120** and/or users for which attachments are to be encrypted. For example, selected mobile devices **120** may be excluded from receiving encrypted attachments based on one or more mobile device management system **126** policies and/or one or more secure mobile gateway **128** policies.

(151) Encrypted attachments that are forwarded and/or sent from a mobile device **120** can be decrypted by the secure mobile gateway **128** before being delivered to new recipient(s). As a result, a new recipient within the enterprise can receive the attachment based on its policy. When the new recipient is a mobile device **120** with an enterprise agent **320**, the attachment data can be re-encrypted for that particular recipient mobile device **120**. When the new recipient is an unmanaged mail client, the attachment data can be delivered unencrypted.

(152) Example communications and events related to delivering an email with an attachment from an enterprise resource **130** to a mobile device **120** via a secure mobile gateway **128** will be described with reference to FIG. 31. Then example communications and events related to forwarding and/or sending an email from a mobile device **120** through a secure mobile gateway **128** and an enterprise resource **130** will be described with reference to FIGS. 32 and 33.

(153) FIG. 31 illustrates an example of a process by which an email message with an encrypted attachment can be delivered to a mobile device **120**. In this process, the secure mobile gateway **128** identifies an attachment to an email message being delivered to a mobile device **120**. The secure mobile gateway **128** can encrypt the attachment data prior to transmitting the attachment to a mobile device **120**. The attachment data can be encrypted and sent to the mobile device **120**

either when the email message is sent to the mobile device **120** or in response to a user of the mobile device **120** attempting to open the attachment. The secure mobile gateway **128** can also encrypt an attachment key associated with the encrypted attachment data. In event A of FIG. 31, the mobile device **120** transmits a sync request to the secure mobile gateway **128**, for example, by way of the ActiveSync protocol. Then the secure mobile gateway **128** transmits a sync request to an enterprise resource **130** in event B. The enterprise resource **130** may, for example, be an enterprise email server, such as a Microsoft Exchange Server. In event C, the enterprise resource **130** sends a sync response to the secure mobile gateway **128**. The sync response can include email messages to be delivered to the mobile device **120**.

(154) In event D of FIG. 31, the secure mobile gateway **128** processes an email message being sent to the mobile device **120**. Such processing can include determining whether the email message includes an attachment. For instance, when the enterprise email server sends a response that includes email messages in event C, the secure mobile gateway **128** can parse the response and programmatically identify attachments. For example, attachments can be identified from a name and a server reference in a WBXML message. As another example, attachments can be identified by being inlined in a MIME message. The secure mobile gateway **128** can mark and/or modify the attachment in a detectable way. For instance, the secure mobile gateway **128** can rename an attachment. In one embodiment, a suffix can be appended to the name of an attachment document. For example, an attachment with an original name of “Foo.xyz” can be renamed to “Foo.xyz.zendata”.

(155) An attachment can also be encrypted in event D of FIG. 31 when the attachment is inlined, such as in a MIME message, or otherwise included with the email in a substantially complete form. Any suitable attachment can be encrypted, such as a document (for example, a Word document, a PDF document, etc.). The secure mobile gateway **128** can also encrypt an attachment key associated with the attachment. The attachment key can be generated by the secure mobile gateway **128** and/or received by the secure mobile gateway **128** from the mobile device management system **126**, for example, as discussed in more detail with reference to FIG. 34. The encrypted attachment key can be included in the new attachment file with the encrypted attachment data.

(156) The sync response from the enterprise email server and/or another enterprise resource **130** as modified by the secure mobile gateway **128** is delivered to the mobile device **120** in event E of FIG. 31. This can provide the mobile device **120** with encrypted attachment data in some circumstances. For example, MIME messages with embedded, encrypted attachments can be provided to the mobile device **120**. For some other types of messages, emails with renamed attachment references that can be used with subsequent requests to retrieve attachments are provided to the mobile device **120**.

(157) For emails with attachment references, such as WBXML emails, a request to retrieve attachments can be sent from the mobile device **120** in event F of FIG. 31. Then, in event G, the secure mobile gateway **128** can detect that the attachment reference has been marked and/or modified. For example, the secure mobile gateway **128** can programmatically identify that that attachment reference includes a particular suffix previously added by the secure mobile gateway **128**, such as “zendata” in the example provided above. The secure mobile gateway **128** can then unmap the attachment reference so that the enterprise email server and/or another enterprise resource **130** can process a request to provide the attachment. In some embodiments, this can



involve a URL rewrite. In event H, the secure mobile gateway **128** requests the attachment from the enterprise email server and/or another enterprise resource **130**. Then the enterprise email server delivers the attachment to the secure mobile, gateway **128** in event I. The secure mobile gateway encrypts the attachment in event J. The secure mobile gateway **128** can also encrypt an attachment key associated with the attachment. The encrypted attachment key can be included in a file with the encrypted attachment data and/or provided separately to the mobile device **120**. Then in event K, the secure mobile gateway **128** delivers the encrypted attachment data to the mobile device **128**.

(158) Email messages and associated attachments stored on a mobile device **120** can be forwarded from the mobile device **120** to a new recipient. FIGS. 32 and 33 illustrate examples of processes of forwarding an email message from a mobile device **120**. In the example illustrated in FIG. 32, a secure mobile gateway **128** can function as a pass through in transmitting a request to forward an email message with an attachment from the mobile device **120** to an enterprise resource **130**, such as an enterprise email server. The process illustrated in FIG. 32 can be implemented in situations in which the email with the attachment is stored on the enterprise email server or in which the enterprise email server otherwise has access to the attachment data. For instance, the mobile device **120** can send information identifying the attachment, such as a reference, to the enterprise email server via the secure mobile gateway **128**. In some embodiments, the process of FIG. 32 can be implemented with a Smart Forwarding feature in which a marker is inserted in a forwarded email message with an attachment. The enterprise resource **130** (for example, an Exchange server or other enterprise email server) can insert the attachment into the forwarded email message that is sent to the recipient by the Smart Forwarding feature. In this way, the mobile device **120** can forward the email message without downloading the entire email message and attachment to the mobile device **120**.

(159) In event A of FIG. 32, the mobile device **120** sends, to the secure mobile gateway **128**, a request to forward an email message that includes a reference to the attachment. Then the secure mobile gateway **128** simply passes through the email message to the enterprise resource **130** in event B. The enterprise email server can then use the reference to identify the attachment that is stored on the enterprise email server. The email and the attachment can then be sent to the recipient via the process illustrated in FIG. 31 when the recipient is a mobile device **120** associated with the enterprise. In event C, the enterprise resource **130** responds to the secure mobile gateway **128** to confirm that the message has been sent. The secure mobile gateway **128** passes through the response to the mobile device **120** in event D.

(160) In the example illustrated in FIG. 33, the secure mobile gateway **128** decrypts encrypted attachment data from the mobile device **120** when transmitting a request to forward the email message with the attachment from the mobile device **120** to an enterprise resource **130**, such as an enterprise email server. The process illustrated in FIG. 33 can be implemented in situations in which the email message with the attachment is being transmitted from the mobile device **120**. Such a process can be implemented, for example, on mobile devices **120** in which the process illustrated in FIG. 32 is unsupported (such as mobile devices **120** that do not support Smart Forwarding) and/or disabled.

(161) In event A of FIG. 33, the mobile device **120** sends a request to forward an email message with an attachment to the secure mobile gateway **128**. The request can include the encrypted attachment data. The secure mobile gateway **128** detects a previously encrypted attachment and

decrypts the encrypted attachment data at in event B. For instance, the secure mobile gateway **128** can programmatically identify attachments that are marked and/or modified to indicate that they are encrypted, such as having the suffix “.zendata” in an example provided above. More details regarding some example decryption methods that can be performed in event B will be described with reference to FIG. 35. In event C, the request to forward the email message including the decrypted attachment data is transmitted to the enterprise resource **130**. The enterprise resource **130** responds to the secure mobile gateway **128** to confirm that the message has been sent in event D. The secure mobile gateway **128** passes through the response to the mobile device **120** in event E.

(162) To encrypt email attachments, various keys can be generated, delivered to other devices, encrypted, used to decrypt encrypted attachment data, the like, or any combination thereof. Although encryption of email attachments may be described herein with reference to certain computing devices performing particular functionalities for illustrative purposes, it will be understood that any of the features related to encrypting and/or decrypting an attachment described herein can be performed by any suitable computing device. For example, some functions related to encryption/decryption or a subcombination thereof that are described as being performed by the secure mobile gateway **128** and/or the mobile device management system **126** can be performed by the mobile device **120**. As another example, some functions related to encryption/decryption or a subcombination thereof that are described as being performed by either the secure mobile gateway **128** or the mobile device management system **126** can alternatively or additionally be performed by the other of the two competing systems.

(163) In certain embodiments, the secure mobile gateway **128** can generate keys related to an attachment and the mobile device management system **126** can generate keys for selected mobile devices **120**. For instance, the secure mobile gateway **128** can generate a symmetric secure mobile gateway key Smgkey and store this key in a suitable data store. The symmetric secure mobile gateway key Smgkey can be generated, for example, when the secure mobile gateway **128** is being installed and/or when software is being installed thereon. According to some embodiments, the mobile device management system **126** can generate an asymmetric key DeviceKey associated with a selected mobile device **120**. Alternatively or additionally, the mobile device management system **126** can generate an asymmetric key associated with a group of mobile devices **120**, a user of the enterprise, the like, or any combination thereof. Such an asymmetric key can be used in place of the asymmetric key DeviceKey or in combination with the asymmetric key Device Key. The mobile device management system **126** can distribute a private key DeviceKeyPr of the asymmetric key DeviceKey to the selected mobile device **120**. The mobile device management system **126** can distribute a public key DeviceKeyPb of the asymmetric key DeviceKey to the secure mobile gateway **128**.

(164) FIG. 34 is a flowchart illustrating an embodiment of a method of encrypting an attachment. Some or all of the method steps illustrated in FIG. 34 can be performed, for example, in event D and/or in event J of FIG. 31. At block **3410**, an attachment key AttachmentKey is generated. The attachment key AttachmentKey can be a symmetric key. The attachment key AttachmentKey can be generated by the secure mobile gateway **128**.

(165) The attachment key AttachmentKey is encrypted at block **3420**. For example, the secure mobile gateway **128** can encrypt the attachment key AttachmentKey with the secure mobile gateway key Smgkey. This produces an encrypted secure mobile gateway attachment key

EncryptedSmgAttachmentKey for the secure mobile gateway **128**, which can be used by the secure mobile gateway **128** to decrypt the encrypted attachment data, for example, as described with reference to FIG. 35. Additionally, the secure mobile gateway **128** can encrypt the attachment key AttachmentKey with the public key DeviceKeyPb. This produces an encrypted device attachment key EncryptedDeviceAttachmentKey for the mobile device **120**, which can be used by the mobile device **120** to decrypt the encrypted attachment data, for example, as described with reference to FIG. 35.

(166) At block **3430**, attachment data is encrypted with the attachment key AttachmentKey to generate encrypted attachment data. The secure mobile gateway **128** replaces previous attachment data with encrypted attachment data at block **3440**. The encrypted attachment keys EncryptedSmgAttachmentKey and EncryptedDeviceAttachmentKey can also be included with the encrypted attachment data. For example, the secure mobile gateway **128** can replace attachment data with encrypted attachment data, the encrypted secure mobile gateway attachment key EncryptedSmgAttachmentKey and the encrypted device attachment key EncryptedDeviceAttachmentKey.

(167) Encrypted attachment data can be decrypted in order to access the attachment data. In certain embodiments, a user can be prompted to log-in or otherwise supply access credentials when accessing encrypted attachment data on a mobile device **120**. To maintain the protection of the encrypted attachment data, the encryption keys associated with the attachment data can be provided to particular computing devices. For instance, as discussed with reference to block **3420** of FIG. 34, the secure mobile gateway **128** can encrypt the attachment key AttachmentKey specifically for use with a selected mobile device **120** and/or the secure mobile gateway **128**. FIG. 35 is a flowchart illustrating an embodiment of a method of decrypting an attachment. Some or all of the method steps illustrated in FIG. 34 can be performed, for example, by either a mobile device **120** or the secure mobile gateway **128** when encrypted attachment data stored on the mobile device is accessed by an application on the mobile device **120** and/or in event B of FIG. 33.

(168) At block **3510**, a computing device receives an encrypted attachment. In certain embodiments, the computing device can also receive an encrypted attachment key with the encrypted attachment data. The encrypted attachment data and the encrypted attachment key can both be included in the same file, according to some of these embodiments. The encrypted attachment key is decrypted at block **3520**. Then, at block **3530**, the attachment data is decrypted using the attachment key.

(169) The method illustrated in FIG. 35 can be performed, for example, by an enterprise agent **320** on a mobile device **120**. This can include the mobile device **120** receiving an encrypted attachment and an encrypted attachment key, for example, in accordance with the process illustrated in FIG. 31. The enterprise agent **320** of the mobile device **120** can decrypt an encrypted device attachment key EncryptedDeviceAttachmentKey with a private device key DeviceKeyPr. The decrypted device attachment key can be the attachment key AttachmentKey. With the attachment key AttachmentKey, the enterprise agent **320** of the mobile device **120** can decrypt the encrypted attachment data. This can provide the mobile device **120** with the original attachment data sent to the mobile device **120** by an enterprise resource **130**, such as an enterprise email server. Such data can be, for example, plain-text data.

(170) The method illustrated in FIG. 35 can be performed, for example, on a secure mobile

gateway **128**. This can include the secure mobile gateway **128** receiving an encrypted attachment, for example, when a mobile device **120** forwards an email message with an encrypted attachment. The secure mobile gateway **128** can decrypt an encrypted secure mobile gateway attachment key EncryptedSmgAttachmentKey with the secure mobile gateway key Smgkey. The decrypted device attachment key can be the attachment key AttachmentKey. With the attachment key AttachmentKey, the secure mobile gateway **128** can decrypt the encrypted attachment data. This can provide the secure mobile gateway **128** with the original attachment data previously sent to the mobile device **120** by an enterprise resource **130**, such as an enterprise email server. The secure mobile gateway **128** can then forward the attachment data to the enterprise resource **130**.

(171) To support distribution and/or updating of public device keys, such as the public device key DeviceKeyPb, a web service interface or other suitable interface can be provided. The interface can enable a user to define device/key pairs and/or user/key pairs. The interface can enable a user, such as an IT staff member or an enterprise network administrator, to update the key pairs by, for example, adding new pairs, replacing existing pairs, removing pairs, the like, or any combination thereof. The interface can enable a user to map a mobile device **120** to a set of properties (for example, name/value pairs). Such properties can include the attachment public key, blocking attachments, blocking selected attachment types, blocking contact sync, blocking calendar sync, client certificate ID, any of the other properties described herein, the like, or any combination thereof.

#### (172) Application Tunnels

(173) With reference to FIGS. 1A-3, a tunneling mediator, such as the tunneling mediator **224** of the mobile device management system **126**, can be configured to receive access requests generated by software applications **318** installed on the mobile devices **120**, for access to the enterprise resources **130** (especially enterprise resources **130** comprising software applications), and to generate application tunnels between the device applications **318** and the enterprise resources **130**. An application tunnel is a technique in which one network protocol (for example, the delivery protocol) encapsulates a different network protocol. By using tunneling, it is possible to, for example, provide a secure path through an untrusted network.

(174) One benefit of using application tunnels for communications between mobile device applications **318** and enterprise resources **130** is that it is possible to limit the mobile device's access to those enterprise resources **130** that the user **115** of the mobile device **120** needs for the performance of his or her enterprise role **206**. Another potential advantage of using application tunnels is that access control can be provided at the application level for pre-existing applications. In preferred embodiments, the application tunnels are defined at the application layer in the OSI model. This is in contrast to a virtual private network (VPN), a methodology which is widely used to provide remote offices or individual users secure access to their organization's network. A VPN operates at the network layer (or lower) of the Open Systems Interconnection (OSI) model and ordinarily provides users with full access to all of the resources within an enterprise's computer network. A significant problem with using a VPN connection is that no suitable mechanism exists for restricting access by the mobile applications (and potentially mobile applications containing malware) to the VPN connection. In contrast, as described below, each application tunnel may be exclusive to (available for use only by) a single, corresponding mobile application. By limiting access only to enterprise resources **130** needed by a particular user **115**, the use of application tunnels can promote enterprise network security.

(175) As explained in further detail below, an additional benefit of using application tunnels for communications between a mobile device **120** and an enterprise system **110** is that it allows the enterprise to improve the user's connectivity experience (e.g., by caching data in the event of a network connection loss), log data flows, and implement other features.

(176) In order to implement the application tunnels, a tunneling mediator can be provided, through which the tunneled communications flow. The tunneling mediator is a component that receives mobile device application communications formatted according to an encapsulation protocol, “unpacks” or extracts data from the communications using the protocol, and sends the unpacked or extracted data to a network resource requested or specified by the mobile device application. The tunneling mediator also does substantially the same for communications sent by a network resource to a mobile device application via the tunneling mediator. The tunneling mediator can comprise a software application installed on a server. The tunneling mediator can be located within the enterprise system **110** (e.g., the tunneling mediator **224** of the mobile device management system **126**), or alternatively outside of the enterprise system **110** (e.g., in a cloud computing environment **156** as in FIG. 1B).

(177) A tunneling mediator or enterprise agent **320** can use a tunnel definition to construct an application tunnel, in accordance with methods described below. The mobile device management system **126** illustrated in FIG. 2 includes a repository **228** of tunnel definitions. A tunnel definition can include information to implement an application tunnel between a mobile device application **318** and a remote resource (such as an enterprise resource **130**). A tunnel definition can be specific to a particular application **318** or type thereof. Similarly, a tunnel definition can be specific to a particular remote resource or type thereof. A tunnel definition can identify a specific port of a mobile device **120** and/or a URL or specific port of a computer server on which the remote resource is installed. Accordingly, a tunnel definition can include an application or server port and information mapping such a port to a client port to specify the endpoints of an application tunnel. A tunnel definition can also include a URL of a tunneling mediator, which can be useful, particularly in implementations involving multiple tunneling mediators. Multiple application tunnels can be mapped to a specific port of a mobile device **120** and/or a URL or specific port of a computer server on which the remote resource is installed, and the multiple application tunnels can be multiplexed such that a single port of the mobile device **120**, and/or a URL or specific port of the computer server on which the remote resource is installed, is used to implement multiple application tunnels. The mobile device management system **126** can be configured to send (e.g., push) at least portions of the tunnel definitions **228** to mobile devices **120**. For example, the tunnel definitions can be sent with the “rule packages” described below. The enterprise agents **320** can be configured to store the tunnel definitions locally on the mobile devices **120**, and use the tunnel definitions to generate application tunnel formation requests, as described below.

(178) A tunneling mediator or related system can include an interface, such as a web console, for viewing, creating, and editing tunnel definitions. The interface can also allow an administrator or other person to view data associated with mobile devices **120** adapted to connect via application tunnels. At least some of the data can be obtained from the repository of mobile device information **204** (FIG. 2).

(179) Many mobile device software applications **318** are capable of issuing network communications (also referred to as “application-generated communications”), including requests to access and communicate with enterprise resources **130**. The enterprise agent **320** can be

configured to intercept and/or receive these communications, and redirect at least some of them to URLs associated with one or more tunneling mediators, such as the mediator **224**. The tunneling mediator can redirect the application-generated communications to requested enterprise resources **130**, receive responsive communications from the enterprise resources **130**, and forward the responsive communications back to the mobile devices **120**. Advantageously, the tunneling mediator can add a layer of enterprise security by applying access policies **218** to grant or deny access, and restricting access only to the requested enterprise resources **130**.

(180) In one embodiment, upon intercepting and/or receiving an application-generated communication for accessing an enterprise resource **130** (or another resource), the enterprise agent **320** searches the application tunnel definitions stored in local storage to retrieve a tunnel definition associated with the software application **318** that produced the application-generated communication, and/or associated with the requested enterprise resource **130** (or other resource). The enterprise agent **320** generates an application tunnel formation request that identifies the retrieved tunnel definition, and encapsulates at least a portion of the application-generated communication within one or more headers of an encapsulation protocol. The encapsulated application-generated communication is also referred to herein as an “agent-generated communication.” The enterprise agent **320** sends the application tunnel formation request and the encapsulated application-generated communication (which can together comprise a single communication) to the tunneling mediator **224** (e.g., via connections **142** and **144** of FIGS. 1A and 1C, or via connections **142** and **160** of FIG. 1B) or another such mediator defined in the tunnel definition. Skilled artisans will appreciate that the defined tunneling mediator can be one of a plurality of tunneling mediators associated with the agent **320** and enterprise system **110**.

(181) The tunneling mediator **224** receives the application tunnel formation request (which identifies the tunnel definition) and the agent-generated communication. The tunneling mediator **224** can read the tunnel definition identified in the tunnel formation request and then retrieve the identified tunnel definition from the repository **228**. The tunneling mediator **224** can determine, from the retrieved tunnel definition or even from the information provided in the tunnel formation request, a URL and/or port of a computer server or other computing device on which the requested enterprise resource **130** is located. The tunneling mediator **224** opens a network connection to the server port (e.g., the connection **152** of FIGS. 1A and 1C, or the connection **162** of FIG. 1B). In some embodiments, the tunneling mediator **224** remains connected to the enterprise resource **130** at all times or during pre-scheduled time ranges, such that a connection can be available immediately upon the receipt of an application tunnel formation request from a mobile device **120**. Based on the encapsulation protocol the tunneling mediator **224** extracts the application-generated communication from the agent-generated communication, and sends the former to the URL/server port associated with the requested enterprise resource **130**. At this point, an application tunnel has been formed between the mobile device **120** and the requested enterprise resource **130**. In some embodiments, the tunneling mediator **224** sends a message back to the mobile device **120** to indicate the formation of the tunnel, and asks that the enterprise agent **320** affirmatively accept the tunnel before sending application-generated communications to the enterprise resource **130**. Once the tunnel is formed, the enterprise agent **320** can send additional application-generated communications (encapsulated using the encapsulation protocol) to the tunneling mediator **224**, which can forward them to the enterprise resource **130**.

(182) Communications in the opposite direction (e.g., from an enterprise resource **130** to a mobile

device application **318**) can be encapsulated by the tunneling mediator **224**, sent by the tunneling mediator **224** to the mobile device **120**, and then unpacked by the enterprise agent **320**, in accordance with the encapsulation protocol. The tunneling mediator **224** can communicate with the enterprise resource **130** as though the mediator **224** is the mobile device application **318**, and so that responses generated by the enterprise resource **130** are returned to the tunneling mediator **224** (e.g., via connection **152** of FIGS. 1A and 1C, and connection **162** of FIG. 1B). When the tunneling mediator **224** receives such responses to the application-generated communications, the tunneling mediator **224** can encapsulate at least a portion of each of these “resource-generated responses” within one or more headers, such as HTTP headers, in accordance with the encapsulation protocol, and then send the encapsulated response to the enterprise agent **320** (e.g., via connections **144** and **142** of FIGS. 1A and 1C, and connections **160** and **142** of FIG. 1B). The tunneling mediator **224** can be configured to send its communications to a specific port of the mobile device **120**, the port being defined in the tunnel definition associated with the operative-application tunnel. The enterprise agent **320** can be configured to “listen” to this local port for tunneled communications from the tunneling mediator **224**. Based on the encapsulation protocol, the enterprise agent **320** can extract the resource-generated response from the one or more headers, and then provide the resource-generated response to the application **318**.

(183) In this type of application tunnel, the software application **318** installed on the mobile device **120** can be given an impression that it is connecting directly with a resource (such as an enterprise resource **130**) associated with the URL of the network request issued by the application **318**. In reality, the application **318** is actually communicating with the resource via a tunneling mediator (such as the tunneling mediator **224**). Thus, the application **318** need not be aware of the tunnel's existence.

(184) In some embodiments, the enterprise agent **320** can be configured to filter out those application-generated communications that meet predefined and/or configurable criteria. Such criteria can include, for example, any one or more of the following, as well as various other criteria: (1) the URL (e.g., of the enterprise system **110**, or of web sites whose access is restricted by the enterprise), (2) server port(s) to which an application **318** attempts to send the request, (3) data regarding the application that issues the request (e.g., name, version, etc.), (4) time of day, (5) day of the week, and/or (6) geographic location of the mobile device **120**. Such filtering criteria can be communicated to a mobile device **120** by the enterprise system **110** via wireless communications to the enterprise agent **320**.

(185) In one method of initiating the formation of an application tunnel, the enterprise agent **320** is configured to intercept the application-generated communications from the software applications **318**. For instance, in mobile devices **120** running certain Microsoft™ operating systems (e.g., Windows Mobile™, Windows CE™), it is possible to use a layered service provider (LSP) to filter network requests issued by mobile device applications **318**. An LSP, which is a feature of the Microsoft Windows Winsock 2 Service Provider Interface (SPI), is a DLL that uses Winsock APIs to insert itself into the TCP/IP protocol stack. Once in the stack, the LSP can intercept and modify inbound and outbound Internet traffic. The LSP can allow for processing of all the TCP/IP traffic taking place between the Internet and the device's software applications **318**. The LSP can be configured to be loaded automatically by any application **318** that uses network connections. The LSP has a layered model, like a filter. Thus, every time an application **318** makes a network call, it goes through the LSP. The LSP allows the enterprise agent **320** to intercept every application

network communication attempting to send information to one or more defined URLs, and redirect the communication to a tunneling mediator, such as the mediator **224** associated with the enterprise system **110**. In this manner, the enterprise agent **320** can detect requests from the applications **318** to connect to the enterprise resources **130**, and modify and redirect the requests to a URL of the tunneling mediator. The enterprise agent **320** can be configured to filter requests from the applications **318** by one or more identified ports of the enterprise resources **130**. The enterprise agent **320** can be configured to select port(s) of the tunneling mediator(s) to send the redirected requests, based at least partly on the enterprise resource ports provided within the requests.

(186) As noted above, after the tunneling mediator establishes an application tunnel connection between the mediator and the requested resource, the mediator can send a notification thereof to the enterprise agent **320**, and the enterprise agent **320** can accept the application tunnel connection. All of this can happen transparently with respect to the software application **318**. The application **318** can send network requests via the tunneling mediator without modifications or reconfiguration of the application **318**, according to certain embodiments.

(187) Unfortunately, in some mobile devices it is difficult or even impossible for a mobile device **120** to intercept network connection requests issued by software applications **318**. Some mobile device operating systems (such as iOS™ and Android™) can restrict the ability of different software applications to interact and share data with each other. Such restrictions are sometimes referred to as the “sandboxing” of software applications, and can be useful in preventing rogue applications from stealing data from mobile devices **120** and sending the data to unauthorized Internet locations. This can prevent an enterprise agent **320** from accessing or modifying network requests issued by the applications **318**.

(188) Hence, another approach to initiating the formation of an application tunnel is to reconfigure how the software applications **318** send their network requests (or at least some of them). In certain embodiments, a software application **318** is reconfigured to send its network requests to a local host of the mobile device **120**, on a defined mobile device port. The enterprise agent **320** can be configured to “listen” to the port and react to an application's network request by establishing a connection with a tunneling mediator (if it is not already established) to open an application tunnel with a resource requested by the application **318**. The enterprise agent **320** can consult the relevant application tunnel definition in order to determine the port to which to listen for the application tunnel request. In other embodiments, a software application **318** is reconfigured to send at least some of its network requests directly to the tunneling mediator. Further, the application **318** can also be configured to “unpack” communications (encapsulated via the encapsulation protocol) received from the tunneling mediator. An enterprise can make available an application store of downloadable mobile device applications **318** that are configured to generate application tunnel requests as described herein.

(189) Encapsulation protocols for producing application tunnels are now further described. The enterprise agent **320** or software applications **318** (depending on which particular approach to forming an application tunnel is used) can be configured to modify the software application's network connection request using any of a variety of different methods or encapsulation protocols. An encapsulation protocol for use in an application tunnel can allow for the addition of metadata for various purposes. For example, the encapsulation protocol, via added metadata, can identify the particular application tunnel, which allows the tunneling mediator to distinguish the funnel from



other application tunnels that the tunneling mediator may simultaneously be handling. This can help to prevent mixing data between the different application tunnels, helping to ensure that the tunneled data is delivered to the correct resource (e.g., enterprise resource **130**). Stated differently, the encapsulation protocol may add metadata that enables multiple application tunnels to be multiplexed for transmission on a common connection. The added metadata can also specify the length of each message sent through the tunnel. Added metadata can also be unrelated to the application tunnel or to the application **318** that initiated the tunnel such as a list of software applications **318** installed on the mobile device **120**, or results of commands sent to the mobile device **120** by the mobile device management system **126**. Such data can be used by the mobile device management system **126** to update the mobile device information **204**.

(190) A typical network connection request generated by the software application **318** may use a multi-layered communication protocol involving multiple protocol headers. In a simplified example, the access request generated by the software application **318** may take the following form: [IP header][TCP header][HTTP header][SOAP header][SOAP body],

wherein “IP” refers to the Internet Protocol, “TCP” refers to the Transmission Control Protocol, “HTTP” refers to the Hypertext Transfer Protocol and “SOAP” refers to the Simple Object Access Protocol. In this example, the mobile device's enterprise agent **320** can be configured to intercept this communication (e.g., by use of an LSP) at the TCP layer, and then rewrap or encapsulate the TCP payload (which in this example is [HTTP header][SOAP header][SOAP body]) in multiple layers according to an encapsulation protocol used by the enterprise agent **320**. For example, the enterprise agent **320** could rewrap or encapsulate the TCP payload within the following plurality of layers: SSL (Secure Sockets Layer), TCP, IP, etc. The enterprise agent **320** can then send the encapsulated request to the tunneling mediator. In other embodiments, as described above, the software application **318** can be configured to send the request to a local port of the mobile device **120** (from which the enterprise agent **320** receives, encapsulates, and redirects the request to the tunneling mediator), or even encapsulate the request and send it directly to the tunneling mediator.

(191) Upon receipt of the encapsulated request from the mobile device **120**, the tunneling mediator can unpack the request according to the encapsulation protocol. In the above example, the tunneling mediator extracts the TCP payload generated by the mobile device's software application **318**. The tunneling mediator can then send the TCP payload to a URL/port (obtained from the relevant tunnel definition **228**) of the requested enterprise resource **130** (e.g., a server port of the server on which the requested enterprise resource **130** is installed). In the above example, the extracted TCP payload contains the higher level protocols, HTTP and SOAP. In certain embodiments, the encapsulation protocol uses Secure Sockets Layer (SSL) over HTTPS to form the tunnel.

(192) FIG. 5 is a flowchart illustrating an embodiment of a method in which an enterprise agent **320** of a mobile device **120** redirects communications generated by a mobile device application **318** to an enterprise resource **130** through an application tunnel. In step **502**, the application **318** generates a network request for access to an enterprise resource **130** of the enterprise computer system **110**. As explained above, this request can comprise a payload for the enterprise resource **130**, encapsulated within other protocol headers (“application-generated communication”). In step **504**, the enterprise agent **320** intercepts or receives the request. In step **506**, the enterprise agent **320** modifies the request by encapsulating some or all of the request within one or more headers according to an encapsulation protocol (producing an “agent-generated communication”). For

example, the enterprise agent **320** could encapsulate a portion containing the payload for the enterprise resource **130**. In step **508**, the enterprise agent **320** opens a network connection (e.g., connection **142**, **144** of FIGS. 1A and 1C, or connections **142**, **160** of FIG. 1B) between the mobile device **120** and a tunneling mediator (e.g., the tunneling mediator **224**) associated with the enterprise system **110**. In step **510**, the enterprise agent **320** sends the agent-generated communication to the tunneling mediator via the network connection. In step **512**, the enterprise agent **320** receives data from the tunneling mediator, the received data being responsive to the request (“resource-generated response”). The received data can be encapsulated according to the encapsulation protocol, and the enterprise agent **320** may need to unpack the data, for example, according to the encapsulation protocol. Finally, in step **514**, the enterprise agent **320** provides the received data to the application **318**.

(193) FIG. 6 is a flowchart illustrating an embodiment of the application tunneling methodology, from the perspective of the enterprise system **110**. As with all of the methods described herein, some of the illustrated steps can be optional. In step **602**, a tunneling mediator of or associated with the enterprise system **110** (e.g., the tunneling mediator **224**) receives a request from the mobile device application **318**, for access to the enterprise resource **130**. As explained above, the request can comprise an agent-generated communication—an application-generated communication that the device's enterprise agent **320** has intercepted or received, modified according to the encapsulation protocol, and then redirected to the tunneling mediator (e.g., via network communication links **142** and **144** of FIG. 1A). The request may comprise a payload for the enterprise resource **130**. In step **604**, the enterprise system **110** can determine whether access to the enterprise resource **130** is authorized. For example, as described below, the mobile device manager **202** or tunneling mediator **224** can determine whether the request is permissible under one or more of the enterprise access policies **218** of the mobile device management system **126**. In step **606**, the tunneling mediator extracts the payload for the enterprise resource **130** from the encapsulated request after the request is authorized. In step **605**, the tunneling mediator or another component of the enterprise system **110** logs information about the request and/or the payload. This logging functionality is described in more detail below, in step **610**, the tunneling mediator opens a resource network connection (e.g., connection **152** of FIGS. 1A and 1C, or connection **162** of FIG. 1B) between the tunneling mediator and a server port associated with the requested enterprise resource **130**. In step **612**, the tunneling mediator sends at least the enterprise resource payload to the server port via the resource network connection. In many applications, the enterprise resource **130** responds to the request by sending data (“resource-generated response”) back to the mobile device **120**. Accordingly, in step **614**, the tunneling mediator receives data (e.g., a plurality of data packets) from the enterprise resource **130**, via the resource network connection. The data is typically responsive to the request received in step **602**. In step **616**, the tunneling mediator (or another component) logs information about the data received from the enterprise resource **130**. Finally, in step **618**, the tunneling mediator sends the data to the mobile device **120**.

(194) The illustrated logging steps **608** and **616** of FIG. 6 can allow an enterprise to keep track of data that flows through the resource network connection (e.g., connections **152**, **162** of FIGS. 1A-1C) between the tunneling mediator and the enterprise resource **130**. The use of application tunnels for such logging enables user and device behaviors to be tracked at more granular level, and with a greater level of control. For example, because each application tunnel is ordinarily tied to a particular mobile device **120**, user, and mobile application, data transmitted over that tunnel can be stored in association with this mobile device, user and application. This gives an enterprise

greater visibility into the activities of its mobile device users **115**. The tunneling mediator (or other component associated therewith) can be configured to log various types of information, such as the actual data sent through the resource network connection, the amounts of data sent through the resource network connection, types of data sent through the resource network connection, names of files sent through the resource network connection, the number of times a particular user accesses one or more enterprise resources **130**, the times at which a user requested access to one or more enterprise resources **130**, etc. Analytics can be generated from the logged data. The mobile device management system **126** can set rules based on such analytics. As one example, access to one or more enterprise resources **130** can be restricted for a mobile device **120** with a high volume of downloads.

(195) Application tunnels as described above can also be used for purposes other than accessing enterprise resources **130**. For example, as described below in connection with FIGS. 12, 13, and 18), an application tunnel can be used to conduct a “remote control session” between a mobile device **120** and a controller computer.

(196) Another use of an application tunnel involves so-called “web filtering” or “content filtering,” in which an enterprise may wish to restrict the network sites (e.g., websites) or other online information resources that a mobile device **120** is authorized to access. Using an application tunnel to perform content filtering can be implemented with features related to modifying a pre-existing mobile application, and/or through the use of a secure web browser as described below. Access can be authorized, for example, at all times, only during business hours, etc. In certain embodiments, the enterprise agent **320** is configured to redirect intranet and/or Internet requests generated by the mobile device **120** (e.g., a URL entered into a web browser, or an HTTP request generated by the web browser, for an information resource available on the world wide web) through an application tunnel to a content-filtering server associated with the enterprise. The content-filtering server acts as a tunneling mediator, and inspects each request to determine whether the requested site is authorized by the enterprise. For example, the content-filtering server can maintain a list of sites that are “blacklisted” by the enterprise, and can deny requests to access blacklisted sites. In certain embodiments, this determination may be based on the specific mobile device **120** and user **115** making the request (e.g., based on user role **206**). The content-filtering server can be located within or outside of the enterprise system **110**, and could be a third-party server operated at least partially for the benefit of the enterprise. If the request is authorized, the content-filtering server can send the request to a server associated with the authorized site to be accessed by the mobile device **120**. The content-filtering server can be configured to modify the request to strip away any headers that were produced by the enterprise agent **320** to form an application tunnel with the content-filtering server (according to the encapsulation protocol). The server associated with the requested site can then receive the request in a form as though it was never sent to the content-filtering server.

(197) FIG. 25 illustrates an embodiment in which application tunnels are created using an enterprise agent **320** that runs on the mobile devices **120** (one shown). In this embodiment, the enterprise agent **320** includes, or acts as, an HTTP proxy server **320a** for one or more mobile applications that run on the mobile device **120**. The enterprise agent **320** communicates via a wireless network (WIFI, cellular, etc.) with the mobile device management system **126**, which may, for example, be implemented on a dedicated server within the enterprise system **110**. The mobile device management system **126** illustrated in FIG. 25 includes a web admin console **126a** that

enables administrators, via a web-based interface, to configure and deploy application tunnels between mobile devices **120** and application servers **2500**. The mobile device management system **126** illustrated in FIG. 25 also includes a tunnel mediator **126b** which implements the tunneling encapsulation protocol, and which routes packets sent between the mobile devices **120** and application servers **2500**.

(198) In this embodiment of FIG. 25, the enterprise agent **320**, upon deployment of the application tunnel, creates a socket that listens on a particular port that is known to the mobile application(s) that use the application tunnel. When a mobile application writes to this port (by writing to localhost:XXX, where “XXX” is the listerted-to port number), the enterprise agent **320**, acting at an HTTP proxy for the mobile application, encapsulates and forwards the message, for example, as described above. More specifically, when a mobile application generates an HTTP request that is directed to an application server **2500** (or other resource) of the enterprise system **110**, the enterprise agent **320** intercepts the request, and sends the request over an application tunnel established between the mobile device **120** and the mobile device management system **126**. The tunnel mediator component **126b** of the mobile device management system **126** then extracts the encapsulated HTTP message, and sends it to the relevant application server **2500**.

(199) One potential problem with this approach is that some application servers, such as Microsoft SharePoint, will reject the request if the hostname is incorrect. To address this issue, the enterprise agent **320**, in some embodiments, replaces the hostname (localhost:XXX) in the intercepted request with the correct hostname of the target application server **2500**. This involves modifying the relevant HTTP header or headers of the original HTTP request received from the mobile application, and then sending the modified HTTP request via the application tunnel. In other embodiments, the task of replacing the hostname is instead performed by the mobile device management system **126** upon receiving and extracting the encapsulated HTTP request.

(200) The process by which HTTP requests are intercepted and modified in the configuration of FIG. 25 is further illustrated in FIG. 27. In event A, an administrator configures and deploys an application tunnel between a mobile device **120** and an application server **2500**. This may be accomplished using the web admin console **126a** as will be described below. In event B, the agent **320**, in response to the deployment of the tunnel, creates a socket and begins listening on the associated port (addressable as localhost:XXX) In event C, the agent **320**, acting as an HTTP proxy, receives or “intercepts” an HTTP request from an application running on the mobile device **120**, and modifies the hostname to the actual hostname of the target application server **2500**. The agent **320** then encapsulates the modified HTTP requests and sends it to the mobile device management system **126**. In event D, the tunnel mediator **126b** running on the mobile device management system **126** extracts the modified HTTP request and sends it to the application server **2500** associated with the tunnel. The tunnel mediator **126b** also encapsulates the application server's response for transmission to the mobile device **120**.

(201) FIG. 26 illustrates one embodiment of a tunnel configuration page/screen provided by the web admin console **326a** of FIG. 25. An administrator can use this page to set up an application tunnel between a particular mobile device **120** and an application server **2500**. In the example shown in FIG. 26, the tunnel will be deployed on and specific to a single mobile device **120**. The “Application device parameters” section includes a “client port” field that is used to specify the port that the agent **320** listens to on the mobile device **120**. The “application device parameters” section also includes three options for specifying how traffic is to be intercepted and redirected. The page

also includes various other configuration options, including an option to use a secure (SSL) connection.

(202) Referring again to FIG. 25, in some configurations a custom SSL (Secure Sockets Layer) library **320b** may be installed on the mobile device **120** to support secure application tunnels. The custom SSL library **320b** may be part of the agent **320** (as shown in FIG. 25), or may be distinct. The custom SSL library **320b** supplements the standard SSL library provided by the mobile device's operating system, and modifies the SSL handshaking protocol in a manner that enables the SSL handshaking sequence to be performed over an application tunnel. More specifically, the custom SSL library enables the mobile device **120** to accept the application server's transmission of a digital certificate even though the hostname transmitted with this digital certificate does not match the expected hostname. By contrast, the standard SSL libraries typically provided with existing mobile operating systems would reject the application server's digital certificate in this situation. The custom SSL library **320b** may perform this task by overriding some of the Trust Manager certificate inspection functionality to create an exception to the mismatch in the hostname as part of the certificate. To support the use of the custom SSL library **320b**, application developers may be provided with an API (such as a Java file) that enables them to develop mobile applications that use the custom SSL library **320b** to establish SSL connections.

(203) FIG. 28 illustrates additional processing that is performed when the application tunnel is set up as a secure (SSL) tunnel in the configuration of FIG. 25. In this process, the custom SSL library **320b** (shown in FIG. 25) installed on the mobile device **120** creates an exception to the requirement that the application server's digital certificate must specify a hostname that matches the expected hostname. In event A of FIG. 28, an administrator configures and deploys the HTTPS application tunnel, preferably using the web administration console **126a**. In event B, the agent **320** creates a socket and begins listening on port localhost:XXX, as described above in connection with FIG. 27. (Although not shown in FIG. 27, the agent **320** in this embodiment intercepts and modifies requests from applications using the same process as shown in FIG. 27.) In event C, the mobile device **120**, using the custom SSL library **320b**, initiates SSL handshaking with the application server **2500** via the application tunnel. This involves the mobile device **120** sending a hello message, including the SSL version, encryption and compression information, and a 28-byte random number. This message is intercepted by the agent **320** (as described above with reference to FIG. 27), and is sent via the agent **320** to the mobile device management system **126**, which forwards the message to the application server **2500**.

(204) In event D of FIG. 28, the application server **2500** responds by returning a digital certificate containing a public key and cipher suites. This digital certificate contains or specifies the localhost hostname of the agent **320** (localhost:XXX). Ordinarily (i.e., if a standard SSL library were used), the SSL library would reject this digital certificate because it expects the digital certificate to specify the application server's hostname. As shown in event E of FIG. 28, the custom SSL library **320b** avoids this problem by making an exception to this requirement. The custom SSL library can create this exception by updating the SSL Trustmanager to permit a mismatch between the application server's hostname and the localhost hostname used by the agent **320**. (Although the exception could be created for all hostnames, this could facilitate a man-in-the-middle attack.) As further shown in event E, the custom SSL library **320b** also sends to the application server **2500** authentication code keys encrypted with the application server's public key. Thereafter, for the duration of the SSL session, the mobile device **120** and application server **2500** can use symmetric

keys for encryption.

#### (205) Use of Mobile Device Management System to Regulate Mobile Device Access to Enterprise System

(206) If the mobile device management system **126** is used as a tunneling mediator for application tunnels between mobile devices **120** and enterprise resources **130**, the system **126** can be configured to regulate the devices' access to the resources **130**. The system **126** can be configured to read information from the application tunnel request headers or bodies, compare it to the mobile device data **204** (FIG. 2) to determine information about the user **115** and/or mobile device **120** associated with the request, and enforce the enterprise access policies **218** to grant or deny the application tunnel requests. Access policies **218** can be enforced based on the locally stored user roles **206**, mobile device properties **208**, user-device assignments **210**, other data, or any combination thereof. It will also be understood that any tunneling mediator other than the mediator **224** can be configured to enforce the access policies **218**, as long as the tunneling mediator has access to the mobile device information **204**.

(207) FIG. 7 is a flowchart illustrating an embodiment of a method in which a tunneling mediator such as the mediator **224** in FIG. 2, uses access policies **218** to regulate mobile device access to enterprise resources **130**. The mobile device management system **126** can be configured to receive application tunnel access requests from mobile devices **120** (e.g., via an application tunnel using network connections **142** and **144**) to access the enterprise resources **130**. Accordingly, in step **702** of FIG. 7, the mobile device management system **126** receives an access request from one of the mobile devices **120**. In certain embodiments, when such a request is received from a mobile device **120**, the tunneling mediator **224** is configured to deny the request if one or more properties of the mobile device **120** and/or one or more properties of a user **115** assigned to the mobile device **120** do not comply with one or more of the access policies **218**. Accordingly, in decision step **704**, the tunneling mediator **224** determines whether one or more properties of the mobile device **120** comply with one or more relevant access policies **218** (e.g., general access policies, or access policies associated with the requested enterprise resource(s) **130**). The mobile device properties on which the tunneling mediator **224** can evaluate the access request can be the device properties **208** or other properties determined from the request itself. If the mobile device properties ascertained from the access request do not comply with the relevant access policies **218**, then, in step **710**, the tunneling mediator **224** can deny the access request. On the other hand, if the mobile device properties are in compliance with the one or more associated access policies **218**, then the method proceeds to decision step **706**, in which the tunneling mediator **224** determines whether one or more properties of the user **115** assigned to the mobile device **120** are in compliance with the one or more relevant access policies **218**. The properties of the user **115** can be, e.g., the user's role **206** or other user-related information that may or may not be stored within the mobile device information **204**. The tunneling mediator **224** can determine which user **115** is assigned to the mobile device **120** by, e.g., using the user-device assignment records **210**. If the one or more user properties comply with the one or more access policies **218**, then the tunneling mediator **224** grants the mobile device **120** access to the requested enterprise resource(s) **30**, in step **708** (through the connection **152** or **162**). If not, then the tunneling mediator **224** denies access in step **710**. It will be appreciated that this methodology allows the enterprise to regulate mobile device access to the enterprise resources **130** in a very flexible way, based on various combinations of mobile device properties and user properties.

(208) As noted above, in some embodiments the tunneling mediator **224** is positioned outside of the enterprise system **110** (e.g., in a cloud-computing system as in FIG. 1B). It will be appreciated that the mobile device information **204**, enterprise access policies **218**, mobile device rules **214**, and/or remedial action descriptions **216** can also be stored outside of the enterprise system **110**, such as with the tunneling mediator **224**. In those embodiments, the tunneling mediator **224** can still be configured to receive the access requests from the mobile devices **120**, and then grant or deny the requests based on the access policies **218**. In such embodiments, the tunneling mediator **224** can be configured to send the granted access requests to a network node positioned within the enterprise system **110**, which in turn routes the requests to the requested enterprise resources **130**. For example, the network node can comprise a computer server, the secure mobile gateway **128**, or another network device.

#### (209) Examples of Policies for Controlling Mobile Device Access to Enterprise System Resources

(210) There are many possible cases in which an enterprise may wish to regulate or restrict mobile device access to enterprise resources **130** based on mobile device properties and/or properties of users **115** assigned to the mobile devices **120**. Several of these “use cases” are now described. For clarity, the use cases are enumerated below. Also, for simplicity, the use cases are described in the context of access policies **218** stored in the mobile device management system **126**. As discussed above, the system **126** can be a provider **408** of gateway rules **404** to the secure mobile gateway **128**, and/or can regulate mobile device access to enterprise resources **130** via application tunnels. However, it will be appreciated that such gateway rules **404** could be created and given to the gateway **128** by any other provider **408**.

(211) Skilled artisans will understand that the following examples represent only a small portion of the full range of possibility for how enterprise access can be regulated using the disclosed components and/or processes. For instance, it will be appreciated that the access policies **218** can depend on any combination of user **115** properties, mobile device **120** properties (e.g., device properties **208**), the specific enterprise resources **130** for which access is being requested, and other information, and that the specific examples provided below are merely illustrative and far from exhaustive. Further, it will be understood that some use cases can be combined.

(212) Use Case 1: One or more of the access policies **218** may require that the mobile device **120** requesting access (the “access-requesting device”) is enrolled with the mobile device manager **202**. This helps to prevent giving enterprise resource access to people who are not associated with the enterprise.

(213) Use Case 2: One or more access policies **218** may require that the access-requesting device **120** be a certain device type (e.g., iPhone™, Windows Mobile™, etc.)

(214) Use Case 3: One or more of the access policies **218** may require that the access requesting device **120** have certain settings, such as being password-protected. This helps to prevent giving enterprise resource access to people who are not associated with the enterprise (e.g., are not users **115**) but somehow obtain a mobile device **120** (e.g., a device **120** that is misplaced or lost by the assigned user **115**) and attempt to access the enterprise system **110**.

(215) Use Case 4: One or more of the access policies **218** can require that the access-requesting device **120** use a current operating system version.

(216) Use Case 5: One or more of the access policies **218** can require that the access-requesting device **120** complies with a security requirement (e.g., an antivirus requirement) of the enterprise. If a mobile device **120** is not security-compliant (e.g., does not have up-to-date antivirus software installed or has not conducted a sufficiently recent auto-scan of its files, data, or applications for viruses), then permitting the device **120** to access an enterprise resource **130** may cause the virus to infect the resource **130**, potentially jeopardizing the operability of the enterprise system **110** or at least the specific resource **130** to which access is given. Hence, these types of access policies **218** can prevent such undesirable outcomes.

(217) Use Case 6: One or more of the access policies **218** can require that the access-requesting device **120** not be “jailbroken.” Jailbreaking is a process that allows a mobile device **120** to gain full access (“root access”) to unlock all features of its operating system, thereby removing limitations that may be imposed by the device manufacturer. Once jailbroken, a mobile device **120** may be able to download previously unavailable applications and extensions. Jailbreaking a mobile device **120** can give access to its root file system, allowing modification and installing third-party software components. Hence, a jailbroken device is often one in which security protections are removed. Thus, preventing jailbroken devices from accessing enterprise resources **130** further protects the enterprise system **110** from security threats and vulnerabilities.

(218) Use Case 7: One or more of the access policies **218** can require that the access-requesting device **120** not have any unauthorized applications installed. In this example, an “unauthorized application” can be a software application that is not authorized to be installed on the access-requesting device **120**, and/or on a particular group of devices **120** of which the access-requesting device is a member.

(219) Use Case 8: One or more of the access policies **218** can require that the user **115** assigned to the access-requesting device **120** have, one or more predefined roles **206** associated with the enterprise. For example, an access policy **218** can deny mobile device access to one or more of the enterprise resources **130** for mobile devices **120** assigned to users **115** having roles **206** that are not related to sales, engineering, or upper management.

(220) Use Case 9: One or more of the access policies **218** can depend on which particular enterprise resources **130** are being requested to be accessed by an access-requesting device **120**. For example, the conditions for which an enterprise may grant mobile device access to a CRM resource may be different than the conditions for which an enterprise may grant access to a product information database. Accordingly, different access policies **218** can be created and used for different enterprise resources **130**. In addition to depending on the requested enterprise resource(s) **130**, an access policy **218** can require that the user **115** assigned to the access-requesting device **120** have certain properties, such as a specific role **206** (as in Use Case 8 described above) or another status indication. For example, for a CRM resource **130**, an enterprise may wish to grant mobile device access only to users **115** with roles **206** involving sales or upper management. In that case, an access policy **218** for the CRM resource **130** may require that the user **115** assigned to the access-requesting device **120** have a sales or upper management role **206**, and the mobile device manager **202** can be configured to deny access requests from mobile devices **120** assigned to users without those roles **206**. An access policy **218** can further require that the user **115** assigned to the access-requesting device **120** be in good standing with the enterprise (e.g., users **115** whose employment is not terminated and who are not on a probationary status).



## (221) Meta-Application

(222) Referring again to FIG. 1A, the meta-application **150**, if present, can be configured to discover, model, and/or monitor various components of the enterprise system **110**, including by methods described in Qureshi '536. The meta-application **150** can also be configured to use encoded logic rules to detect “features” and “problems,” perform “root cause analysis,” plan “remedial actions,” and/or execute the remedial actions on the enterprise system **110**, including by methods described in Qureshi '536. In this context, a logic rule can comprise a logical combination of features of the managed system **110**, and can correspond to at least one problem. Further, a logic rule can include queries for specific information from the enterprise system (“telemetry queries”) or from a model of the enterprise system (“enterprise model query”), wherein the enterprise model is generated by the meta-application **150**. A problem can comprise any problematic state of any software, hardware, or firmware of the enterprise system **110** or of a mobile device **120**. The meta-application **150** can detect a problem by satisfying the logic of a corresponding logic rule. A feature can comprise a condition of a problem. For example, a logic rule can contain a telemetry query or enterprise model query for detecting a feature of the enterprise system **110**. Root cause analysis can refer to the detection of a component (again, software, hardware, firmware, or even the relationship between such types of components) that is a “root cause” of observed problematic behavior. The meta-application **150** can be configured to address detected problems by planning or executing remedial actions associated with the problems.

(223) Inputs (e.g., features) to the logic rules used by the meta-application **150** to detect problems can come not only from the “backend” of the enterprise system **110** (the portion of the system **110** behind the internal firewall **124**), but also from other sources, such as the secure mobile gateway **128**, the enterprise agents **320** on the mobile devices **120**, or an application tunnel mediator, such as embodiments of the mobile device management system **126**. For example, an input to a logic rule can be a grant or denial of a mobile device's access request **402** by the secure mobile gateway **128**. For instance, a logic rule can define a particular problem, at least in-part, as the denial by the gateway **128** of enterprise system access to a mobile device **120** used by the CEO of the enterprise. If the CEO is denied access, data indicative of this event satisfies this portion of the logic rule. In another example, an input to a logic rule can be data indicating that a user **115** has downloaded greater than a certain threshold amount of data within a specified time period. Such data could be provided to the meta-application **150** by an application tunnel mediator. In still another example, an input to a logic rule can be data indicative of the device's configuration or performance, such as data indicating that a user **115** has installed a certain software application on the user's mobile device **120**. Such data could be provided to the meta-application **150** by the enterprise agent **320** of the user's device **120**.

(224) In certain embodiments, one type of remedial action defined by a logic rule used by the meta-application **150** can be the creation of a new gateway rule **404** or the modification of an existing gateway rule **404**, along with sending the new or modified gateway rule to the secure mobile gateway **128**. In this manner, the meta-application **150** can be configured to programmatically control the gateway **128** to block mobile device access requests in an automated fashion. Another type of remedial action can be the creation of a new access policy **218** or the modification of an existing access policy **218**, along with sending the new or modified policy to the mobile device management system **126**. Another type of remedial action can be the creation of a mobile device rule **214** or the modification of an existing mobile device rule **214**, along with sending the new or

modified mobile device rule to the mobile device management system **126** and/or one or more of the mobile devices **120**. Another type of remedial action can be to send a command directly to one or more of the mobile devices **120**, for execution by the enterprise agent **320**. In this manner, the meta-application **150** can effectively execute actions on the devices **120**, such as wiping data or applications from the devices **120**, locking (i.e., preventing usage of) the devices **120**, preventing certain applications installed on the devices from running, turning device features on or off, adjusting device settings, and the like.

(225) In the embodiment of FIG. 1C, the meta-application comprises a portion **150** residing in the enterprise's backend, and a portion **151** residing in a cloud computing system or "cloud" **156**. The cloud-based system **156** is ordinarily separate and distinct from the enterprise system **110** (e.g., the two systems do not share any physical computers or servers) and is ordinarily operated primarily by cloud service provider business entity that is separate and distinct from the enterprise. In certain embodiments, the backend meta-application portion **150** collects data from the enterprise system **110**, sends it to the cloud-based meta-application portion **151**, and possibly also detects "features" as mentioned above. In certain embodiments, the cloud-based meta-application portion **151** uses the data to model the enterprise system **110**, to detect "problems" and "root causes," to plan remedial actions, and/or to execute the remedial actions.

(226) FIG. 8 shows one particular embodiment of a partially cloud-based meta-application. The meta-application includes several components residing on enterprise servers **802**, and other components residing on servers within the cloud **156**. Additionally, the meta-application communicates with the mobile device management system **126**, the secure mobile gateway **128**, and the enterprise device agents **320** running on the mobile devices **120**.

(227) In the illustrated embodiment, the enterprise system **110** includes one or more computer servers **802**, which can include some or all of the elements shown in the systems **110** of FIGS. 1A-C. A meta-application agent **804** can be installed on each server **802** having components that are desired to be monitored and/or managed by the meta-application **150**. Each meta-application agent **804** can be "born" (at installation) with the URL of the cloud-based meta-application portion. Alternatively, the agents **804** can be configured to receive the URL from an administrator. It will be understood that it is not necessary to install meta-application agents **804** on every computer server of the enterprise system **110**. The enterprise-based portion of the meta-application can be configured to allow an IT administrator to select the enterprise servers **802** on which to install the meta-application agents **804**, as part of the installation process of the meta-application.

(228) In the illustrated embodiment, the meta-application agent **804** includes an enterprise modeling processor **806**, a telemetry processor **808**, a feature detector **810**, and a remedy agent **812**. These components are now described.

(229) The enterprise modeling processor **806** can be configured to access and/or obtain information from the server **802**, which is needed or useful for constructing a queryable model **814** of the enterprise system. The enterprise model **814** can describe the hardware, software, and/or firmware of the enterprise system **110**, and can include, for example, configuration information, registry data, database information, and other information useful for evaluating logic rules **818**. The enterprise model **814** can comprise an object graph, with the objects representing hardware, software, firmware, relationships therebetween, and the like. Exemplary methods and approaches to modeling are described in Qureshi '536, particularly the sections relating to "discovery" and

“application models.” Each enterprise modeling processor **806** can be configured to construct a model of the particular server **802** on which it is installed. The cloud-based meta-application portion can be configured to receive data from the enterprise modeling processors **806** and use the data to construct the overall enterprise model **814**. The enterprise modeling processors **806** can be configured to send new data to the cloud-based meta-application portion on an ongoing basis, to support dynamic updating of the enterprise model **814**. Finally, it will be appreciated that the enterprise agents **320** of the mobile devices **120** can also be configured to conduct discovery of information about the devices **120** and send the discovered information to the enterprise model **814**, and the enterprise model **814** can thereby model one or more of the devices **120** as well as the enterprise system **110**. In other words, agents **320** can include enterprise modeling processors **806** or similar functionality.

(230) The telemetry processor **808** can be configured to receive, from the cloud-based meta-application portion **151**, requests for specific data about the server **802** on which it is installed. The telemetry processor **808** can be configured to respond to such a request by gathering the requested data (referred to herein as “telemetry”) and providing it to the feature detector **810** for analysts. The telemetry can comprise many different types of data about the hardware, software, and/or firmware of the enterprise system **110**, including without limitation configuration data, performance data, data about the mobile devices **120**, and data from or about the mobile device management system **126**, secure mobile gateway **128**, and enterprise resources **130**. Telemetry can comprise “state metric data,” as described in Qureshi '536. State metric data can comprise raw time-varying data indicative of a state of the server **802** or any component thereof. It will be appreciated that the enterprise agents **320** of the devices **120** can also be configured to gather device data based on requests for same from the meta-application portion **151**, and to send the gathered telemetry to a local feature detector **810** or back to the meta-application portion **151**. In other words, agents **320** can include telemetry processors **808** or similar functionality.

(231) The feature detector **810** can be configured to analyze the telemetry received from the telemetry processor **808**, to detect features of the logic rules **818**. The features can be defined within a telemetry query that the cloud-based meta-application portion sends to the meta-application agent **804**. Performing feature detection at least partly within the enterprise system **110**, as opposed to within the cloud **156**, can significantly reduce the bandwidth for communications between the meta-application agent **804** and the cloud **156**, because not all of the telemetry is sent to the cloud **156** in certain applications. For instance, the meta-application agent **804** can merely send the detected features to the cloud **156**. Skilled artisans will understand that a feature can be much less data-intensive than the raw telemetry from which the feature is detected. For example, a feature can simply be an indication that a particular condition is true. In an alternative embodiment, the feature detector **810** resides within the cloud **156**, and the telemetry processor **808** can send some or all of the gathered telemetry to the cloud for feature detection. It will be appreciated that the enterprise agents **320** of the mobile devices **120** can also be configured to analyze telemetry gathered in response to a request from the meta-application portion **151**, in order to detect features of the logic rules **818** and send those features back to the meta-application portion **151**. In other words, agents **320** can include feature detectors **810** or similar functionality.

(232) The remedy agent **812** can be configured to execute remedial actions **820** on the server **802** on which it is installed. The meta-application agent **804** can receive remedial actions **820** from the cloud-based meta-application portion. Although not shown in FIG. 8, the mobile device

management system **126** can include a remedy agent **226** (FIG. 2), and so can the secure mobile gateway **128**. Such remedy agents can allow the meta-application to execute remedial actions against the mobile device management system **126** and the secure mobile gateway **128**. It will be appreciated that the enterprise agents **320** of the mobile devices **120** can also be configured to execute remedial actions **820** on the devices **120**. In other words, agents **320** can include remedy agents **812** or similar functionality.

(233) Referring still to FIG. 8, the illustrated cloud-based meta-application portion **151** includes a telemetry monitor **822**, the enterprise model **814**, logic rules repository **816**, inference engine **824**, repository **826** of detected problems and/or root causes, user interface **828**, notification manager **830**, and remedy workflow module **832**. It will be understood that the cloud-based meta-application portion need not include all of these components, and can also include additional components not shown in FIG. 8.

(234) The telemetry monitor **822** can manage communications between the cloud-based meta-application portion and the meta-application agents **804**, as well as any other components that provide data that the cloud-based meta-application portion can use to evaluate the logic rules **818**, such as the enterprise agents **320** of the mobile devices **120**, the mobile device management system **126**, and the secure mobile gateway **128**. Hence, the telemetry monitor **822** can receive features detected by the feature detectors **810**, and can provide the features to the inference engine **824**. The telemetry monitor **822** can be configured to prioritize incoming features and other data, so that more important or urgent information is passed on to other components of the meta-application before less important or less urgent information.

(235) The inference engine **824** can be configured to access the repository **816** of logic rules **818** and evaluate whether individual rules **818** are satisfied by features of the deployment, wherein each satisfied rule corresponds to the detection of at least one problem. A logic rule **818** can include queries for information, such as a telemetry query or an enterprise model query. The inference engine **824** can be configured to process these queries of the logic rules **818** by querying the enterprise model **814** or relevant ones of the meta-application agents **804** for the needed information (e.g., features of the rule). The inference engine **824** can also be configured to perform root cause analysis to detect root causes of problematic behavior of the enterprise system **110**. A root cause can be an object of the enterprise model **814**, which represents a component of the enterprise system **110**. The inference engine **824** can be configured to employ rule evaluation methods and root cause analysis methods as taught in the '536 Qureshi patent (refer to discussions of "Problem Logic" and root cause analysis, respectively). The inference engine **824** can further be configured to log detected problems and root causes in a repository **826**.

(236) The user interface **828** can allow administrators to interact with the cloud-based meta-application portion. The illustrated user interface **828** comprises a web server interface to facilitate access over the Internet. The user interface **828** can also include a server terminal interface as well.

(237) The notification manager **830** can be configured to send notifications to administrators about information detected or computed by the meta-application, such as problems and root causes. Notifications can comprise, for example, emails, voice messages, SMS text messages, and the like. Preferably, the notification manager **830** allows an IT administrator to set and adjust the criteria under which the notification manager **830** sends notifications.

(238) The remedy workflow module **832** can be configured to select remedial actions **820** for attempting to solve or counter problems or root causes detected by the inference engine **824**. The remedial actions **820** can be stored in the repository **816** of logic rules **818**. A remedial action **820** can be stored in association with one or more of the logic rules **818**. The remedy workflow module **832** can be configured to determine an optimal sequence of execution of remedial actions **820** associated with the detected problems or root causes. The remedial actions **820** can be abstract or generalized for many different types of managed computer systems **110**. In that case, the remedy workflow module **832** can be configured to customize the remedial actions **820** into plans that are tailored for the specific enterprise system **110** and mobile devices **120** managed by the meta-application. The remedy workflow module **832** can be configured to send the customized plans and/or other instructions to the remedy agents **812** of the meta-application agents **804**, to similar remedy agents of the mobile device management system **126** and secure mobile gateway **128**, or to the enterprise agents **320** installed on the mobile devices **120**. These remedy/enterprise agents can be configured to execute the plans and/or other instructions on such systems and devices. A plan can require human (e.g., an IT administrator) confirmation of plan steps at stages of the plan. A plan can also be designed to be executed by the remedy agent **812** without human intervention or approval.

(239) The meta-application **150** of FIGS. 1A and 1B can include all of the components illustrated in FIG. 8, including the components residing within the cloud **156**, and all of such components can reside within the enterprise system **110**.

(240) Meta-application components installed on the mobile devices **120** (e.g., within the enterprise agents **320** or separately) can be configured to collect state metric data from the devices **120** and send the data back to the cloud-based meta-application portion **150** and/or the enterprise system **110**. Such data can be collected regularly (e.g., periodically) or upon specific request by the cloud-based or enterprise system-based meta-application portions. Such data can be analyzed (e.g., by the inference engine **824** using the logic rules **818**) to diagnose problems involving the devices **120**, and to select remedial actions for addressing such problems. Such analysis can be conducted even if there is no currently available connection to the device **120**.

(241) Persons of ordinary skill in the art will understand that the meta-application can be configured to enforce and implement a wide variety of different types of logic rules **818** and remedial actions **820** involving the mobile devices **120**. For example, a logic rule **818** can define a problem as the downloading of more than a particular threshold amount of data to a mobile device **120**. The enterprise backend portion of the meta-application can detect the throughput of data downloaded to a user's device **120** and determine if it exceeds the threshold defined in the rule **818**. A remedial action **820** associated with the rule **818** can require the disabling of the mobile device **120**, or perhaps merely the disabling of the device's ability to download data. Such remedial actions **820** may involve the meta-application sending to the device's enterprise agent **320** a command or script configured to enforce the remedy. Alternatively, the remedial action **820** can require the revocation of the mobile device's certificate by the mobile device management system **126**. Still further, the rule **818** can revoke the device's permission to use application tunnels for communicating with enterprise resources **130** or other network resources.

(242) In another example, the meta-application **150** can be configured to create gateway rides **404** based at least partly on the time(s) at which a mobile device **120** was "wiped" (e.g., deletion of some or all data stored on the device or removal of software application(s) from the device).

(243) In an embodiment in which the meta-application **150** is configured to manage Microsoft Exchange™, the meta-application **150** can have full visibility into the ActiveSync partnership data for the mobile devices **120** associated with the enterprise. The meta-application **150** can use the ActiveSync partnership data to generate gateway rules **404** that filter mobile device access requests **402** based on such data. For example, the ActiveSync partnership data includes the ActiveSync DeviceID's of the mobile devices **120**. The meta-application application **150** can use this information to generate gateway rules **404** that filter access requests **402** based on the known DeviceID's.

#### (244) Device-Resident Management System

(245) In certain embodiments, an enterprise may wish to regulate the settings, applications, uses, other activities, or any combination thereof associated with the mobile devices **120** used by the enterprise's users **115**. This can safeguard against threats to the security of enterprise data and resources and/or to address productivity risks—the risk of users using then mobile devices **120** in ways that can negatively affect user productivity in meeting the user's duties toward the enterprise. Such embodiments are now described.

(246) With continued reference to FIG. 2, the illustrated mobile device management system **126** includes a computer-readable storage repository **212** storing a plurality of different mobile device rules **214**. The storage repository **212** can be implemented on any suitable non-transitory computer-readable medium. A mobile device rule **214** can be an encoded, computer-readable rule configured to be used by a mobile device **120** (e.g., by an enterprise agent **320** installed on the mobile device **120**) to detect a problem indicative of a security risk and/or a productivity risk to which the device **120** can expose the enterprise. Numerous examples or “use cases” of problems that can be detected using the mobile device rules **214** are described below.

(247) The mobile device rules **214** can be relatively simple, taking the form of, for example, IF-THEN statements and/or simple declarative logic rules. In other embodiments, the mobile device rules **214** can be much more complex, such as the logic rules described in Qureshi '536, which describes logic rules that are configured to be used to generate virtual circuits that have atomic gates and downstream operator gates. The mobile device rules **214** can include metadata for calculating various parameters associated with the rules and related problems, such as a confidence value indicative of a confidence in the detection of the problem associated with a mobile device rule **214**, for example, as taught by Qureshi '536.

(248) In some embodiments, a mobile device rule **214** has the following format: <rule name> <security key><authentication information> <encrypt><rule body>

The rule name can be a name of the particular mobile device rule **214**. If the rule **214** is encrypted, the security key can allow the enterprise agent **320** to decrypt the rule body. The authentication information can include data concerning the applicability of the rule to the mobile device **120**. The enterprise agent **320** can use the authentication information to determine whether the rule **214** can am on the mobile device **120**. The rule body includes the underlying logic of the rule, and is the part that the enterprise agent **320** evaluates in order to detect problems and execute one or more associated remedial actions **216**.

(249) In certain embodiments, a mobile device rule **214** maps one or more mobile device state

metric data values to one of a plurality of the aforementioned problems indicative of security risks and/or productivity risks to which the devices **120** can expose the enterprise. A “state metric” can be any data item indicative of a mobile device state, such as error log entries, records of activations of device features, operating system version, installed software applications **318** (including applications that the enterprise may have “blacklisted” as not being authorized for installation), whether the mobile device **120** is roaming, a battery level of the mobile device **120**, a signal strength of a signal received by of the mobile device **120**, available memory of the mobile device **120**, etc. For example, a “state metric” can be a metric that indicates whether a mobile device feature (e.g., a camera, web browser, password-protection, etc.) has been activated. Another example of a state metric is an indicator of whether the mobile device's SIM card is properly engaged with the mobile device **120**. Other examples of state metrics will be apparent from the examples of mobile device rule applications provided below.

(250) With continued reference to FIG. 2, the repository **212** can include a plurality of encoded, computer-readable remedial actions **216** for countering the problems. In some embodiments, each of the remedial actions **216** corresponds to one or more of the problems associated with the mobile device rules **214**. Examples of remedial actions **216** are provided below. In some embodiments, the mobile device management system **126** (or another component of the enterprise system **110**) can include tools **221** that assist IT personnel in the creation and/or editing of mobile device roles **214** and/or remedial actions **216**. Such tools **221** can comprise, e.g., a customized word processor or other software application with extensions, tutorials, and the like to help construct the rules **214** and/or actions **216**.

(251) In certain embodiments, the mobile device rules **214** and their associated remedial actions **216** are organized into separate “rule packages,” each rule package including one or more of the rules **214** and preferably the rules' associated remedial actions **216**. Each rule package can be designed or customized for users **115** with specific types of user roles **206** and/or mobile device properties **208**. Accordingly, each rule package can be associated with one or more of the user roles **206**, and/or with one or more of the mobile device properties **208**. For example, a rule package of mobile device rules **214** and associated remedial actions **216** can be prepared for all users **115** having roles **206** that that are sales-oriented (e.g., all sales people of the enterprise). As another example, one rule package can be prepared for people using iPhones™ and another rule package can be prepared for people using Android™ devices. If it is desired to differentiate the permissible activities associated with mobile device users **115** having a given role **206**, based on differences in their mobile device properties **208**, then different rule packages of mobile device rules **214** and associated remedial actions **216** can be formed for the different types of mobile devices **120**. For example, an enterprise can form one rule package of mobile device rules **214** and remedial actions **216** for sales people using iPhones™, another rule package of mobile device rules **214** and remedial actions **216** for sales people using Android™ devices, and so on. In this manner, rule packages can be customized as desired for different user roles **206** and/or mobile device properties **208**.

(252) It will be appreciated that different mobile device rule packages can share common mobile device rules **214** and/or remedial actions **216**. For example, suppose that a first mobile device rule and an associated remedial action is suitable for sales people and corporate board members, and a second mobile device rule and associated remedial action is only suitable for sales people. A rule package for users **115** that are sales people can include the first and second mobile device rules

and their remedial actions, while a mobile device rule package for users **115** that are board members of the corporate enterprise may include the first mobile device rule and remedial action but not the second mobile device rule and remedial action. Many other examples are possible and are in accordance with the principles and advantages described herein.

(253) The mobile device manager **202** is preferably responsible for sending appropriate rule packages to the mobile devices **120**, based on, e.g., the properties **208** of the mobile devices and/or the roles **206** of the users **115** assigned to the mobile devices. In certain embodiments, a deployment rule is associated with each rule package or individual mobile device rule **214** and associated remedial actions **216**. The mobile device manager **202** can be configured to use the deployment rule to determine which mobile devices **120** to send the rule package or individual mobile device rule **214** and associated remedial actions **216**. A deployment rule can cause the mobile device manager **202** to access the mobile device information **204** to identify the mobile devices **120** whose assigned users **115** have a role **206** associated with a given one of the rule packages or rules, and/or the mobile devices **120** whose properties **208** are associated with the given rule package or rule. Further, the mobile device manager **202** can be configured to send the given rule package (including mobile device rules **214** and/or remedial actions **216**) to the identified mobile devices **120**. In this manner, the mobile device manager **202** can send the appropriate mobile device rule packages) to each mobile device **120**.

(254) For example, suppose that a new mobile device user **115** (e.g., a new employee) joins the enterprise. The new user's role information **206** and/or mobile device properties **208** can be entered (by administrators and/or by a computer-automated process) into the enterprise's mobile device information **204**. In one embodiment, the user's role information **206** is entered into an RBAC system of the enterprise, and a software module (such as the mobile device manager **202**) transfers the role information **206** to the mobile device information **204**. In another embodiment, the user role information **206** of the mobile device information **204** is an RBAC role repository that directly supports an RBAC system. The mobile device manager **202** can be configured to use the new user's role information **206** and/or mobile device properties **208** to determine an appropriate mobile device rule package to send to the new user's mobile device **120**. In another embodiment, the mobile device information **204** does not come from or support an RBAC system.

(255) In another example, suppose that an enterprise modifies its policies regarding a particular group of mobile device users **115**. IT personnel can modify a mobile device rule package customised for the particular user group. This can include creating new mobile device rules **214** for the rule package, deleting rules **214** from the rule package, and/or modifying some of the rules **214** of the rule package. Alternatively or additionally, modifying the mobile device rules package can include creating, deleting, and/or modifying remedial actions **216** of the rules package. The mobile device manager **202** can send the updated mobile device rule package to each of the mobile devices **120** of the users **115** of that particular group.

(256) In many cases, the updated mobile device rule package may be fairly similar to older mobile device rule packages that have already been sent to the users' mobile devices **120**. In such cases, the mobile device manager **202** can be configured to send only the new and/or modified mobile device rules **214** and/or remedial actions **216** to each mobile device **120**, along with instructions for deletion of those rules **214** and/or actions **216** that have been deleted from the rule package, such instructions being carried out by the enterprise agent **320** of each mobile device **120**. In this manner, the mobile device manager **202** can be configured to send mobile device rule package



updates to the mobile devices **120**.

(257) In certain embodiments, the enterprise agent **320** is configured to implement and/or execute the mobile device rules **214** on the mobile device **120**. Accordingly, the enterprise agent **320** is preferably configured to receive (e.g., via the network interface **310**) mobile device rules **214** and/or remedial actions **216** from the mobile device management system **126** associated with the enterprise, and store the received rules **214** and/or remedial actions **216** in a computer-readable storage of the mobile device **120**, such as the hard drive **306** or a memory card inserted into the memory card port **307**. The enterprise agent **320** can be configured to receive and store the aforementioned mobile device rule packages and rule package updates from the mobile device management system **126** and store them on the hard drive **306** or memory card. In the illustrated embodiment, the hard drive **306** stores a plurality of mobile device rules **214** and remedial actions **216**. In some embodiments, the enterprise agent **320** is configured to separately store the mobile device rules **214** and remedial actions **216** of the rule packages and/or rule package updates. In other embodiments, the mobile device rules **214** and their corresponding remedial actions **216** are stored together in association with one another. In some embodiments, a mobile device **120** can receive mobile device rules **214** and/or remedial actions **216** from sources other than the mobile device management system **126**.

(258) FIG. 9 is a high-level flowchart illustrating an embodiment of a method in which a mobile device **120** applies mobile device rules **214** to detect security-related or productivity-related problems associated with the mobile device **120**, and in which the mobile device **120** addresses the problems. According to the method illustrated in FIG. 9, in step **902** the enterprise agent **320** obtains or receives state metric data values associated with the mobile device **120**. These state metric data values are preferably for state metrics represented in one or more of the mobile device rules **214**. The enterprise agent **320** can be configured to obtain or receive one or more state metric data values from other hardware, software, or firmware components of the mobile device **120**. The enterprise agent **320** can be configured to proactively gather data values of certain state metrics, for example by issuing an API call for data. For other state metrics or operating systems, the agent **320** can subscribe to a notification callback mechanism of the mobile device **120**, so that the mobile device **120** notifies the enterprise agent **320** about certain events that occur on the mobile device **120**.

(259) With continued reference to FIG. 9, in step **904** the enterprise agent **320** detects one or more problems defined by the mobile device rules **214**. The enterprise agent **320** is preferably configured to programmatically detect instances of the problems, at least in-part, by using the mobile device rules **214** to analyze the received state metric data values. In certain embodiments, the received state metric data can be analyzed in combination with other data values (e.g., user properties, time of day, date, etc.). Further, the enterprise agent **320** can be configured to respond to a detected instance of one of the problems by executing, in step **906**, one of the remedial actions **216** on the mobile device **120**, in which the executed remedial action **216** corresponds to the problem detected in step **904**. In some cases, there may be multiple remedial actions **216** corresponding to a particular problem, and the enterprise agent **320** may be configured to select among the available remedial actions based on various factors, such as likelihood of successfully countering the problem (e.g., based on past results of running remedial actions), computing costs associated with executing the remedial actions, user preferences, enterprise preferences, and the like. In certain instances, the enterprise agent **320** can execute two or more remedial actions **216** in response to

detecting a particular problem.

(260) Some remedial actions **216** can comprise producing an alert, such as a message delivered to the user **115** of the mobile device **120**. The message can include text, images, audio, and/or video. The enterprise agent **320** can be configured to produce the message and convey the message to the user **115** via the user interface **304**, such as displaying the message on the screen **326** and/or playing an audible message using the speaker **328**. The message can comprise information about a detected problem, and/or instructions to the user **115** to execute an action on the mobile device **120**, such as activating or deactivating a feature of the device **120**. The message can be statically defined in the remedial action **216**. Alternatively, the message can be defined using variables that can be bound to actual data values when evaluating a mobile device rule **214** (e.g., by the resolution of queries), for example, as taught in Qureshi '536. This can allow the enterprise agent **320** to customize the message to the specific circumstances of the device **120**. Further, any remedial action **216** instructing the agent **320** to produce such a message can further include instructions for actions to be conducted by the enterprise agent **320** if the user **115** (or other person handling the mobile device **120**) does not execute the action instructed by the message. For example, the remedial action **216** can cause the enterprise agent **320** to conduct the action if the user **115** does not execute the instructed action within a time period defined in the remedial action.

(261) An enterprise can vary the punitiveness of the remedial action **216** to be applied for a detected problem or violation of a mobile device rule **214** based on properties of the mobile device **120** and/or its user **115**. For instance, it may be desirable to vary the remedy based on the role **206** of the user **115**. In one example, an enterprise may wish to apply less stringent remedial actions for higher level executives of an enterprise.

(262) As noted above, some remedial actions **216** can comprise an action (other than generating and conveying a message to the user) executed by the enterprise agent **320** on the mobile device **120**. In certain embodiments, the remedial actions **216** can comprise actions that the mobile device **120** is already designed to conduct, such as activating or deactivating certain mobile device features, adjusting device settings, and the like. In such cases, the enterprise agent **320** can be configured to use the mobile device's API's to conduct such remedial actions **216**.

(263) In some embodiments, the enterprise agent **320** includes a scripting engine **322**, and at least one of the remedial actions **216** comprises a script that the scripting engine **322** is configured to execute on the mobile device **120**. The scripts can be written in a scripting language associated with the mobile device **120**, which can be a command set targeted at controlling the device hardware, software, and/or operating system. The scripting engine **322** can be configured to interpret a script, and/or to convert, the script to a bytecode or other form that can be interpreted relatively quickly. In some cases, the mobile device management system **126** (or another component of the enterprise system **110**) can include one or more script-creation tools or applications **220** that assist IT personnel in the creation of the scripts.

(264) In some embodiments, a script can have the following high-level format: # USE CASE: [description of what the script does] import android import zenlib [decryption & authentication] [rule body]

In this example, the script imports a library of code ("android") associated with the Android™ operating system, as well as a library of compiled code ("zenlib") that interprets the rule body and

decryption and authentication information. For example, the “zenlib” code can be configured to interpret logical, mathematical, and/or Boolean operators such as “AND,” “OR,” “THEN,” “LESS THAN,” “MORE THAN,” etc.

(265) From the various use cases described below, it will be appreciated that it is possible to provide many different types of mobile device rules **214** that cause the enterprise agent **320** to detect and guard against various types of problematic events associated with the mobile device **120**. It is also possible to provide many different types of corresponding remedial actions **216** that cause the agent **320** to react to such problematic events by conducting various types of actions, such as restricting network communications, enforcing password-protections, sending reports back to the enterprise system **110** (e.g., reports of data content stored on the mobile device **120**, data usage on the device **120**, applications **318** running on the mobile device **120**, and many other types of information), deleting data from the device **120**, uninstalling applications **318** from the mobile device **120**, and many other actions.

(266) The use of mobile device rules **214**, remedial actions **216**, and/or scripts to be run by the scripting engine **322** can be leveraged to conduct compliance audits of mobile devices **120**. In certain embodiments, an enterprise system **110** can be configured to cause the enterprise agents **320** of all or just some of the mobile devices **120** enrolled with the mobile device manager **202** to run one or more mobile device rules **214** at the request of the enterprise.

(267) For example, suppose that the enterprise learns of a new computer virus to which the enterprise's mobile devices **120** may be particularly vulnerable. In such a case, the enterprise's IT personnel can cause the mobile device manager **202** to send instructions to the enterprise agents **320**, for example, to run a particular mobile device rule **214** that scans for the new virus or simply determines whether the mobile device **120** is using the latest antivirus software updates.

(268) In some cases, the enterprise's IT personnel can cause the mobile device manager **202** to send one or more “special” mobile device rules **214** to the mobile devices **120**. In certain instances, the special mobile device rules **214** can be sent with instructions for the enterprise agents **320** to immediately determine whether the mobile devices **120** comply with these rules. Also, the special mobile device rules **214** can be sent with associated remedial actions **216**, and it will be understood that different types of these special mobile device rules **214** and remedial actions **216** can be sent to different types of mobile devices **120**. The mobile device manager **202** can send a special mobile device rule **214** to all of the mobile devices **120** whose assigned users **115** have particular roles **206**. These special mobile device rules **214** may or may not be the same as the mobile device rules **214** and remedial actions **216** provided within the customized rule packages described above.

(269) Upon receipt of such a special mobile device rule **214** and possibly a special remedial action **216**, or upon receipt of instructions to run a mobile device rule **214** already stored on the mobile device **120**, a mobile device's enterprise agent **320** can be configured to immediately determine whether the mobile device **120** is in compliance with the rule **214**. If the mobile device **120** is not in compliance, the enterprise agent **320** can be configured to simply implement the special remedial action **216**.

(270) Alternatively or additionally, the agent **320** can be configured to send a compliance report to the mobile device manager **202**, detailing the results of running the special mobile device rule **214** (e.g., a report detailing compliance or non-compliance with the rule, and/or a degree of

compliance). The mobile device manager **202** can be configured to use these reports for various purposes. For example, the mobile device manager **202** can respond to the reports by sending, only to those mobile devices **120** that are not in compliance with the executed mobile device rule(s), (1) instructions for the agent **320** to run one or more additional mobile device rules **214** and, if the mobile device **120** is not in compliance with the additional mobile device rules **214**, one or more additional remedial actions, or (2) additional special mobile device rules **214** and/or special remedial actions **216**. These additional mobile device rules **214** can check for other forms of non-compliance, based on the assumption that a mobile device **120** that does not comply with one mobile device rule **214** is more likely to be out of compliance with other mobile device rules **214**.

#### (271) Example Use Cases for Device-Resident Management System

(272) There are numerous possible “use cases” for which an enterprise may wish to use a mobile device rule **214** and an associated remedial action **216** on a mobile device **120**. Examples of such use cases are now described. It will be understood that the following examples are not exhaustive, and that many different types of mobile device rules **214** and associated remedial actions **216** can be used for many different purposes. Further, skilled artisans will understand that a remedial action described below for a particular use case can be alternatively be executed for any other mobile device rules, problems, or use cases, as may be desired by the enterprise. Some of the use cases described below contain one or more sub-cases, also described below. Finally, some of these use cases overlap in certain ways.

(273) Use Case 1: One possible use case involves a situation in which a mobile device **120** is lost or stolen from its assigned user **115** (FIG. 1A). A mobile device rule **214** can define conditions for concluding that the device is lost or stolen. The mobile device rule **214** can specify that a mobile device **120** is lost or stolen, for example, when a different SIM card is installed, when a certain period of time elapses without a user login, or when the mobile device is reported as lost or stolen. An associated remedial action **216** can cause the enterprise agent **320** to remove data and/or software applications **318** from the mobile device **120**, such as enterprise-related applications, all applications, enterprise-related data, or all data. An alternative remedial action **216** can cause the agent **320** to lock the device **120** to render it unusable. These remedies are useful because the mobile device **120** may contain valuable and/or confidential enterprise-related data that is desired to be kept from persons not associated with the enterprise. In some implementations, then the enterprise system **110** can issue a command to the device **120** to delete the data and/or destroy an encryption key used to decrypt the data. This command can be sent by the mobile device management system to the mobile device **120** over a wireless carrier network **125**.

(274) Use Case 2: This use case relates to Use Case 1. A thief can prevent a wireless command, sent from the enterprise system **110**, from reaching the mobile device **120** by removing the device's SIM card (or, depending on the mobile device **120**, a similar or equivalent card that securely stores, e.g., the service-subscriber key (IMSI) used to identify a subscriber on the mobile device **120**) from the SIM card port **312**, which can effectively disable the connectivity of the mobile device **120** to the carrier network **125**. In such an instance, the enterprise may be prevented from deleting the data from the device **120**, and the thief may be able to access the data. This problem can be addressed by providing a mobile device rule **214** that the enterprise agent **320** uses to detect the disengagement of the SIM card from the SIM card port **312** of the device **120**. In this use case, the agent **320** can execute a remedial action **216** that comprises producing a message delivered via the user-interface **304**, the message instructing the person using the device **120** (e.g., the user **115**

or a thief) to reengage the SIM card with the SIM card port **312**. For example, the message can instruct the person to reengage the SIM card with the SIM card part **312** within a specified time period (e.g., five minutes), or all of the data on the mobile device **120** (or just the enterprise-related data) will be deleted. In that ease, the agent **320** can be further configured to delete the data if the SIM card is not reengaged within the specified time period. Alternatively or additionally, an encryption key used to decrypt the enterprise data can be invalidated or deleted as a remedial action associated with problems related to the SIM card disengagement.

(275) Use Case 3: The enterprise agent **320** can use a mobile device rule **214** to detect a problem defined as the disablement of password-protection for the mobile device **120**. A corresponding remedial action **216** can cause the agent **320** to produce a message on the user interface **304**, the message instructing the user **115** to activate password-protection on the device **120**, perhaps within a specified time period. The remedial action **216** can further include instructions for the agent **320** in the event that password-protection is not activated, such as disabling the mobile device **120**, deleting enterprise-related data from the device **120**, decommissioning the device **120** (e.g., revoking its certificate and/or terminating its enrollment with the mobile device manager **202**), and the like. It will be understood that deleting data from the mobile device **120** (in the context of this use case or any other) can include permanently deleting the data or, alternatively, merely deleting pointers to the data or deleting and/or invalidating data decryption keys. In a related example, a mobile device rule **214** can require the user **115** to change the password periodically, such as every 90 days.

(276) Use Case 4: The enterprise agent **320** can use a mobile device rule **214** to detect a problem defined as the mobile device **120** being located outside of an authorized geographical zone, or the device being located within an unauthorized geographical zone. A geographical zone can be specified in a variety of different ways, such as by inputting a location (e.g., on a map, or longitude/latitude values), a shape and size of the geographical zone, and a positional relationship between the inputted location and the shape of the zone. For example, a circular zone centered about the inputted location can be defined by specifying a radius of the geographic circle. A mobile device rule **214** can also include time ranges (hours, days, etc.) within which the restriction applies. The agent **320** can detect the location of the device **120** using the GPS chip **316**.

(277) A corresponding remedial action **216** can cause the agent **320** to produce a message delivered via the user interface **304**, the message instructing the user **115** to return the device **120** to the authorized geographical zone or leave the unauthorized zone, for example, within a specified time period. The remedial action **216** can further include instructions for the agent **320** in the event that the device **120** is moved as instructed, such as disabling the mobile device **120**, disabling features or software applications (e.g., the camera, Bluetooth connectivity, Wi-Fi connectivity etc.) of the device **120**, deleting enterprise-related data from the device **120**, and the like. A remedial action **216** can simply send a communication (e.g., SMS text, email) to appropriate authorities of the enterprise, alerting them to the mobile device's location.

(278) Use Case 5: As described above in Use Case 4, mobile device rules **214** can effectively lead to activation or deactivation of mobile device features based on a location of the mobile device **120** (e.g., as determined by using the GPS chip **316**) and/or temporal data. The mobile device feature in question can be the user interface **304** (keyboard, touchscreen, etc.), network interface **310**, camera **314**, microphone **330**, USB connection, etc.

(279) Take for example the camera **314**. The enterprise agent **320** can use a mobile device rule **214** to detect a problem defined as the mobile device **120** being located within premises of the enterprise with the camera **314** being available for use. An enterprise may wish to prevent use of the camera **314** while the mobile device **120** is within the enterprise premises, to prevent the camera from capturing any sensitive or confidential information, images, or video from within the premises. As used herein, “enterprise premises” can include any buildings, facilities, factories, campuses, design houses, or other structures or areas owned, used, or operated by the enterprise. In one embodiment, a remedial action **216** corresponding to this problem can cause the agent **320** to deactivate or disable the camera **314** without the user's consent. In another embodiment, a remedial action **216** corresponding to this problem can cause the agent **320** to produce a message delivered via the user interface **304**, the message instructing the user **115** to deactivate or disable the camera **314**, perhaps within a specified time period. The remedial action **216** can further include instructions for the agent **320** in the event that the user **115** does not deactivate or disable the camera **314**, such as deactivating or disabling the camera **314** without the user's consent. Preferably, after the remedial action **216** has been executed (and the camera **314** has been disabled), the agent **320** is configured to detect when the mobile device **120** has left the enterprise premises. At that point, the agent **320** can be configured to either reactivate the camera **314** without the user's consent, or produce a message delivered via the user interface **304**, informing the user **115** that the user is authorized to reactivate the camera **314**.

(280) Use Case 6: Related to Use Case 5, another example of a mobile device “feature” that can be regulated based on mobile device location is a software application **318**, such as the device's web browser. For example, the enterprise agent **320** can use a mobile device rule **214** to detect a problem defined as the mobile device **120** being located within premises of the enterprise with the device's web browser being available for use. Corresponding remedial actions **236** can cause the agent **320** to instruct the user to disable the web browser (by producing a message on the user interface **304**), or to simply disable the web browser without the user's consent. Then, when the mobile device **120** subsequently leaves the enterprise premises, the agent **320** can be configured to detect this and either inform the user that the web browser can be used or simply re-enable the web browser without the user's knowledge or consent. It will be appreciated that other software applications **318**, aside from the web browser, can be regulated similarly.

(281) Use Case 7: Related to Use Cases 4 and 5, upon detecting that the mobile device **120** has entered a defined geographical area (e.g., the enterprise premises), the enterprise agent **320** can be configured to execute a remedial action **216** that causes the agent **320** to require the user **115** to enter a password into the device **120** in order to use certain device features, such as the camera **314** and/or web browser. Such a remedial action may be more appropriate for users **115** whose roles **206** require the users to have access to such features within the geographical area. Once the mobile device **120** leaves the defined area, the agent **320** can be configured to no longer require the password for the user **115** to use such mobile device features.

(282) Use Case 8: A mobile device rule **214** can cause the enterprise agent **320** to disable certain mobile device features (e.g., camera, microphone) based on temporal information (possibly without considering geographical data), such as the time of the day, the day of the week, a date range of the calendar, etc.

(283) Use Case 9: The mobile device **120** can comprise a credit card scanner for use within a store or other retail establishment. When an agent **320** of the scanner detects that the scanner has

physically left the store, the agent can execute a remedial action **216** that instructs a user **115** of the scanner to return the scanner to the store, perhaps within a specified time period. The remedial action **216** can further include instructions to delete scanned credit card data from the scanner if the scanner is not returned to the store.

(284) Use Case 10: Another mobile device feature that can be regulated is the device's network connection capability, such as the network interface **310**. The enterprise agent **320** can use a mobile device rule **214** to detect a problem defined as the mobile device's use of the network connection capability to connect or attempt to connect to a communication network that is unsecured or blacklisted by the enterprise (e.g., a false base Wi-Fi station). For example, the user **115** may attempt to connect to an unsecured Wi-Fi network or blacklisted cellular service towers, which may expose the mobile device **120** to a security threat. A remedial action **216** can prevent the device **120** from accessing the restricted network(s).

(285) In another embodiment, a remedial action **216** corresponding to this problem can cause the agent **320** to terminate or prevent the mobile device's connection to the unsecured network, without the user's consent. In another embodiment, the remedial action **216** can cause the agent **320** to deactivate the mobile device's network connection capability (e.g., by shutting down the network interface **310**), without the user's consent. Such an action may leave one type of network communication capability cellular networks, such as 3G or 4G networks) available, while only terminating a network communication capability (e.g., Wi-Fi) associated with the connection to the unsecured network. In another embodiment, the remedial action **216** can cause the agent **320** to produce an audio alert to the user **115** or a message delivered via the user interface **304**, the message instructing the user **115** of the device **120** to terminate the connection to the unsecured network, perhaps within a specified time period. In yet another embodiment, the remedial action **216** can cause the agent **320** to produce a message delivered via the user interface **304**, the message instructing the user **115** of the device **120** to deactivate the device's network connection capability, perhaps within a specified time period. In embodiments in which the agent **320** produces a message delivered via the user interface **304**, the remedial action **216** can further include instructions for the agent **320** in the event that the user **115** does not terminate the connection or deactivate the network connection capability, such as taking one of such actions without the user's consent. In still other embodiments, a remedial action **216** can cause the agent **320** to lock the mobile device **120** to render it unusable, perhaps until the device disconnects from the unsecured or blacklisted communication network.

(286) Use Case 11: An enterprise may wish to regulate which software applications **318** are authorized for installation on a mobile device **120**. For example, certain types of software applications **318** can negatively impact a user's productivity (e.g., by distracting the user from his or her duties), while other applications **318** can introduce a security threat (e.g., file-sharing applications that may allow other devices to copy enterprise data stored on the mobile device **120**, or a rogue application that has malware or has been determined to collect device data and send the data to a rogue server). The enterprise agent **320** can use a mobile device rule **214** to detect a problem defined as the mobile device **120** having installed a software application **318** that the enterprise has blacklisted (e.g., forbidden for installation) or at least not white-listed (expressly permitted for installation). The agent **320** can be configured to use device-specific API's to determine which applications are installed on the mobile device **120**.

(287) Since different mobile device platforms vary as to the ability of an enterprise system **110** to

uninstall the unauthorized application **318** without the user's consent, several different remedial actions **216** are possible. In one embodiment, a corresponding remedial action **216** can cause the agent **320** to producing a message on the user interface **304**, the message instructing the user **115** to uninstall the unauthorized software application **318** from the mobile device **120**, perhaps within a specified time period. The remedial action **216** can further include instructions for the agent **320** in the event that the user **115** does not uninstall the unauthorized application **318**, such as disabling the mobile device **120**, uninstalling the unauthorized application **318** (e.g., by causing the scripting engine **322** to run a script or plan that uninstalls the application), preventing the unauthorized application **318** from starting or running (e.g., by causing the scripting engine **322** to run a script that terminates one or more processes associated with the unauthorized application **338**), deleting enterprise-related data from the device **120** (which can also be achieved by the scripting engine **322** running an appropriate script), sending an alert message (SMS text, email, etc.) to enterprise authorities about the installation of the blacklisted software application, and the like. In another embodiment, a corresponding remedial action **216** can cause the agent **320** to uninstall the unauthorized application **318** from the mobile device **120** without the user's consent. For mobile device platforms that do not permit an enterprise system **110** to uninstall software applications **318** from a mobile device **120** without the user's consent, the enterprise may opt to cause the agent **320** to use the scripting engine **322** to run a script that terminates one or more processes associated with the unauthorized application **318**, thereby preventing it from running on the mobile device.

(288) An enterprise can vary the punitiveness of the remedial action based on the role **206** of the user **115** assigned to the mobile device **120** that is running an unauthorized software application **318**. For example, consider a corporate enterprise having some users **115** with roles **206** corresponding to high level executives, other users **115** having roles **206** corresponding to mid-level managers, and other users having roles **206** that correspond to lower level employees. For a high level executive whose mobile device **120** has an unauthorized application **318**, the agent **320** can implement a remedial action **216** that simply instructs the user **115** to uninstall the application **318**. For a mid-level manager whose mobile device **120** has an unauthorized application **318**, the agent **320** can implement a remedial action **216** that causes the scripting engine **322** to terminate one or more processes associated with the unauthorized application **318**, thereby preventing it from running on the mobile device **120**. Moreover, the agent **320** might run such a script only under certain conditions (e.g., when the mobile device is on enterprise premises during normal working hours). Finally, for a lower level employee whose mobile device **120** has an unauthorized application **318**, the agent **320** can implement a remedial action **216** that uninstalls the application **318** without the user's consent. Skilled artisans will appreciate that an enterprise can vary its remedial actions in many different ways based on different sets of criteria, and that this is just one example.

(289) The enterprise may allow certain software applications **318** to be installed on a mobile device **120**, but only under certain conditions, such as conditions relating to user roles **206** and/or mobile device properties **208**. An enterprise may allow users **115** with particular roles **206** to install such applications **318** on their devices **120**, while disallowing other users **115** from doing so. An enterprise may allow mobile devices **120** having certain device-types to install particular software applications **318**, while disallowing the same for different device types. Prohibitions on the installation of particular software applications **318** on the mobile devices **120** can be regulated in a very flexible and customizable way, by defining appropriate mobile device rules **214**.



(290) Use Case 12: Related to Use Case 11, a mobile device rule **214** can define a problem as an attempt to run (as opposed to install) a software application **318** in violation of defined restrictions. Such restrictions can be temporal (the application is allowed to run only during certain times and/or days), geographical (the application is allowed to run only when the mobile device **120** is in one or more defined geographical zones), password-dependent (the application is allowed to run only if the user provides a correct password associated with the application), other types of restrictions or conditions, or combinations thereof.

(291) In one embodiment, the rule **214** includes a list of restricted or blacklisted applications **318**, and possibly even a list of unrestricted or white-listed applications **318**. The enterprise agent **320** can use an application monitor service **334** (which can be part of the agent **320** itself or alternatively another part of the mobile device **120**, as shown) to detect which applications **318** or processes are running. For example, the Android™ operating system provides a mechanism for collecting and viewing system output, whereby logs from various applications and portions of the system are collected in a series of circular buffers, which then can be viewed and filtered by the “logcat” command. The “logcat” command can be used from an ADB (Android Debug Bridge) shell to read the log messages. Alternatively, Android's Dalvik Debug Monitor Server (DDMS) can automatically report “logcat” information via connection to ADB. Hence, in a mobile device **120** running the Android™ operating system, the enterprise agent **320** can be configured to “listen” to certain “logcat” information and detect the invocation of mobile device applications of interest. It will be appreciated that other mobile device operating systems provide alternative systems and methods for detecting the invocation of mobile device applications.

(292) When the agent **320** determines that an application **318** is invoked, the agent **320** determines if the application is blacklisted (or white-listed). If the application **318** is white-listed or at least not blacklisted, the agent **320** allows the application to run. If the application **318** is blacklisted (or perhaps, more strictly, not white-listed), the agent **320** can use the rule **214** to determine the defined restriction(s) for the application and whether the restrictions apply. For example, if a restriction is temporal, the agent **320** can determine if allowing the application to run currently would violate the temporal restriction. If a restriction is geographical, the agent **320** can determine if the device **120** is in a restricted geographical zone. If a restriction is password-dependent, the agent **320** can invoke a password input activity (which can be part of a remedial action **216**) that prompts the user **115** for a password associated with the application **318**. If any of the restrictions is violated (e.g., unauthorized time or day, device **120** outside of authorized geographical zone, incorrect password provided, other restrictions, combinations of these restrictions, etc. as defined by the rule **214**), then the agent **320** can prevent the application **318** from running by, e.g., using the scripting engine **322** to run a script that kills the application.

(293) In certain embodiments, the agent **320** is configured to terminate a running application **318** if the use restriction is violated after the application **318** was invoked. In other words, if the use conditions are met at the invocation of the application **318**, but then subsequently violated during the use of the application **318**, the agent **320** can be configured to kill the application **318**. For example, suppose that the applicable mobile device rule **318** allows for an application **318** to be used only during a defined time window, and that the application **318** is invoked during the allowed time window but then remains in use at the expiration of the time window. In this case, the rule **318** may direct the agent **320** to terminate the application **318**. In another example, suppose that the mobile device rule **318** allows for an application **318** to be used only when the mobile device **120** is

in a defined geographical zone, and that the application **318** is invoked when this condition is met. Suppose further that the user **115** takes the device **120** outside of the defined geographical zone during the use of the application **318**. In this case, the rule **318** may direct the agent **320** to terminate the application **318** as soon as the device **120** leaves the defined geographical zone.

(294) Use Case 13: A mobile device rule **214** can also define a problem as the removal of a required software application **318** from the mobile device **120**. A user **115** might accidentally or intentionally uninstall the application. An associated remedial action **216** can cause the enterprise agent **320** to notify the user **115** of the removal of the application **318**, and that its reinstallation is required.

(295) Use Case 14: Related to Use Case 13, a mobile device rule **214** can also be used by the enterprise agent **320** to detect when a required software application **318** is installed but not running on the mobile device **120**. An associated remedial action **216** can cause the enterprise agent **320** to notify the user **115** and instruct the user to run the required application.

(296) Use Case 15: The enterprise agent **320** can use a mobile device rule **214** to detect a problem defined as the mobile device **120** storing enterprise-related data for which the device is not authorized to store. In one embodiment, a corresponding remedial action **216** can cause the agent **320** to produce a message on the user interface **304**, the message instructing the user **115** to delete the unauthorized enterprise-related data from the mobile device **120**, perhaps within a specified time period. The remedial action **216** can further include instructions for the agent **320** in the event that the user does not delete the data, such as deleting the data from the device **120** without the user's consent, disabling the device **120**, and the like. In another embodiment, a corresponding remedial action **216** can cause the agent **320** to delete the enterprise-related data from the mobile device **120** without the user's consent.

(297) Use Case 16: A mobile device, rule **214** can be used by an enterprise agent **320** to detect when the mobile device **120** is in a roaming network, and an associated remedial action **216** can cause the agent **320** to alert the user **115** of the same. A remedial action **216** can also cause the agent **320** to connect the device **120** to available Wi-Fi networks while the device is roaming.

(298) Use Case 17: A remedial action **216** can cause the agent **320** to begin recording the mobile device's location for a certain time period, such as when the device **120** is roaming. The agent **320** can report this information back to the enterprise system **110**.

(299) Use Case 18: A mobile device rule **214** can cause the enterprise agent **320** to activate or make applicable new mobile device rules **214** if a mobile device **120** goes a certain time period (e.g., a few hours or days) without connecting to the enterprise system **110**.

(300) Use Case 19: A mobile device rule **214** can cause the enterprise agent **320** to toggle the mobile device **120** from its airplane mode if a Wi-Fi or other network becomes available to the device.

(301) Use Case 20: If the mobile device **120** uses a VPN, a mobile device rule **214** can cause the enterprise agent **320** to disable connectivity to networking hotspots.

(302) Use Case 21: Related to Use Case 11, a mobile device rule **214** can cause the enterprise

agent **320** to detect when a user **115** or mobile device **120** attempts to use a software application **318** (e.g., Facebook™, Dropbox™, Gmail™, Hotmail™, etc.) to send enterprise data that is sensitive or confidential. An associated remedial action **216** can cause the agent **320** to kill the software application **318**, uninstall it, or other action preventing the data transfer.

(303) Use Case 22: Related to Use Case 21, a mobile device rule **214** can cause the enterprise agent **320** to detect when a user **115** or mobile device **120** is connected to an enterprise resource **130** and accessing sensitive or confidential data. In certain circumstances, a remedial action **216** can cause the agent **320** to prevent the device **120** from downloading, copying, and/or sending the data to anyone else.

(304) Use Case 23: A mobile device rule **214** can cause the enterprise agent **320** to detect when the number of SMS messages in a mobile device inbox exceeds a defined amount, and an associated remedial action **216** can cause the agent **320** to alert an IT administrator of the same.

(305) Use Case 24: A mobile device rule **214** can cause the enterprise agent **320** to monitor the mobile device's message inbox and detect inbound SMS messages from blacklisted telephone numbers or messages that include enterprise information that is confidential or sensitive. An associated remedial action **216** can cause the agent **320** to alert an IT administrator of the same, disable the device **120**, delete the sensitive messages, disable the device's messaging capability, and the like.

(306) Use Case 25: Related to Use Case 24, a mobile device rule **214** can cause the enterprise agent **320** to monitor the mobile device's outbound message queue and detect outbound SMS messages to blacklisted telephone numbers or messages that include enterprise information that is confidential or sensitive. An associated remedial action **216** can cause the agent **320** to alert an IT administrator of the same, disable the device **120**, delete the sensitive messages, disable the device's messaging capability, and the like.

(307) Use Case 26: A mobile device rule **214** can be used by the enterprise agent **320** to detect when a new or unauthorized SIM card is inserted into the mobile device **120**. A remedial action **216** can cause the agent **320** to send a communication to enterprise authorities of the new SIM card, instruct the user **115** to remove the SIM card, etc.

(308) Use Case 27: A mobile device rule **214** can be used by the enterprise agent **320** to detect a pattern or signature of suspicious behavior by a user **115** of a mobile device **120**. For example, the rule **214** can define a problem involving some logical combination of user behaviors, such as frequenting of blacklisted or suspicious websites, use of blacklisted or suspicious IP addresses, and/or the installation or running of blacklisted mobile device applications. If the agent **320** determines that the behaviors of a user **115** have violated the rule **214**, the agent **320** can enforce a remedial action **216** such as preventing the user **115** from logging into the enterprise system **110**, deleting all enterprise data from the device **120**, etc.

(309) Some mobile device operating systems do not permit an application (such as the enterprise agent **320**) to see what other applications on the device **120** are doing. This is sometimes referred to as the “sandboxing” of applications on the device **120**. Preferably, the mobile device's applications whose usage is necessary to implicate the mobile device rule **214** that defines the user's suspicious behavior pattern are programmed to record these behaviors into a secure

document container **336**, which is described more fully below. By doing so, the agent **320** can be configured to read those suspicious behaviors by accessing the container **336**.

(310) Use Case 28: The enterprise agent **320** can use a mobile device rule **214** to detect a problem defined as the mobile device's receipt of an unauthorized or suspicious network connection. Generally, a mobile device **120** receives much fewer incoming network connections than it generates outgoing connections, because users **115** of mobile devices **120** more typically connect outwardly (e.g., when users **115** browse web sites, search online stores, etc.). Hence, the incoming network connection may be due to an attempt by a third party to hack into the mobile device **120** for nefarious reasons, such as to steal enterprise information, disable the device **120**, and the like. Of course, there are some instances when incoming connections are authorized or benign, such as when a mobile device **120** receives email. However, email is typically received through a well known port of the device **120**, which the agent can be configured to determine. Thus, the enterprise agent **320** can be configured to react to the receipt of an incoming network connection by inspecting parameters of the connection (e.g., the mobile device port for the connection). If the inspection leads to a determination that the incoming connection is authorized, then the agent **320** can be configured to allow the incoming connection. On the other hand, if the inspection leads to a determination that the incoming connection is not authorized or is suspicious, the agent **320** can be configured to execute a corresponding remedial action **216** that denies, prevents, or terminates the unauthorized or suspicious network connection. This functionality may be referred to as a “mobile firewall”.

### (311) Cloud-Based Enterprises

(312) In some embodiments, the enterprise system **110** is provided substantially or entirely within the cloud **156**. Any needed mobile device management systems **126**, secure mobile gateways **128**, and enterprise resources **130** are deployed substantially or entirely within the cloud **156** in such cloud-based enterprise systems **110**. A meta-application system can be deployed within the cloud **156** and/or the mobile devices **120** to help manage the devices **120**. Such embodiments may or may not include a non-cloud enterprise system, or meta-application components deployed within a non-cloud enterprise system.

(313) For example, an enterprise (e.g., a social networking enterprise) can provide mobile devices **120** (e.g., iPads™) to a group of people, with meta-application components being deployed within the devices **120**, and with meta-application components and any needed systems **126**, gateways **128**, and resources **130** being deployed solely within the cloud **156**. In certain embodiments, an enterprise can use policies (e.g., access policies **218**) stored within the cloud **156** and/or the devices **120** to help manage or restrict mobile device communications or access to cloud-based enterprise resources. The meta-application can also be used to monitor/measure/remediate the cloud or cloud-based services used by the enterprise.

### (314) Improved Communication Experience Between Enterprise and Mobile Devices

(315) For many carrier networks **125**, there are typically some geographical areas in which wireless service is weak or unavailable. This can occur in for example, the wireless carrier has relatively few or no cellular communication nodes or towers in such areas. With reference to FIG. 1A, the network connection **142** between the mobile device **120** and the carrier network **125** is often unreliable, particularly when the mobile device **120** is located within such areas with weak or nonexistent

wireless service. Accordingly, the network connection **142, 144** between the mobile device **120** and the enterprise system **110** is often unreliable.

(316) From the perspective of a mobile device **120**, the loss of the network connection **142** can be inconvenient when a user **115** inputs data to be sent to an enterprise resource **130** of the enterprise system **130**. For example, a software application **318** may be configured to open a network connection **142, 144** to the mobile device management system **126** or other network component, and to request data input from the user, typically via the user interface **304** of the mobile device **120**. For instance, an application **318** can be configured to provide one or more data fields on the display **326**, the data fields configured to receive the user's data as text entry via the keypad **324**. The application **318** can be further configured to send the data to the enterprise resource **130** once the data is input by the user **115**. However, if the network connection **142** is lost before the data is sent to the mobile device management system **126**, the application **318** might discard the data that the user **115** input. For example, the application **318** might discard the data upon receipt of a TCP socket error reporting the lost connection **142**. Or, the application **318** may attempt to send the data to the mobile device management system **126** and wait for a reply. Since the connection **142** is lost, the application **318** would eventually time-out after receiving no reply for a certain time period. In either case, the application **318** might discard the data that the user **115** provided, without the data being sent to the mobile device management system **126**. Ultimately, this makes the user **115** re-enter the data once the connection **142** is regained.

(317) A somewhat similar dynamic may occur from the perspective of an enterprise resource **130** and tunneling mediator **224** (or other tunneling mediator). In particular, the mobile device's network connection **142** can become lost when the tunneling mediator **224** attempts to send data to a mobile device **120** via an application tunnel.

(318) In some embodiments, upon the creation of an application tunnel between a software application **318** of a mobile device **120** and an enterprise resource **130** as described above, the device's enterprise agent **320** and/or the enterprise's tunneling mediator **224** (or other tunneling mediator) can be configured to enhance communications between the mobile device **120** and the enterprise resource **130**, by caching data. For example, the agent **320** can cache data on the mobile device **120**, and the tunneling mediator **224** can cache data within the mobile device management system **126**.

(319) FIG. 10 is a flowchart illustrating an embodiment of a method in which a mobile device **120** can cache data input by a user **115** in response to a loss of a network connection **142** to an enterprise computer system **110**. The method is described in the context of FIG. 1A, but could also be used in other computing systems, such as any of the systems of FIGS. 1B-1E. The method begins in step **1002**, in which a software application **318** on the mobile device **120** prompts the user **115** for data. At this point, an application tunnel may have already been formed between the application **318** and an enterprise resource **130** via a tunneling mediator. In step **1004**, the application **318** receives the data, for example, via the user interface **304** of the mobile device **120**. In step **1006**, the application **318** generates a request to send the received data to an enterprise resource **130** of the enterprise system **110**. In step **1008**, the enterprise agent **320** receives or intercepts the application's request to send the received data to the enterprise resource **130**. In decision step **1010**, the agent **320** determines the availability of the network connection **142, 144** between the mobile device **120** and the tunneling mediator **224**. If the network connection **142, 144** is available, then, in step **1012**, the agent **320** begins sending the data to the tunneling mediator via

the connection **142, 144**. For example, the agent **320** can open up a TCP socket to the tunneling mediator server. If the agent is able to send all of the data received from the user **115**, the application **318** may take no further action relate to the data previously received from the user at step **1004**. In some embodiments, the method may return to step **1004** if the user **115** is still inputting new data to the application **318**.

(320) If the network connection **142, 144** is lost and unavailable, then, in step **1016**, the agent **320** can prevent the software application **318** from detecting the loss of the network connection **142, 144**. For example, the agent **320** can prevent the application **318** from detecting a TCP socket error caused by the loss of the connection **142, 144**. Then, in step **1018**, the agent **320** caches at least a portion (and preferably all) of the received data that has not been sent from the mobile device **120** to the tunneling mediator **224**. The data can be cached in any suitable machine-readable memory device, such as the random access memory **308**, the hard drive **306**, flash memory, or a memory card engaged with the memory card port **307** of the mobile device **120**. Then, in decision step **1020**, the agent **320** determines whether the network connection **142, 144** to the tunneling mediator **224** has been regained. The determination in decision step **1020** can involve the agent **320** receiving a notification from a notification service to which the agent has subscribed. If the network connection **142, 144** to the tunneling mediator **224** has not been regained, the method can wait for a time period and then return to decision step **1020**. Once the network connection **142, 144** is regained, the agent **320** sends the cached data to the tunneling mediator **224** via the regained network connection **142, 144**.

(321) In the illustrated embodiment, the enterprise agent **320** caches user-provided data (step **1018**) only after the agent **320** determines that the connection to the tunneling mediator **224** has been lost (step **1010**). In other embodiments, the agent **320** can be configured to cache user-provided data before determining whether the connection to the tunneling mediator **224** is lost or available. For instance, the agent **320** can cache the data in response to receiving the data from the user at step **1004**. In such embodiments, the cached data can be erased after the data has been sent to the tunneling mediator **224**.

(322) It will be appreciated that the software application **318** may conduct a process in which the user inputs data in several successive stages, wherein the application **318** attempts to send the received data after each stage. If the network connection **142, 144** is lost before the final data input stage, and the application **318** receives additional data after the connection **142, 144** is lost, then the enterprise agent **320** can be configured to cache at least a portion (and preferably all) of the additional data. In that, case, the agent **320** can respond to a regaining of the network connection **142, 144** by sending the cached additional data to the tunneling mediator via the regained network connection **142, 144**.

(323) As noted above, in step **1016** the enterprise agent **320** can prevent the software application **318** from detecting the loss of the network connection **142, 144**. From the perspective of the software application **318**, the connection **142, 144** is available in such circumstances. As far as the application **318** is concerned, it has an IP address and a server port with which to communicate. In this way, the application **318** can be given the impression that it is communicating with the enterprise resource **130**, when in reality it is either communicating only with the agent **320** (when the connection **142, 144** is lost) or with the tunneling mediator **224** via the agent **320** (when the connection **142, 144** is available). When the connection **142, 144** is lost, the agent **320** can give the application **318** the impression that the enterprise resource **130** is still in the process of reading and

responding to the request, thereby preventing the application **318** from timing out.

(324) The mobile device user's experience can be similar to that of the application **318**. The user's experience is dependent on the application **318**. So, if the agent **320** keeps the application **318** unaware of the lost network connection **142, 144**, the user may also remain unaware of it. This method can prevent, for example, the aforementioned problem of the user having to reenter the data into the application **318** when the connection **142, 144** is lost.

(325) In some cases, particularly when a mobile device **120** is downloading a large amount of data from the enterprise system **110**, it may be useful to respond to a lost network connection by caching data packets within the enterprise system **110**. FIG. 11 is a flowchart illustrating an embodiment of a method in which an enterprise computer system **110** caches data to be sent to a mobile device **120** when a network connection **142, 144** to the mobile device **120** is lost. The method is described in the context of an enterprise resource **130** sending data to the mobile device **120**. While the method is described in the context of FIG. 1A, it could be used in other computing systems, such as any of the systems of FIGS. 1B-1E. The method begins in step **1102**, wherein an application tunnel is established between a mobile device application **318** and an enterprise resource **130**, via the tunneling mediator **224**, for example, as described above. For instance, the application tunnel may be established in response to an access request generated by a software application **318** on the mobile device **120**. In step **1104**, the tunneling mediator **224** receives one or more data packets from the enterprise resource **130**. In decision step **1106**, the tunneling mediator **224** determines whether the network connection **142, 144** between the tunneling mediator **224** and the mobile device **120** is available. If the network connection **142, 144** is available, then, in step **1108**, the tunneling mediator **224** sends the data packets to the mobile device **120** via the network connection **142, 144**. On the other hand, if the network connection **142, 144** is not available, then, in step **1110**, the tunneling mediator **224** caches the one or more received data packets in a computer-readable storage, such as a storage of the mobile device management system **126**. In step **1110**, the tunneling mediator **224** can be configured to send to the enterprise resource **130**, one or more acknowledgements of receipt of the data, on behalf of the mobile device **120**, if the resource **130** expects such acknowledgement(s) from the device **120**. After either of steps **1108** and **1110**, the tunneling mediator **224** determines, in decision step **1112**, whether the tunneling mediator **224** is receiving additional data packets from the enterprise resource **130**. If so, then the method returns to decision step **1106**. If not, then the method can end in step **1114**.

(326) In the illustrated embodiment, the tunneling mediator **224** caches data (step **1110**) only after the mediator **224** determines that the connection to the mobile device **120** has been lost (step **1106**). In other embodiments, the tunneling mediator **224** can be configured to cache the data before determining whether the connection to the mobile device **120** is lost or available. For instance, the tunneling mediator **224** can cache the data responsive to receipt of the data from the enterprise resource **130**. In such embodiments, the cached data can be erased after the data has been sent to the mobile device **120**.

(327) As noted above, during the method illustrated in FIG. 10, the enterprise agent **320** on the mobile device **120** preferably gives the software application **318** (which may be the intended recipient of the data being sent by the enterprise resource **130**) an impression that the network connection **142, 144** has not been lost, using the methods described above. Similarly, the tunneling mediator (e.g., the mediator **224**) can be configured to give the enterprise resource **130** an impression that the network connection **142, 144** has not been lost, for example, in accordance

with the method illustrated in FIG. 11.

(328) In some embodiments, the tunneling mediator (e.g., the mediator **224**) and/or the enterprise agent **320** is configured to compress data transmitted through the application tunnel. The tunneling mediator can be configured to compress data received from the enterprise resource **130** (or another resource outside the enterprise system **110**) through the resource network connection **152**, and to send the compressed data to the mobile device **120** through the network connection **142**, **144**. Upon receipt of the compressed data, the enterprise agent **320** can be configured to decompress the data before it is provided to a software application **318** that is the intended recipient of the data. Thus, the application **318** need not be capable of decompressing the data.

(329) Similarly, the mobile device's enterprise agent **320** can be configured to compress data intercepted or received from a software application **318**, and to send the compressed data to the tunneling mediator through the network connection **142**, **144**. Upon receipt of the compressed data, the tunneling mediator can be configured to decompress the data before it is provided to an enterprise resource **130** (or another resource outside the enterprise network **110**) that is the intended recipient of the data. Thus, the enterprise resource **130** need not be capable of decompressing the data.

(330) This compression functionality can be useful when the mobile device **120** is sending or receiving large data files, or when the mobile device **120** is in an area in which the network connection **142**, **144** has low bandwidth. In certain embodiments, data is compressed by about 20-95%. The extent of the data compression can depend on the data type, the available bandwidth of the network connections **142**, **144**, and **152**, as well as other factors. Moreover, both the application **318** and the user **115** of the mobile device **120** can remain unaware of the compression and decompression of the data.

(331) In some embodiments, an application tunnel can be used by the enterprise system **110** for error correction (e.g., parity checks), resending of lost data packets, etc. The tunneling mediator **224** can be used for load balancing or thread safety/synchronization of a thread unsafe server application.

(332) “Remote Control” of Mobile Devices

(333) In some embodiments, a “remote control” system and methodology can be provided to allow an enterprise's mobile devices **120** to be diagnosed and controlled by one or more helpdesk operators, administrators or other persons (collectively referred to herein as “controllers”) at computers (“controller computers”) that are remotely located with respect to the mobile devices **120**. Such systems and methods are now described.

(334) With reference to FIGS. 2 and 12, the mobile device management system **126** can be configured to facilitate a “remote control session” between a mobile device **120** and a controller computer **1200** having installed thereon a remote control module **1202**. The controller computer **1200** is operated by a user referred to herein as a controller **1204** and may be located either within or outside of the enterprise computer system **110** (FIG. 1A). In this context, the tunneling mediator **224** can help form an application tunnel between the controller computer **1200** and the enterprise agent **320** (FIG. 3) of the mobile device **120**.



(335) With reference to FIG. 12, the remote control module **1202** is preferably configured to initiate a network connection (e.g., over the Internet) to a server associated with the tunneling mediator **224** (e.g., a server on which the tunnel definitions **228** are stored, or a proxy server). In some embodiments, this connection is via an application tunnel, such as those described above. It will be appreciated that the enterprise may have multiple mobile device management systems **126**. Hence, the remote control module **1202** can allow the controller **1204** to specify one or more tunneling mediators **224** with which to connect.

(336) A user **115** of a mobile device **120** may encounter technical difficulties with the user's mobile device **120**, and may wish to seek help from a helpdesk service. A helpdesk service can be operated exclusively by or for the enterprise, or alternatively for multiple enterprises. In some embodiments, the user **115** can request a remote control session with a controller computer **1200** by contacting the helpdesk service (e.g., by a phone call, email, text message, and the like). In such embodiments, a controller **1204** associated with the helpdesk service can then cause a remote control module **1202** of a controller computer **1200** to send to the user's mobile device **120** a request for a remote control session between the controller computer **1200** and the mobile device **120**. In some embodiments, the enterprise agent **320** of a mobile device **120** allows the user **115** to request or initiate a remote control session with the controller computer **1200**. In some embodiments, a remote control session can be initiated by a controller **1204** without first being requested by the user **115**.

(337) FIG. 13 is a flowchart illustrating an embodiment of a method in which a controller computer **1200** (FIG. 12) participates in a remote control session with a mobile device **120**. The method begins at a point at which the remote control module **1202** has connected to a server associated with the tunneling mediator **224** (or another mediator of remote control sessions with mobile devices **120**).

(338) In step **1302**, the remote control module **1202** provides, for the controller **1204**, identifications of one or more mobile devices **120** that are available for a remote control session. This may be achieved by the remote control module **1202** sending a request to the mobile device management system **126** for such identifications, and the mobile device manager **202** responding by looking up the information in the mobile device information **204** and sending the requested information to the controller computer **1200**. The provided identifications can comprise, e.g., the names or usernames of the users **115** assigned to the mobile devices **120**. The identified devices **120** can be filtered (e.g., by the mobile device manager **202** or the remote control module **1202**) in accordance with any criteria, such as criteria specified by the controller **1204** to the remote control module **1202**. For example, the remote control module **1202** can list only those mobile devices **120** that are currently connected to the enterprise system **110**, or only those mobile devices **120** or users **115** that are members of a defined user group, etc. Also, the remote control module **1202** can be configured to allow the controller **1204** to conduct searches against the enrolled mobile devices **120**, to, e.g., search for a specific device **120** or user **115**. In addition to identifying the users **115** of the mobile devices **120** to the controller **1204**, the remote control module **1202** can also be configured to provide additional information about the identified devices **120**, such as device model, operating system version, platform, etc. The mobile device manager **202** can obtain such information from the mobile device information **204**, such as the mobile device properties **208**.

(339) Referring still to FIG. 13, in step **1304** the remote control module **1202** receives from the controller **1204** a selection of at least one of the mobile devices **120**, and/or an instruction to initiate

a remote control session with the selected device **120**. In step **1306**, the remote control module **1202** sends a request for a remote control session to the selected mobile device **120**. In embodiments in which the remote control sessions are conducted via application tunnels, the request can be sent to the tunneling mediator **224**. In other embodiments, the request is sent directly to the selected mobile device **120**. In step **1308**, the controller computer **1200** begins to repeatedly receive batches of newly updated “user interface emulation data” from the mobile device **120**. In an application tunnel context, this data flows from the mobile device **120** to the controller computer **1200** via the tunneling mediator **224**. User interface emulation data may comprise data that the enterprise agent **320** of the mobile device **120** captures using any of various device display “scraping” methods (also referred to as “screen scraping” and/or “screen buffer capture”), as known generally in the desktop computer field. For example, in the desktop computer environment, one known protocol for providing a graphical interface to another computer is Remote Desktop Protocol (RDP) developed by Microsoft™.

(340) With continued reference to FIG. 13, in step **1310**, the remote control module **1202** uses the user interface emulation data to emulate a current state of the user interface **304** of the mobile device **120**. For example, FIG. 14 shows an embodiment of a screen display for a controller computer **1200**, including a virtual user interface **1402** that emulates a user interface **304** of a mobile device **120** engaged in a remote control session with the controller computer **1200**. Referring again to FIG. 13, steps **1308** and **1310** will ordinarily occur repeatedly and one after the other. Accordingly, a batch of user interface emulation data is received (step **1308**) and then used by the remote control module **1202** to emulate the mobile device's user interface **304** (step **1310**), and then a new batch of user interface emulation data is received (step **1308**) and then used to emulate the user interface **304** (step **1310**), and so on. In this manner, the remote control module **1202** keeps updating the emulated user interface to reflect a current state of the user interface **304**.

(341) Preferably, the remote control module **1202** of the controller computer **1200** allows the controller **1204** to issue commands to the mobile device **120**. Such commands are referred to herein as “remote control commands.” Accordingly, referring still to FIG. 13, the remote control module **1202** can receive, in step **1312**, remote control commands from the controller **1204**. In some embodiments, the controller **1204** can provide these commands via the emulated user interface **1402**. The remote control commands can be for accessing resources installed on the mobile device **120**. In this context, the mobile device resources can include operating system features and functionalities, software applications, mobile device hardware, data resources, files, and the like. Then, in step **1314**, the remote control module **1202** sends the remote control commands to the mobile device **120**. At least some of the remote control commands can be commands that the user **115** could otherwise input directly into the mobile device **120**. The mobile device **120** can react to such remote control commands as if they were received via the user interface **304** of the device **120**. These types of remote control commands will typically cause the user interface **304** of the mobile device **120** to change, which in turn will be reflected in a new batch of user interface emulation data received from the mobile device. Accordingly, in step **1316**, the remote control module **1202** receives updated user interface emulation data from the mobile device **120**, reflecting a state of the device's user interface **304** after the device **120** reacts to at least some of the remote control commands, as if they were received via the user interface **304**. Then, in step **1318**, the remote control module **1202** uses the updated user interface emulation data to emulate the current state of the user interface **304** of the mobile device **120**.

(342) In certain embodiments, the remote control module **1202** can allow the controller **1204** to view information about the mobile device **120**. The controller's viewing of information can be sequestered from the user interface **304** of the mobile device **120**. Hence, in step **1320**, the remote control module **1202** can receive a request from the controller **1204** for information about the mobile device **120**. In step **1322**, the remote control module **1202** can send the request for information to the mobile device **120**. The request can essentially automate an API for a mobile device feature that returns requested information (e.g., API's for task manager, file explorer, registry editor, etc.). In step **1324**, the remote control module **1202** can receive the requested information from the mobile device **120**, preferably without displaying the information within the emulated user interface **1402**. In step **1326**, the remote control module **1202** can display the requested information on a display associated with the controller computer **1200**, preferably in a location other than the emulated user interface **1402**. Examples of mobile device information that can be requested in steps **1320** and **1322**, received in step **1324**, and displayed in step **1326** include the mobile device's system information, processes occurring on the mobile device, files stored on the mobile device, the mobile device's registry, and other data.

(343) For example, the screen display of FIG. 14 includes a system information display **1404** shown next to the emulated user interface **1402**. The system information display **1404** can provide some or all of, e.g., the mobile device's operating system version, platform, model, hardware serial number, CPU type, total storage memory capacity, storage memory in use, storage memory that is free, total RAM, RAM in use, RAM that is free, total storage card memory (e.g., SD card) capacity, storage card memory in use, storage card memory that is free, AC power availability, remaining battery power, and/or device usage time available from remaining battery power. It will be appreciated that additional system information can also be provided.

(344) In another example, FIG. 15 shows an embodiment of a screen display of a controller computer **1200** engaged in a remote control session with a mobile device **120**, wherein the screen display includes a task manager display **1502** showing application processes occurring on the mobile device **120**. The illustrated task manager display **1502** is shown next to the emulated user interface **1402**. The task manager display **1502** can show some or all of, e.g., names of applications associated with the processes, amounts of RAM being used by the processes, percentages of CPU power being utilized by the processes, amounts of CPU time consumed by the processes, numbers of threads associated with the processes, and the device paths. It will be appreciated that additional information concerning such processes can also be provided. In some embodiments, the controller **1204** can issue remote control commands (to the remote control module **1202**) associated with the task manager, such as terminating one or more processes on the mobile device **120**. For instance, such remote control commands can be issued responsive to a selection made via the task manager display **1502**.

(345) FIG. 16 shows an embodiment of a screen display of a controller computer **1200** engaged in a remote control session with a mobile device **120**, including an interface **1602** for viewing files stored on the mobile device **120** (in any of the aforementioned memory storages), downloading files from the mobile device **120** to the controller computer **1200**, and/or uploading files from the controller computer **1200** or from a different networked computer to the mobile device **120**. The commands issued by the controller **1204** to the remote control module **1202** to view files, download files, and/or upload files can be sent to the mobile device **120** as remote control commands.

(346) In another example, FIG. 17 shows an embodiment of a screen display of a controller

computer **1200** engaged in a remote control session with a mobile device **120**, including an interface **1702** for viewing and/or editing a registry of the mobile device **120**. The illustrated registry interface **1702** is shown next to the emulated user interface **1402**.

(347) FIG. 18 is a flowchart illustrating an embodiment of a method in which a mobile device **120** participates in a remote control session with a controller computer **1200**. The method shown in FIG. 18 can correspond to the method shown in FIG. 13, except that the method of FIG. 18 is shown from the perspective of a mobile device **120**. As described elsewhere herein, the mobile device **120** can comprise a user interface **104** configured to receive local commands from a user **115** of the mobile device **120**, for accessing resources installed on the mobile device. Further, the user interface **304** is typically configured to convey information to the user **115**, such as via a screen or display **326**.

(348) The method begins in step **1802**, in which the enterprise agent **320** of the mobile device **120** receives a request from a controller computer **1200** to participate in a remote control session with the controller computer. In some embodiments, the agent **320** can be configured to automatically accept such requests. In other embodiments, the agent **320** is configured to obtain permission from the user **115** to participate in the remote control session, e.g., by prompting the user for an indication of permission. In the illustrated method, the agent **320** determines, in decision step **1804**, whether to accept the request. If the agent **320** does not accept the request (e.g., due to the user **115** denying the request, or due to the user **115** simply not giving permission within a predefined time period), then the method can end in step **1806**.

(349) On the other hand, if the enterprise agent **320** accepts the request, then the agent **320** responds to the request by requesting or establishing an application tunnel connection with the controller computer **1200** and obtaining, in step **1808**, user interface emulation data (described above) from the mobile device **120**. In step **1810**, the agent **320** sends the user interface emulation data to the controller computer **1200**. The agent **320** can repeatedly send updated user interface emulation data, for example at fixed time intervals or perhaps only when changes occur to the mobile device's user interface **304**.

(350) Referring still to FIG. 18, in step **1812** the agent **320** can receive remote control commands from the controller computer **1200**, for accessing resources installed on the mobile device **120**. As mentioned above, such mobile device resources can include operating system features and functionalities, software applications, mobile device hardware, data resources, files, and the like. At least some of these remote control commands can be commands that the user **115** could otherwise input directly into the mobile device **120** via the user interface **304**. Hence, in step **1814**, the mobile device **120** reacts to at least some of the remote control commands as if they were received via the user interface **304**. Step **1814** can involve the agent **320** translating and/or providing the remote control commands to the device's hardware and/or software in a native language of the device, in the same manner that such hardware and/or software would receive the commands if the commands had been received via the mobile device's user interface **304**. Since step **1814** can result in changes to the device's user interface **304**, the agent **320** can be configured to subsequently send updated user interface emulation data to the controller computer **1200**.

(351) In step **1816**, the enterprise agent **320** of the mobile device **120** receives a request from the controller computer **1200** for information about the mobile device. For example, such information can include the information described above in steps **1320**, **1322**, **1324**, and **1326** of FIG. 13. In

step **1818**, the agent **320** sends the requested information to the controller computer **1200**, without displaying the information on the user interface **304** of the mobile device **120**.

(352) In conducting a remote control session with a remote control module **1202** of a controller computer **1200**, the enterprise agent **320** of a mobile device **120** can be configured to allow the controller **1204** to execute actions on the mobile device **120**. In some cases, these can include actions that even the user **115** of the device **120** cannot perform (e.g., if the remote control module **1202** has functionality beyond that of the software applications **318** installed on the mobile device **120**).

(353) It will be appreciated that the remote control module **1202** can be configured to allow the controller **1204** to conduct numerous other operations against the mobile device **120** during a remote control session. For example, the remote control module **1202** can be configured to allow the controller **1204** to shut down or reboot the mobile device **120**. In another example, the remote control module **1202** can be configured to allow the controller **1204** to install new software onto the mobile device **120**. This may involve sending software application installation files from the controller computer **1200** or another networked computer to the mobile device **120**, and then installing the application. In another example, the remote control module **1202** can be configured to allow the controller **1204** to uninstall software applications **318** from the mobile device **120**. Many other operations are possible.

(354) In some embodiments, the remote control module **1202** of the controller computer **1200** and the enterprise agent **320** of the mobile device **120** are configured to enable the controller **1204** and the mobile device user **115** to communicate with one another, using the controller computer **1200** and mobile device **120**. For example, the remote control module **1202** and the enterprise agent **320** can be configured to enable a voice over internet protocol (VOIP) session that allows the controller **1204** and user **115** to speak to each other audibly. The mobile device **120** can use the speaker **328** of the mobile device **120** to audibly broadcast the controller's speech (input via a microphone of the controller computer **1200**) to the user **115**. Alternatively, the user **115** can listen to the controller's speech by connecting a pair of headphones to a headphone jack of the mobile device **120**. Similarly, a speaker of the controller computer **1200** can broadcast the user's speech (input at the microphone **330** of the mobile device **120**) to the controller **1204**.

(355) In another example, the remote control module **1202** and the enterprise agent **320** can be configured to enable a text chat session between the controller **1204** and the user **115**. FIG. 19A shows an embodiment of a screen display of a controller computer **1200** engaged in a remote control session with a mobile device **120**, including a chat session interface. In the illustrated embodiment, the remote control module **1202** produces a chat session area **1902** in which the controller **1204** can enter text communications to be sent to the user **115**, and in which the user's text communications are displayed to the controller **1204**. The illustrated chat session area **1902** is shown next to the emulated user interface **1402**. FIG. 19B shows an embodiment of the mobile device **120** emulated in FIG. 19A. The enterprise agent **320** is preferably configured to display, on the screen **326** of the mobile device **120**, substantially the same text communications displayed in the chat session area **1902** of FIG. 19A.

(356) In another example, the remote control module **1202** and the enterprise agent **320** can be configured to enable shared whiteboard communications between the controller **1204** and the user **115**. FIG. 20 shows an embodiment of a screen display of a controller computer **1200** engaged in a

remote control session with a mobile device **120**, including a shared whiteboard feature. In the illustrated embodiment, the remote control module **1202** allows the controller **1204** to superimpose images **2002** onto the emulated user interface **1402**. The agent **320** of the mobile device **120** can be configured to receive the images **2002** and then superimpose them onto the screen **326** of the mobile device **120**. The images **2002** can comprise, for example, text, drawings, and the like. In the illustrated screen display, the controller **1204** has circled an icon on the emulated user interface **1402** and superimposed the words “click here.”

(357) In certain embodiments, the remote control module **1202** is configured to allow the controller **1204** to adjust the view of the emulated user interface **1402**. For example, in various embodiments, the remote control module **1202** is configured to allow the controller **1204** to adjust the emulated interface's resolution, color scheme, bits per pixel (BPP), zoom level, rotational orientation, etc. Further, the remote control module **1202** can be configured to allow the controller **1204** to adjust a “refresh rate” at which the enterprise agent **320** of the mobile device sends updated user interface emulation data to the controller computer **1200**. The remote control module **1202** can also be configured to allow the controller **1204** to specify whether the data received from the mobile device **120** is to be compressed by the enterprise agent **320**, as well specify the degree of compression.

(358) In certain embodiments, the remote control module **1202** is configured to capture and save aspects of remote control sessions. For example, the remote control module **1202** can be configured to allow the controller **1204** to capture images of the emulated user interface, print the images onto a hardcopy printout, to record video of a remote control session, and the like. The remote control module **1202** can be configured to allow the controller **1204** to edit the captured images or video, and/or send captured media files to others, via email and the like.

(359) In some embodiments, the remote control module **1202** can be configured to allow the controller **1204** to create macros for activating or executing certain features, settings, and/or software applications of the mobile device **120**.

#### (360) Analytics on Secure Mobile Gateway

(361) Referring again to FIG. 4, the secure mobile gateway **128** can include a repository **410** of logged data. The repository **410** can store data indicative of state information generated at mobile devices **120** or generated by the secure mobile gateway **128**. For example, the logged data can include various information, such as data regarding grants and denials of mobile device access requests by the gateway filter **401**. The logged data can alternatively or additionally include data logged by and extracted from managed mobile devices **120**. Such logged data can include, for example, data indicative of documents downloaded to the mobile device **120**, system state(s) on particular mobile devices **120**, programs launched on particular mobile devices **120**, records of websites or other network resources accessed by particular mobile devices **120**, information associated with email accounts of users copied on messages associated with managed mobile devices **120**, documents attached to emails or other messages received by the mobile devices **120**, etc. The logged data can include data obtained from the mobile device requests **402**. For instance, for a secure mobile gateway **128** that supports ActiveSync, the logged data can include the DeviceId, DeviceType, User, and/or User Agent from the ActiveSync request **402**, as well as the ActiveSync command issued by the request. In the case of an access denial, the logged data can also include the provider **408** of the violated gateway rule **404**, and information indicative of the reason for the denial. If access is denied based on a violated enterprise access policy **218** of the

mobile device management system **126**, the gateway **128** can determine which policy **218** was violated from the mobile device management system **126** and store it in the repository **410** of logged data. The logged data can also include mobile traffic data and/or other network information about the request **402**, such as the IP address of the mobile device **120** that issued the request. The logged data can be stored in accordance with a logging standard such as Syslog, so that the data is readable by other applications.

(362) The logged data can be provided to or accessed by an analytics service **414**. In the illustrated embodiment, the secure mobile gateway **128** includes a log redirector service **412** that periodically reads the logged data **410** and sends some or all of it to the analytics service **414**. The log redirect or service **412** is preferably configurable so that an IT administrator can direct it to send only those portions of the logged data that match configurable criteria. For example, the log redirectar service **412** can be configured to send only the logged data concerning denied requests **402**, or only the logged data concerning granted requests **402**, or logged data filtered based on different criteria. Further, the log redirector service **412** and/or the repository **410** of logged data can comprise a data-sharing interface that enables other systems (such as the analytics service **414**) to query or extract data concerning the logged requests **402**, such as user data, mobile device data, mobile traffic data (e.g., IP address of sender device), etc. It will be understood that the principles and advantages described with reference to analytics on the secure mobile gateway **128**, can be applied to implement a variety of data mining and correlation for security or other purposes. As an example, if the logged data indicates that a mobile device **120** has accessed certain prohibited sites and also recently downloaded confidential documents which were then forwarded to an external email, this information can be a basis for denial of access to enterprise resources.

(363) The analytics service **414** can comprise, for example, a Security Information Management (SIM) system, a Security Event Management (SEM) system, or a Security Information and Event Management (SIEM) system. SIEM solutions are a combination of SIM and SEM solutions. The analytics service **414** can be configured to monitor, analyze, and/or generate and send alerts, notifications, or reports based on the logged data. The analytics service **414** can be configured to detect patterns in the logged data, provide metrics useful for further analysis or actions, and diagnose problems associated with the data. The analytics service **414** can be configured to process data formatted according to various standards, such as Syslog. For instance, the analytics service **414** can utilize Splunk, a software program having these types of features. The analytics service **414** can be part of the enterprise system **110**, or alternatively can be part of a third party system for analyzing data of the type logged in the repository **410**.

(364) For example, the analytics service **414** can be configured to process an access denial by the secure mobile gateway **128** by sending a communication (e.g., an email or SMS message) to the denied user **115**, possibly specifying the reason for the denial of access (e.g., “Your request to access the XYZ Corp's network was denied because your mobile device does not comply with the enterprise's policy against installing the Angry Birds™ software application”).

(365) FIG. 21 shows an example of logged data that can be provided to an analytics service **414**, in accordance with one embodiment. In this example, the logged data comprises a table of rows and columns. Each row corresponds to a mobile device access request **402**. Columns **2102** and **2104** include data indicative of the date and time, respectively, at which the secure mobile gateway **128** logged the corresponding row of data. With regard to column **2106**, “Priority,” is a configurable Syslog setting that identifies the collector of messages and level. Priority is a configurable item that

applies across all Syslog collection types. Column **2108**, under the heading “Hostname,” is the IP address of the host that provided the corresponding row of data. In the illustrated embodiment, the hostname **2108** is the IP address of the gateway **128**. Column **2110**, under the heading “Message,” includes various information about a selected mobile device access request **402**. The illustrated message data includes the date and time at which the request was received, the action (allow or deny) that the gateway **128** taken against the request, the user (in the first row; “jmcginty”) associated with the request, the mobile device type, and the IP address that the mobile device used when submitting the access request.

(366) FIG. 22 shows an example of an interface of an analytics service **414**, for configuring criteria under which the analytics service sends alerts based on data logged by the secure mobile gateway **128**. The illustrated interface is part of a Splunk SIEM tool. The interface allows an administrator to input the conditions under which an alert will be sent (“Splunk Alert: Allow ActiveSync Users Alert”), the type of alert (email), content of the alert (“Include search results”), etc.

### (367) Authentication of Mobile Device Users

(368) Enterprise networks typically authenticate their users at the onset of the users' computer transactions with enterprise resources. In existing systems, authentication commonly involves a login process of receiving a username and password from the user's client device, verifying that the username corresponds to an authorized user, and verifying that the password is the correct password for the username. While some enterprise resources **130** may be configured to consume username data for all transactions with mobile devices (e.g., to grant access based on user ID, user role **206** or other group membership, etc.), other resources **130** do not. For some types of enterprise resources **130**, after authentication, the user is permitted to conduct at least some transactions with the resource **130** without providing login information. For a defined time period after the last transaction with the authenticated user, some enterprise resources **130** downstream of the enterprise's firewall(s) assume that new requests that use the authenticated IP address (e.g., the IP address of the device that sent the user's login information to the enterprise network) are from the authenticated user. Such enterprise resources generally do not request and confirm the user's login information for each transaction with the user's computing device.

(369) While this approach is generally suitable for non-mobile client devices, it can present security risks specific to mobile devices. Mobile devices often change their IP addresses when in use. For instance, a mobile device connected to a cellular network while in a moving vehicle can switch between different cellular towers. Similarly, a mobile device can switch between different Wi-Fi networks. A mobile device can also switch between different IP addresses associated with a single cellular tower or Wi-Fi network. Hence, an enterprise resource **130** that determines the user associated with an inbound mobile device request by examining only the request's IP address risks conducting a transaction with a person who is not the user.

(370) FIG. 23 illustrates an embodiment of a method by which the analytics service **414** can leverage the secure mobile gateway **128** (FIG. 4) to assist in determining whether and/or how to respond to a mobile device's request **2302** for accessing or using an enterprise resource **130**. For instance, the enterprise resource **130** can receive the mobile device request **2302** via a gateway different than the secure mobile gateway **128**. The request **2302** could be received via an application tunnel. While the illustrated embodiment depicts a resource **130** that queries the analytics service **414** for a binding of user information (e.g., an ID number for a user **115**) to mobile



traffic data (e.g., IP address), components other than resources **130** (such as the tunneling mediator **224**) can also be configured to do the same.

(371) In the illustrated embodiment, the secure mobile gateway **128** includes a gateway filter **401** and a repository **410** of logged data, for example, as described above. The logged data can include data from mobile device access requests **402** received by the gateway filter **401**, for example, as described above. For example, if the gateway **128** supports ActiveSync, the logged data can include the DeviceId, DeviceType, User, and/or User Agent property values from an ActiveSync request **402**, as well as the ActiveSync command issued by the request **402**.

(372) The request **2302** can include mobile traffic data, such as an IP address of a mobile device **120** that sent the request **2302**. The request **2302** may or may not include data about the mobile device **126** that sent the request **2302**. The enterprise resource **130** can receive the request **2302** and send a user determination request **2304** to the analytics service **414**. The user determination request **2304** includes the mobile traffic data of the request **2302**. The user determination request **2304** can additionally include the time at which the enterprise resource **130** received the request **2302**, the data about the mobile device **120** that sent the request, as well as other data associated with the request **2302**. In some embodiments, the user determination request **2304** can include an identification of a user **115** that the enterprise resource **130** or another enterprise component believes to be the sender of the request **2302**, such that the analytics service **414** is essentially being asked to verify whether the identified user **115** is the actual person who sent the request **2302**.

(373) The analytics service **414** can employ a user determination algorithm for determining user information associated with the request **2302** received by the enterprise resource **130**. In this context, user information can include a determination of whether the request **2302** was sent by a user **115** (as opposed to someone who is not associated or enrolled with the enterprise), a determination of whether a user **115** identified in the user determination request **2304** is the person who sent the request **2302** to the enterprise resource **130**, and/or an identification (e.g., username) of a user **115** who sent the request **2302**. The user determination algorithm can additionally determine a reliability score indicative of a confidence level in the computed binding—a degree of confidence that a particular user **115** is the actual person who sent the request **2302**. The analytics service **414** can produce and send a response **2306** containing result(s) produced by the user determination algorithm. The results of the algorithm can comprise the user information and/or the reliability score.

(374) In the embodiment illustrated in FIG. 23, the enterprise resource **130** receives the request **2302** and sends the user determination request **2304** to the analytics service **414**, and the analytics service **414** sends the response **2306** back to the enterprise resource **130**. In such embodiments, the enterprise resource **130** can be configured to use the data within the response **2306** to determine how to respond to the request **2302**. For example, the enterprise can respond to the request **2302** by responding to the device **120** that sent the request **2302**, ignoring the request **2302**, sending an alert to an IT administrator, etc.). The enterprise resource **130** can be configured to make this determination at least partly based on the reliability score (if provided) and/or the specific action or command issued within the request **2302**. For example, the enterprise resource **130** can be configured to require a relatively high reliability score if the request **2302** seeks to download sensitive or confidential enterprise data, while imposing a relatively low reliability score requirement if the request **2302** seeks to upload data to the resource **130**. The enterprise resource

**130** can be configured to allow an administrator to configure the reliability score threshold at which the resource **130** will take any given action in response to the request **2302**.

(375) In other embodiments, a component upstream of the enterprise resource **130** (e.g., a gateway, firewall, proxy server, DLP monitoring device, tunneling mediator, SSL traffic inspection device, or other components different than those of the secure mobile gateway **128**) receives the request **2302**, generates the user determination request **2304**, and sends the user determination request **2304** to the analytics service **414**, and the analytics service **414** sends the response **2306** to said component upstream of the enterprise resource **130**. In these embodiments, the upstream component can be configured to use the data within the response **2306** to determine whether to pass the request **2302** along to the enterprise resource **130**. Further, the upstream component can be configured to make this determination at least partly based on the reliability score and/or the action or command issued within the request **2302**. For example, if the request **2302** seeks to download sensitive or confidential enterprise data, the upstream component can be configured to send the request **2302** to the enterprise resource **130** only if the reliability score exceeds a relatively high value. In another example, if the request **2302** seeks to upload data to the enterprise resource **130**, the upstream component can be configured to require a relatively low reliability score for passing the request **2302** along to the resource **130**. The upstream component can be configured to allow an administrator to configure the reliability score threshold at which the upstream component takes any given action in response to the request **2302**.

(376) In some embodiments, the analytics service **414** proactively sends out its computed bindings of user **115** to mobile traffic data (e.g., IP address) to the enterprise resources **130**. The analytics service **414** can send the bindings directly to the resources **130**, and/or to one or more components upstream of the resources **130**, which append the bindings or related data to the mobile device communications that are transmitted to the resources **130**. In these approaches, the resources **130** can use the computed bindings without requesting them from the analytics service **414**.

(377) The user determination algorithm employed by the analytics service **414** can include scanning some or all of the logged data for mobile traffic data (from the mobile device requests **402** received by the secure mobile gateway **128**) that matches the mobile traffic data received within the user determination request **2304**. For any requests **402** having mobile traffic data that matches that of the request **2302**, the algorithm can also include determining, from the logged data **410**, user data or mobile device data provided within the requests **402**. For example, the user data and the mobile device data can respectively include the values of the User property and the DeviceID property of an ActiveSync request **402**. The analytics service **414** can determine a user **115** corresponding to the user data and/or mobile device data by, requesting it from the mobile device management system **126**. For instance, the User and DeviceID property values can correspond to a particular user **115** in the mobile device information **204**. If the logged data does not include (or the analytics service **414** is unable to find) mobile traffic data that matches that of the request **2302**, the analytics service **414** can determine that the request **2302** was not sent by a user **115**.

(378) In order to determine the user information and compute the reliability score, the user determination algorithm can evaluate a variety of factors. In certain embodiments, the user determination algorithm compares the time at which the request **2302** was received by the enterprise resource **130** to the time of receipt (by the secure mobile gateway **128**) of mobile device access requests **402** having mobile traffic data matching that of the request **2302**. For instance, suppose an ActiveSync request **402** has User and DeviceID property values corresponding to a

particular user **115**. Suppose further that the sender's IP address within the request **402** is the same as that of the request **2302**, and that the request **402** was received by the secure mobile gateway **128** within a relatively narrow time period (before or after) from the time at which the enterprise resource **130** (or upstream component) received the request **2302**. Under these circumstances, the analytics service **414** might compute a high reliability score indicating that the user **115** associated with the request **402** is the person who sent the request **2302** to the enterprise resource **130**. The user determination algorithm can compute a lower reliability score as the time period between the receipt of the request **2302** and the receipt of the temporally closest request **402** having the same sender IP address increases. On the other hand, if the sender's IP address within the request **402** is different than that of the request **2302**, the analytics service **414** might compute a relatively low reliability score and/or determine that the user **115** associated with the request **402** is likely not the person who sent the request **2302** to the enterprise resource **130**. Further, if there were no requests **402** received by the gateway **128** within a predefined or dynamically computed time window from (before or after) the time of receipt of the request **2302** and which have the same sender IP address as the request **2302**, then the analytics service **414** can compute a relatively low reliability score.

(379) In certain embodiments, the user determination algorithm evaluates the frequency with which the enterprise network sees a particular user **115** associated with certain mobile traffic data, such as an IP address. For instance, suppose that the secure mobile gateway **128** has received numerous ActiveSync requests **402** that have User values corresponding to a particular user **115**, within a relatively short time window containing the time at which the enterprise resource **130** received the request **2302**. Suppose further that all of said ActiveSync requests **402** include sender IP addresses that are the same as that of the request **2302**. Under these circumstances, the analytics service **414** might compute a very high reliability score indicating that the user **115** associated with the requests **402** is the person who sent the request **2302** to the enterprise resource **130**. On the other hand, if the sender IP addresses within the requests **402** is/are different than that of the request **2302**, the analytics service **414** might compute a very low reliability score and/or determine that the user **115** associated with the requests **402** is likely not the person who sent the request **2302** to the enterprise resource **130**.

(380) In certain embodiments, the user determination algorithm evaluates the extent to which different access requests **402** associated with a particular user **115** have different mobile traffic data. For instance, the fact that a string of access requests **402** from a particular user **115** have numerous different sender IP addresses likely indicates that the user **115** is on the move and constantly switching IP addresses while communicating with the enterprise system **110**. Under these circumstances, the analytics service **414** might compute a relatively lower reliability score than if all of the access requests **402** from the particular user **115** had the same sender IP address as the request **2302**. In one specific approach, the analytics service **414** determines a total number of access requests **402** that (1) have user data corresponding to a particular user **115** of interest, (2) have mobile traffic data that does not match the mobile traffic data received within the user determination request **2304**, and (3) were received by the secure mobile gateway **128** within a predetermined or dynamically computed time window containing the time of receipt in the user determination request **2304**. The analytics service **414** can reduce the computed reliability score (in a confidence level that the request **2302** was from the particular user **115**) as the total number of determined access requests **402** increases.

(381) In certain embodiments, the user determination algorithm takes into consideration whether the IP address of a request **2302** is from a known block or subnet of IP addresses that are registered or otherwise associated with the enterprise system **110**. Such a block or subnet of IP addresses can be available via the enterprise's own equipment, primarily for use by enterprise personnel, such as a Wi-Fi network, an enterprise VPN allocation block, or roaming external IP addresses. A block or subnet of IP addresses can be registered with the secure mobile gateway **128**. If a request **2302** is sent from an IP address associated with the enterprise, the algorithm can be configured to compute a higher reliability score.

(382) It will be understood that the user determination algorithm for computing the reliability score can include factors in addition to those described above. It will also be understood that the algorithm need not consider all of the factors described above, and can use any sub-combination thereof.

(383) In the embodiment illustrated in FIG. 23, the analytics service **414** is configured to inspect the logged data in the repository **410** of the secure mobile gateway **128** to establish bindings of users and/or mobile devices to mobile traffic data (e.g., IP address). However, an analytics service **414** can be configured to query multiple different logs of mobile request data to compute such bindings. If the enterprise system **110** has multiple different secure mobile gateways **128** (e.g., for different types or protocols of mobile device communications), the analytics service **414** can be configured to query logged data from each of the gateways **128**.

(384) The analytics service **414** can be configured to generate reports and displays of its bindings of user and mobile device to mobile traffic data (e.g., IP address). The enterprise system **110** can include a web-based or other type of user interface for viewing such bindings. For example, such information could be displayed via a user interface of the mobile device management system **126**.

(385) In preferred embodiments, various components of the enterprise system **110** can use the bindings of user and/or device to mobile traffic data produced by the analytics service **414** to track or log network usage events for one or more mobile devices **120**. The analytics service **414** can be queryable and configured to share its information with other components via, e.g., web services.

(386) As noted above, the analytics service **414** can be configured to generate and send notifications to users **115** or IT administrators based on the logged data. Additionally, the analytics service **414** can be configured to send such a notification at least partly based on one or more reliability scores computed according to the user determination algorithm. For example, if a large number of requests were denied, and if reliability scores associated therewith satisfy a defined threshold, then the analytics service **414** can be configured to send an appropriate alert. On the other hand, the analytics service **414** can be configured to ignore situations involving low reliability scores. If there are a large number of access denials, but they all have low reliability scores, it may not be worth generating and sending a notification.

(387) For security purposes, the analytics service **414** can be configured to encrypt the user, device, and mobile traffic data bindings that the service **414** produces.

(388) Secure Document Containers

(389) Reference is made again to FIG. 3. In some embodiments, a mobile device **120** can include a

secure document container **336**, which can be referred to as a “container.” As explained herein, the container **336** can help prevent the spread of enterprise information to different applications and components of the mobile device **120**, as well as to other devices. The enterprise system **110** (which can be partially or entirely within the cloud **156**) can transmit documents to the devices **120**, which can be stored (e.g., by the enterprise agent **320**) within the container **336**. The container **336** can prevent unauthorized applications **318** and other components of the device **120** from accessing information within the container **336**. For enterprises that allow users **115** to use their own mobile devices **120** for accessing, storing, and using enterprise data, providing containers **336** on the devices **120** helps to secure the enterprise data. For instance, providing containers **336** on the devices **120** can centralize enterprise data in one location on each device **120**, and can facilitate selective or complete deletion of enterprise data from the device **120**.

(390) As used in this context a “document” can comprise any computer-readable file including text, audio, video, and/or other types of information or media. A document can comprise any single one or combination of these media types.

(391) The secure document container **336** can comprise an application that implements a file system **338** that stores documents and/or other types of files. The file system **338** can comprise a portion of a computer-readable memory of the mobile device **120**. The file system **338** can be logically separated from other portions of the computer-readable memory of the mobile device **120**. In this way, enterprise data can be stored in secure document container **336** and private data can be stored in a separate portion of the computer-readable memory of the mobile device **120**. The container **336** can allow the enterprise agent **320**, mobile device applications **318** and/or other components of the device **120** to read from, write to, and/or delete information from the file system **338** (if authorized to do so). Deleting data from the container **336** can include deleting actual data stored in the container **336**, deleting pointers to data stored in the container **336**, deleting encryption keys used to decrypt data stored in the container **336**, and the like. The container **336** can be installed by, e.g., the agent **320**, IT administrators of the enterprise system **110**, or the device **120** manufacturer. The container **336** can enable some or all of the enterprise data stored in the file system **338** to be deleted without modifying private data stored on the mobile device **120** outside of the container **336**. The file system **338** can facilitate selective or complete deletion of data from the file system **338**. For example, a component of the enterprise system **110** can delete data from the file system **338** based on, e.g., encoded rules. In some embodiments, the agent **320** deletes the data from the file system **338**, in response to receiving a deletion command from the enterprise system **110**. In other embodiments, the data is deleted without the assistance of the agent **320**, for example if an agent **320** is not provided.

(392) The secure document container **336** can comprise an access manager **340** that governs access to the file system **338** by applications **318** and other components of the mobile device **120**. Access to the file system **338** can be governed based on document access policies (e.g., encoded rules) stored in the documents and/or the file system **338**. A document access policy can limit access to the file system **338** based on (1) which application **318** or other component of the device **120** is requesting access, (2) which documents are being requested, (3) time or date, (4) geographical position of the device **120**, (5) whether the requesting application **318** or other component provides a correct certificate or credentials, (6) whether the user of the device **120** provides correct credentials, (7) other conditions, or any combination thereof. A user's credentials can comprise, for example, a password, one or more answers to security questions (e.g., What is

the mascot of your high school?), biometric information (e.g., fingerprint scan, eye-scan, etc.), and the like. Hence, by using the access manager **340**, the container **336** can be configured to be accessed only by applications **318** that are authorized to access the container **336**. As one example, the access manager **340** can enable enterprise applications installed on the mobile device **120** to access data stored in the container **336** and to prevent non-enterprise applications from accessing the data stored in the container **136**.

(393) Temporal and geographic restrictions on document access may be useful. For example, an enterprise administrator may deploy a document access policy that restricts the availability of the documents (stored within the container **336**) to a specified time window and/or a geographic zone (e.g., as determined by a GPS chip **316**) within which the device **120** must reside in order to access the documents. Further, the document access policy can instruct the container **336** or agent **320** to delete the documents from the container **336** or otherwise make them unavailable when the specified time period expires or if the mobile device **120** is taken outside of the defined geographic zone.

(394) Some documents can have access policies that forbid the document from being saved within the secure document container **336**. In such embodiments, the document can be available for viewing on the mobile device **120** only when the user **115** is logged in to the enterprise system **110**.

(395) The access manager **340** can also be configured to enforce certain modes of connectivity between remote devices (e.g., an enterprise resource **130** or other enterprise server) and the container **336**. For example, the access manager **340** can require that documents received by the container **336** from a remote device and/or sent from the container **336** to the remote device be transmitted through application tunnels, for example, as described above. Such application tunnels can use the tunneling mediator **224** of the enterprise system **110**. The access manager **340** can require that all documents transmitted to and from the container **336** be encrypted. The enterprise agent **320** or access manager **340** can be configured to encrypt documents sent from the container **336** and decrypt documents sent to the container **336**. Documents in the container **336** can also be stored in an encrypted form.

(396) The secure document container **336** can be configured to prevent documents or data included within documents from being used by unauthorized applications or components of the mobile device **120** or other devices. For instance, a mobile device application **318** having authorization to access documents from the container **336** can be programmed to prevent a user from copying a document's data and pasting it into another file or application interface, or locally saving the document or document data as a new file outside of the container **336**. Similarly, the container **336** can include a document viewer and/or editor that does not permit such copy/paste and local save operations. Moreover, the access manager **340** can be configured to prevent such copy/paste and local save operations. Further, the container **336** and applications **318** programmed and authorized to access documents from the container **336** can be configured to prevent users from attaching such documents to emails or other forms of communication.

(397) A mobile device application **318** can be programmed to lookup and find the secure document container **336** (or a secure web browser **332**, described below, that includes the container **336**) as a resource of the mobile device **120**. In certain embodiments, the application **318** can run in a secure virtual machine separate from a virtual machine of an operating system of the mobile device **120**. According to some other embodiments, the application can run within the secure web browser **332**.

An application **318** can be programmed to write enterprise-related data only into the container **336**. For instance, the application's **318** source code can be provided with the resource name of the container **336**. Similarly, a remote application (e.g., an enterprise resource **130**) can be configured to send data or documents only to the containers **336** of one or more mobile devices **120** (as opposed to other components or memory locations of the devices **120**). Storing data to the container **336** can occur automatically, for example, under control of the application **318**, the enterprise agent **320**, or the web browser **332**. An application **318** can be programmed to encrypt or decrypt documents stored or to be stored within the container **336**. In certain embodiments, the container **336** can only be used by applications (on the device **120** or remote) that are programmed to look for and use the container **336**, and which have authorization to do so.

(398) The secure document container **336** can serve as a temporary repository for documents and other files sent to the mobile device **120**. Remote applications can be configured to send documents to the container **336** (e.g., via application tunnels) on a one-time or periodic basis. For example, a sales-related enterprise resource **130** can be programmed to send sales-related documents (e.g., most recent price sheets) every morning to the containers **336** of a team of users **115** having sales-related roles **206** (e.g., sales persons). The sales-related documents can have document access policies such that the documents will “self-destruct” (e.g., be automatically deleted from the container **336**—the deletion being performed by, e.g., the container **336** itself or the enterprise agent **320**) at a certain time or at the expiration of a time period beginning at a defined event the user's opening of a document). Document distribution policies (e.g., encoded rules) can be provided (e.g., within the mobile device management system **126**) to control when and how remote applications (e.g., enterprise resources **130**) send documents to the containers **336**, to which users **115** the documents are sent, what restrictions (e.g., temporal or geographic restrictions) are placed on the use and availability of the documents (e.g., in the form of document access policies as described above), etc.

(399) Remote applications that send documents to one or more secure document containers **336** of mobile devices **120** can be configured to integrate with other repositories, for the purpose of sending documents from such repositories to the containers **336**. Such other repositories can be stored, for example, within the enterprise system **110** (e.g., enterprise document repositories such as a Microsoft Sharepoint™ repository) or in a cloud-computing system (e.g., a Box.net™ repository).

(400) Software Development Kit for Mobile Device Applications

(401) Another aspect of certain embodiments involves a software development kit (SDK) that enables an application developer to embed one or more of the functionalities described herein into a mobile device software application, such as a software application **318**. As used herein, “embed” can include the modification of an application's source code. FIG. 24 illustrates an embodiment of a software development system **2402** including an SDK **2404** for creating a mobile device application **2406**. The software development system **2402** can be implemented by any suitable computer hardware. A software developer can create an application **2406** such as by generating program code and compiling it into an executable program compatible with a mobile device **120**.

(402) The SDK **2404** can comprise a library of development tools **2408** providing different functionalities. The development tools **2408** can comprise code snippets, data structures, protocols, routines, and the like. The SDK **2404** can provide an application programming interface (API) **2410**

that enables an application **2406** to interface with the development tools **2408**. The SDK **2404** can include a program editor **2412** for generating the code for an application **2406**, and a compiler **2414** for converting the code into a machine-readable format. The SDK **2404** can include a debugging tool **2416** for debugging developed code. It will be appreciated that the SDK **2404** can include other features in addition to these. It will also be appreciated that the SDK **2404** need not include all of the illustrated features.

(403) The development tools **2408** can include tools for embedding one or more of the functionalities described herein into a mobile device software application **2406**. It will be appreciated that any sub-combination of these functionalities can be embedded into the application **2406**, and that other functionalities not described herein can also be so embedded. Different development tools **2408** are now described.

(404) In certain embodiments, the SDK **2404** includes a development tool **2408** that allows an application developer to embed, within an application **2406**, functionality for forming and maintaining an application tunnel (for example, as described above) with a network resource, and communicating with the network resource by sending and receiving communications through the tunnel. The network resource can comprise, for example, an enterprise resource **130**. The tool **2408** can be configured to add application tunnel functionality that participates with an enterprise agent **320**. As described above in the application tunnels section, the enterprise agent **320** can receive, network communications from the application **2406**, encapsulate them according to an encapsulation protocol, send the encapsulated communications to a tunneling mediator, receive similar communications from the tunneling mediator (which came from a tunnel endpoint resource), unpack encapsulated communications received from the tunneling mediator, and send the unpacked communications to the application **2406**. Alternatively, the tool **2408** can provide functionality for forming an application tunnel without the participation of the enterprise agent **320**, wherein the application **2406** itself performs these actions using an encapsulation protocol as described above.

(405) In certain embodiments, the SDK **2404** includes a development tool **2408** that allows an application developer to embed, within an application **2406**, functionality for improving the communication experience between a mobile device **120** and a network resource, such as an enterprise resource **130**, particularly for application tunnel communications. Such functionality can include caching user-inputted data locally on the mobile device **120** in the event of a lost connection to a network, as described above. Such functionality can likewise include compression of data to be sent to a network resource, and decompression of data received from the network resource, as described above. Again, such embedded functionality can participate with an enterprise agent **320** to enable these features, or can provide these features separate from an enterprise agent **320**.

(406) In certain embodiments, the SDK **2404** includes a development tool **2408** that allows an application developer to embed, within an application **2406**, functionality for participating in a remote control session between a mobile device **120** and a helpdesk operator, as described above. Such functionality can allow a helpdesk operator to view data about the application **2406** installed on the mobile device **120**, and/or to control aspects of the application **2406** and possibly other features of the mobile device **120**. Such functionality can include sending user interface emulation data to the helpdesk operator's computer, as described above. Such functionality can include receiving commands from the helpdesk operator for executing actions on the mobile device **120**.



Again, such embedded functionality can participate with an enterprise agent **320** to enable these features, or can provide these features separate from an enterprise agent **320**.

(407) In certain embodiments, the SDK **2404** includes a development tool **2408** that allows an application developer to embed, within an application **2406**, functionality for finding, providing credentials to, reading from, and/or writing to a secure document container **336** as described above. This can allow the application **2406** to access and update information within the container **336**. This can also allow the application **2406** to access documents securely received by the mobile device **120** from a network resource, such as an enterprise resource **130** or other application or component of an enterprise system **110**. The development tool **2408** can be configured to modify the source code of an application **2406** so that the application **2406** can find the container **336** by its resource name on the device **120**. The development tool **2408** can be configured to modify the source code of an application **2406** so that the application **2406** writes all data (or perhaps just data relating to the enterprise **110**) into the container. For example, the development tool **2408** can be configured to parse the application's source code to find commands for writing data to a memory (e.g., application state data for allowing the user to stop using the application and then later restart the application in the exact state in which the user left it) or reading data from the memory, and to adjust one or more of those portions of the source code to write data into the container **336** and read data from the container **336**.

(408) In some embodiments, the SDK's development tool **2408** can embed within the application **2406** the ability to encrypt documents to be stored within the container **336**, and/or the ability to decrypt documents obtained from the container **336**. The development tool **2408** can embed within the application **2406** an editor for allowing a user **115** of a mobile device **120** to view and/or edit documents obtained from the container **336**. The editor can also allow the user **115** to upload edited or newly created documents to the container **336** or to a network resource (e.g., an enterprise resource **130** of the enterprise system **110**).

(409) In certain embodiments, the SDK **2404** includes a development tool **2408** that allows an application developer to embed, within an application **2406**, mobile device rules such as the rules **214** described above. Further, the development tool **2408** can allow the developer to embed functionality for evaluating the mobile device rules, including querying the device **120** or other network resources for data needed for the evaluation. The embedded functionality can also include remedial actions associated with the mobile device rules, such as the remedial actions **216** described above. The embedded functionality can further include a remedy agent for automatically executing remedial actions on the mobile device, as described above. Compared to the aforementioned mobile device rules **218** (which are described above predominantly as user-specific and device-specific rules), a software developer can embed rules and remedial actions that are customized to a specific application **2406**. In certain embodiments, the SDK **2404** includes tools for creating and editing mobile device rules and remedial actions, such as the tools **221** described above. A software developer can use the creating/editing tools to create mobile device rules and remedial actions, and to embed them into an application **2406**. Certain embodiments provide an online library of mobile device rules and remedial actions that a software developer can use, with or without modification, and embed within an application **2406**.

(410) In certain embodiments, the SDK **2404** includes a development tool **2408** that allows an application developer to embed, within an application **2406**, functionality for application fault detection (e.g., using mobile device rules as described above), application performance

measurement, and the detection of related events. The embedded functionality can include the logging of detected faults, performance measurements, related events, event times, event locations, and other data within a local storage of a mobile device **120**. The development tool **2408** can allow an application **2406** to be configured to report such data to a network resource, such as a component of an enterprise system **110**, and/or an analytics service such as the analytics service **414** described above. This embedded functionality can give IT administrators visibility into what is happening on the mobile device, at least as it pertains to the specific application **2406** installed thereon. Further, an analytics service can analyze data across multiple different mobile devices **120** that run the specific application **2406**. The embedded functionality can include encrypting the data logged on the mobile device **120** and/or reported to other components via network communications.

(411) In certain embodiments, the SDK **2404** includes a development tool **2408** that allows an application developer to embed, within an application **2406**, functionality for cooperating with a meta-application, such as an enterprise system-based meta-application portion **150** and/or a cloud-based meta-application portion **151**. The embedded functionality can include discovery procedures for discovering information about the installed application **2406** or a mobile device **120** on which it is installed, and sending the discovered information to the meta-application for use in, e.g., constructing a queryable model (similar to the enterprise model **814** of FIG. 8) of which the application **2306** and/or mobile device **120** forms at least a part. The embedded functionality can include receiving a query from the meta-application, responding to the query by retrieving the queried data from the mobile device **120**, and sending the queried data to the meta-application. As discussed above, the meta-application can use the queried data to detect problems, perform root cause analysis, and/or select remedial actions. Hence, the embedded functionality can include receiving a remedial action from the meta-application, executing the remedial action on the mobile device **120**, and reporting results of executing the remedial action to the meta-application. In some embodiments, the embedded functionality participates with a device-resident, enterprise agent **320** to provide these features, while in other embodiments the embedded functionality provides these features without cooperating with an enterprise agent **320**.

#### (412) Secure Web Browser

(413) Another aspect of certain embodiments involves a web browser within which other mobile device software applications can run. The web browser can be provided with some or all of the enterprise security and other features described herein, and can extend those features for use with the mobile device applications that run within the browser. In this way, the browser can be used to implement BYOD policies while maintaining a desired level of control over applications running on a mobile device **120** of an enterprise user **115**. An enterprise can require some or all of its users **115** to install and use this web browser, to reduce enterprise security risks associated with the use of such mobile device applications. Further, in some circumstances, such a web browser can make it unnecessary for application developers to develop different versions of a mobile device application for different mobile device platforms. As mentioned above, the secure browser can also be used to enable mobile device users to access a corporate intranet without, the need for a virtual private network (VPN).

(414) Referring to FIG. 3, a mobile device **120** can include a specialized web browser **332**. The web browser **332** can be configured to perform the functions of conventional web browsers, including surfing Internet sites, displaying and/or playing multimedia content, received from web

servers, etc. The web browser **332** can store data accessed via a network in a secure document container **336** and/or in a secure browser cache. Such data can be deleted at the direction of an enterprise. For instance, a mobile device management system **126** can initiate deletion or otherwise make data stored in the secure document container **336** and/or the secure browser cache inaccessible. Additionally, the web browser **332** is preferably configured to act as a container for at least some other software applications **318** installed on the mobile device **120**, to allow those applications **318** to run within the browser **332**. A software application **318** can be configured to launch the browser **332** when the application **318** is itself launched by a user **115**. Moreover, an application **318** can be configured to launch the browser **332** and run within the browser **332** in a manner that is transparent to the user **115**. In other words, the user **115** can be given the impression that the application **318** is running conventionally, without involving the web browser **332**. The web browser **332** can leverage a protocol that facilitates its usage as a container for other software applications **318**. For example, the web browser **332** can leverage HTML5 for this purpose.

(415) The web browser **332** can provide some or all of the functionalities described herein. For example, the web browser **332** can include some or all of the functionalities provided by the SDK **2404** and/or enterprise agent **320** described above. Thus, the web browser **332** can be configured to use application tunnels for communications with network resources (such as enterprise resources **130**). The web browser **332** can receive (or have embedded) mobile device rules **214** and remedial actions **216** from the mobile device management system **126** or another component of an enterprise system **110**. The web browser **332** can alternatively have embedded mobile device rules and remedial actions. The web browser **332** can employ caching and/or compression methods within application tunnels, to improve the user's communication experience as described above. The web browser **332** can be configured to provide credentials to, read from, write to, and/or provide an editor for displaying and editing documents obtained from a secure document container **336** of the mobile device **120**, as described above. In certain embodiments, the web browser **332** can implement the secure document container **336**. The web browser **332** can prompt a user **115** to supply access credentials prior and verify the access credentials prior to exposing functionality of an application **318** running within the browser **332** to the user **115**. Alternatively or additionally, the web browser **332** can cause data stored to the mobile device **120** by an application **318** running in the web browser **332** to be encrypted. The web browser **332** can be configured to participate in a remote control session with a helpdesk operator, as described above. The web browser **332** can be configured to log fault detections, performance measurements, related events, event times, event locations, and other data, and to provide such data to an analytics service as described above in connection with the SDK **2404**. The web browser **332** can be configured to engage in communications with a meta-application, again as described above. By providing at least some of these and/or other functionalities, the web browser **332** can make it unnecessary for mobile device application developers to embed such functions within the mobile device applications **318**.

(416) In some embodiments, web browser **332** is configurable so that one or more of these functionalities can be activated or deactivated under defined conditions that can be configured, e.g., remotely by a remote computer system such as the enterprise system **110**. Definable conditions include temporal conditions, location conditions, mobile device properties, user properties (e.g., roles **206**), and others. A temporal condition can be the time of day. For example, the web browser **332** can be configured to force all mobile traffic (at least for applications **318**

configured to launch the browser **332**) through application tunnels only during working hours (e.g., 8 am to 5 pm on Monday through Friday), and to send the traffic conventionally outside of those hours. A location condition can be the location of the mobile device **120**. For example, the browser **332** can be configured to activate the aforementioned compression and caching features when the device **120** is in a geographical area known to have bad wireless connectivity.

(417) Different web browsers **332** can be created for different, mobile device platforms, with each of the browser versions using a single standard for running mobile device applications. This can advantageously allow mobile device application developers to develop mobile device applications **318** in just one programming language, as opposed to creating different versions for the various mobile device platforms. This can substantially reduce the application development workload for developers.

(418) An enterprise can require its users **115** to install the web browser **332** onto their mobile devices **120**, and can prohibit the use of other web browsers. The required browser **332** can be configured to direct at least some of the mobile device traffic through application tunnels to an enterprise-controlled tunneling mediator, such as the mediator **224** described above. This gives the enterprise greater control over the traffic, reducing security risks. An enterprise can deploy a mobile device rule **214** that enables a device-resident enterprise agent **320** or the web browser **332** itself to detect the installation and/or use of a prohibited web browser on the mobile device **120**. An associated remedial action **216** can prevent the usage of the prohibited web browser according to methods described above, such as by uninstalling it, preventing it from running, etc.

(419) In some embodiments, the secure web browser **332** can be configured to direct some or all web surfing requests to a content-filtering server as described above.

#### (420) Modifying Behaviors of Pre-Existing Mobile Applications

(421) A system and process will now be described for enabling non-developers, such as members of a company's IT department, to add to or otherwise modify the behaviors of an existing mobile application, such as an Android, IOS, or Windows Mobile application. The system and process can be used, as one example, to create different versions of a mobile application (with different privileges, access rights, etc.) based on a user's role within the enterprise. For instance, different versions of the mobile application can be created for different job categories (e.g., executive, non-executive employee, intern, etc ) and/or different departments (sales, IT, human resources, etc.) The processes described in this section can be implemented to an application modification or "wrapping" tool or utility that is made available to enterprises that use the disclosed system. This utility may, for example, be hosted on a server (e.g., as a web service) that is accessible to enterprises, or may be provided to the enterprises (e.g., as a PC application).

(422) In a typical use case scenario, the mobile application to be modified is a custom application developed for a particular enterprise. However, this need not be the case. For example, the disclosed system and process are also applicable to commercially available mobile applications available in app stores. The mobile applications can be modified without being specially written to support or enable such modifications. For example, the developer need not include any special code or functionality in the application to enable or facilitate the modifications, and need not be involved in the disclosed process of modifying the application.

(423) The behaviors that are modified typically include or consist of behaviors that involve standard API calls or classes. The following are examples of some of the types of behaviors that can be added or modified via the disclosed process:

(424) 1. The cut-and-paste capability commonly provided through mobile device operating systems, such as Android and IOS, can be disabled within a particular mobile application, such as an application that provides access to confidential corporate data. This behavioral change may be desirable to inhibit employees (or a certain class of employees) from accidentally or maliciously sending or moving confidential data to an unauthorized location.

(425) 2. A mobile application that stores its output in a non-encrypted format can be modified to store its output in an encrypted format. In one embodiment, this is accomplished in-part by modifying the mobile application's input/output references to cause the application to use an encryption library to encrypt and decrypt the data it writes to or reads from memory. Code may also be injected that causes the mobile application to obtain a key from the enterprise agent for use in encrypting and decrypting the data.

(426) 3. A mobile application that uses a certain level or type of encryption can be modified to use a different level or type of encryption. For example, if the Federal Government requires the enterprise to begin using a particular encryption library, an existing mobile application can be modified to effectively replace the existing encryption library with the new one.

(427) 4. An enterprise can modify a mobile application to cause it to use a special secure connection to the enterprise's network or enterprise system. For example, the mobile application can be configured to use a secure application tunnel as described above.

(428) 5. A mobile application can be modified to add a log-in or other authentication prompt or screen.

(429) 6. A mobile application can be configured to log and/or report data regarding its usage. This data may include, for example, the time and duration of use, the location (based, e.g., on GPS coordinates) of use, the application features invoked, the access points accessed, etc. (Existing mobile device operating systems such as Android and IOS provide functionality for enabling applications to obtain these and other types of usage parameters). This usage data may be used by an enterprise to, for example, monitor employee compliance with the enterprise's usage restriction policies, to identify and correct problems with particular enterprise mobile applications, or to determine whether to continue paying for application licenses for particular users. The application usage data collected on a mobile device **120** may, for example, be reported by the enterprise agent **320** to the mobile device management system **126**, or some other system, for analysis.

(430) 7. A mobile application can be modified to enable an enterprise to remotely initiate deletion of the application's data on a particular mobile device **120** of a particular employee, without affecting other users of the application. As mentioned above, such selective wipe operations may also be executed when, for example, a user fails to enter a valid enterprise passcode a threshold number of times.

(431) 8. A mobile application can be modified such that it can only be launched in by a secure

launcher **350B** (FIG. 3B), and not by the general launcher of the mobile device's operating system. This may be accomplished by, for example, changing one or more references in the mobile application to the mobile operating system's general launcher so that they point instead to the secure launcher. As explained above, the secure launcher may implement one or more security policies, such as requiring entry of a valid passcode before the enterprise application is launched. The secure launcher may also cause the enterprise applications to run in a secure execution environment, such as by causing the enterprise applications to be executed using a secure virtual machine (FIG. 3B) that is separate from the mobile operating system's virtual machine (See section below.)

(432) 9. A mobile application can be modified to cause it to launch in a secure virtual machine **350C** (FIG. 3B). This may be accomplished by, for example, modifying a reference in the application (e.g., in an Android application's manifest or in any manner in which the application is launched) to cause it to be launched in a secure VM. As explained below in the section titled Secure Virtual Machine, the secure VM may implement some of the client-side security functions described herein (encryption, application tunnels, etc.), reducing or eliminating the need to add such functions to the mobile applications themselves. This can enable enterprise applications to be run in a secure execution environment, while personal applications are run in a default VM.

(433) Other examples include disabling offline access, adding URL filtering, adding API filtering, disabling writes to local storage, and preventing documents from being opened in new applications.

(434) FIG. 29 illustrates one embodiment of the application modification system. The system includes an application transformer **2900** that makes the modifications based on operator-selected policies. For Android applications the transformer **2900** receives the application's .APK (application package) file, and outputs a new .APK file representing the modified application. For IOS, the transformer **2900** receives a .IPA (iPhone application archive) file, and outputs a new .IPA file representing the modified application. Various other file formats and mobile device operating systems may be supported. As shown in FIG. 29, the application transformer **2900** preferably includes a disassembler **2900A** (for disassembling the application's executable code), a code analyzer/mapper **2900B**, a code modifier/injector **2900C**, and an application rebuilder **2900D**.

(435) As shown in FIG. 29, the transformer **2900** accesses a policy library **2902** containing policy descriptions for various policies and associated behaviors, such as those listed above. For example, a “disable cut-and-paste” policy may be provided. The policies may be described in any appropriate language and format. For example, the policy descriptions may be stored as smali files. As further shown in FIG. 29, the system also includes a control interface **2904** or “console” that enables an administrator to select the policy or policies to be applied to a given mobile application. The console **2904** may also include a tool for enabling administrators to define new policies. For example, a new policy could be defined that adds an authentication sequence, disables cut-and-paste, and causes all files to be stored in encrypted form. This policy could then be used as a basis for modifying multiple mobile applications.

(436) In a typical use case scenario, a member of a company's IT department uses the control interface **2904** to: select a mobile application to be modified, select the policy or policies to be applied, and initiate the transformation process. The modified application is then distributed to the relevant employees or other users (e.g., through a special application store that is accessible through the enterprise agent, as described above). This process may be repeated with different

policy selections to create different versions of the application for different users. The policy library **2902** may, for example, include policy files for implementing some or all of the types of policies described above (and various others).

(437) FIG. 30 illustrates a sequence of steps that may be performed by transformer **2900** to modify an Android application based on a selected set of one or more policies. A similar process may be used to transform applications written for other operating systems, such as IOS and Windows Mobile. The entire process shown in FIG. 30 is preferably fully automated, meaning that no human intervention is required. In block **3000**, the .APK file is opened. As is known in the art, this file contains various application components, such as the application's executable code, images, XML files, a manifest, and other resources. In block **3002**, the disassembler **2900A** disassembles the application's executable code to generate one or more textual smali files. As will be recognized, an intermediate language other than smali can be used to implement the disclosed modification tasks.

(438) In block **3004**, the analyzer/mapper **2900B** analyzes and maps the application code (in smali format) to generate information regarding API calls that will potentially be replaced. In block **3006**, the relevant API calls are replaced with new API calls for implementing the selected policy or policies. In addition, the associated code from the policy library **2902** is added. For example, if the cut-and-paste functionality is being disabled, any API calls that are used by the application to access the operating system's cut-and-paste functionality may be removed or replaced.

(439) As one example, a new version of the Java I/O File Input Stream (Java.io.FileInputStream) class may be generated, and all references to the original class may be modified to point to this new version. The new version may, for example, include code for encrypting and decrypting data on file write and read operations, respectively.

(440) In block **3008** of FIG. 30, additional code may be added, if applicable, to implement one or more features or behaviors that do not require the replacement of any existing API calls. As one example, code may be added for enabling an authorized administrator to remotely trigger the deletion, on a user-specific or mobile device specific basis, of the application's data stored on a particular mobile device. In this example, the code added in block **3008** would add functionality for receiving and processing a message containing a command to perform such a selective wipe or deletion operation.

(441) To provide an additional layer of security, the portions of the code that are modified in the preceding blocks may be obfuscated using obfuscation methods and functions that are known in the art. The use of obfuscation impairs the ability of others to reverse engineer the security functions added to the application. Obfuscation may be applied to the disassembled code (e.g., smali code), or may be applied at a different level.

(442) In block **3010** of FIG. 30, the application's manifest (e.g., AndroidManifest.xml) is modified, if necessary, to reflect the modified behaviors. As one example, if the application is being modified to be launched in a secure shell, the manifest would be modified to instruct the Android operating system to use the secure shell to launch the application. In some embodiments, this involves replacing a reference to the operating system's general launcher with a reference to a secure launcher **350B** (FIG. 3B). In block **3012**, the modified smali code and manifest, together with the other extracted application components, are compiled into a new .APK file. In block **3014**, this new .APK file is signed using a digital certificate.

(443) Mobile applications written for the IOS operating system may be modified in a similar manner. Typically, such an application is distributed as an IPA file that includes an executable in Mach-O format, a P-list, and resources. Once the executable has been disassembled to produce ARM assembly code, it is mapped to identify classes to potentially be replaced, and is then modified by: (1) identifying one or more specific classes to be replaced, (2) adding/modifying the code to replace such class(es), (3) adjusting the class structure to reflect the modifications, so that each new class is a subclass of the original code, and (4) updating the references to point to the new class or classes.

(444) In some embodiments, the above-described process may be augmented with one or more tests for verifying that the mobile application to be modified does not contain malware, or does not otherwise present a risk to enterprise security. One such test involves generating a hash of some or all of the application files, and then comparing this hash to library of hashes that are associated with known malware. If a match is found (indicating that the application likely includes malware), the application modification process may be terminated.

(445) Another such test involves inspecting the API calls and URL requests made by the application to check for suspicious activity. Examples of suspicious activity include reading the personal contacts stored on the device, sending an email to a cloud storage service, and sending location information without first requesting user permission. Based on this analysis, a score (e.g., on a scale of 1 to 100) may be generated that represents the level of risk posed by the mobile application. The modification process may be terminated if this score exceeds a threshold. The score may additionally or alternatively be included in a report that details the suspicious activity detected. The application modification tool may, for example, output this report for review, and may prompt the administrator-user to confirm or indicate whether the modification process should proceed.

(446) The application modification system shown in FIG. 29 may, for example, be implemented on a server, personal computer, workstation, or other computer or system of computers within a company's enterprise system. Alternatively, the application modification system may be implemented as a hosted service that is accessible to corporate customers over the Internet. The various components **2900-2904** of the system may be implemented as code modules that are stored on any type(s) of non-transitory computer storage device or system.

(447) The components **2900**, **2902**, **2904** of the system shown in FIG. 29 may be provided to companies as part of a larger system (such as the system described in other sections of this specification) for enabling the companies to manage mobile devices and to protect data accessed by such devices. For example, these components may be bundled and licensed with various other components described in this disclosure. Alternatively, the application modification system of FIG. 29 may be provided to companies as a standalone product, or as a system that is hosted by a service provider and accessed over a network.

(448) Secure Virtual Machine

(449) As mentioned above, one approach for effectively adding a security layer to the enterprise mobile applications is to configure or force such applications to run within a secure VM **350C** (FIG. 3B) installed on the mobile device. The secure VM may be similar to the mobile operating system's VM, but may point to special code libraries that are added to the mobile device, including code



libraries for performing such functions as encrypting/decrypting data and using application tunnels. The use of a secure VM enables an enterprise's IT department to effectively add a security layer to a pre-existing mobile application with little or no modification to the application itself. This may be desirable when, for example, the enterprise wishes to use a popular, commercially available mobile application as an enterprise application, but does not have authorization to (or otherwise does not wish to) make certain types of modifications to the application.

(450) The secure VM **350C** can be loaded with its own set of private libraries for storage, networking, policy management, etc. For example, some or all of the data stored by an application running in the secure VM **350C** can use a certain encryption library. The secure VM **350C** can implement a set of policies (such as authentication, disabling of cut/paste, prevention of access to certain URLs, prevention of access to certain APIs etc.) to control execution of the application within the secure VM **350C**.

(451) The secure VM **350C** can block the execution of an application running therein based on detecting certain conditions, such, as conditions indicative of the application having a virus or being malware. Hooks can be added to the secure VM **350C** to prevent programs from being executed when certain conditions are detected. The secure VM **350C** can observe the execution characteristics of an application running therein to determine that the application does not have exhibit malicious behavior.

(452) By using a custom VM, all corporate content can essentially be separated from other content stored on the device. Such a custom VM can prevent data or applications from being shared with applications that are executed in the default VM of the mobile device **120**. Moreover, the data accessed and/or manipulated by an application running in the custom VM can be stored in the secure data container **336** as described above.

(453) In one embodiment, a single secure VM is provided on the mobile device **120** for running enterprise applications, and can be used to concurrently run multiple enterprise applications concurrently. In another embodiment, multiple secure VMs are provided on the mobile device, such that each enterprise application runs within a separate secure VM. A hybrid of these two approaches is also possible.

(454) A variety of methods can be used to force or configure a pre-existing mobile application to use a secure VM. One such approach involves modifying the mobile application to cause it to use a secure launcher **350B**, as described in the preceding section. When the application is launched, the secure launcher launches the secure VM, and then effectively passes the mobile application to the secure VM for execution. Another approach involves modifying the mobile application by replacing references to the operating system's default virtual machine with references to the secure VM. Another approach involves instructing the mobile device's operating system, at the time of installation of the application, to execute the mobile application in the secure VM:

(455) In one embodiment, whenever a mobile application running in the secure VM performs a file read or write operation, the secure VM uses an encryption library to process the data being read or written. The secure VM thereby applies encryption to the enterprise data stored locally by enterprise applications.

(456) Library files used by the secure VM may, in some embodiments, be incorporated into the

operating system or otherwise installed on the mobile device with the cooperation of the OS developer, device manufacture/seller, or other party that has the appropriate permission levels for making such additions. The ability to add such library files generally increases the security capabilities of the secure VM, but is not essential.

(457) One benefit of running an application in a secure VM is that the secure VM can be loaded with an alternate set of private libraries for storage, networking, policy management, etc. For example, a library can be loaded that causes all data stored by the application to be encrypted using a certain encryption library. Libraries can also be loaded that, for example, disable cut/copy/paste operations, require user authentication, prevent access to certain URLs, prevent access to certain APIs, etc. The particular libraries that are loaded may, for example, depend on the role or position of the user within the enterprise, the particular application being launched, and/or other criteria.

(458) Another benefit of running an application in a secure or custom VM is that the application's execution can be blocked if the application exhibits suspicious behaviors of the type present in malware or viruses. This may be accomplished by adding hooks to the secure VM to enable an application's execution to be monitored and/or blocked.

(459) The secure or custom VM also provides a mechanism for keeping enterprise content separate from other content stored on the device. For example, through the use of the secure VM, the data stored by an enterprise can be stored in a secure container as described above. This data advantageously is not accessible in unencrypted form to the device's default VM or the applications that run within it.

(460) In the context of the Android OS, one method that can be used to launch an application in the secure VM involves the use of the `app_process` command to modify the standard launch sequence. For example, a command of the following format may be used once Zygote initializes a child process: `execvp("/system/bin/app_process", . . . <args>. . .)`. (Zygote is a special process that is created when Android boots, once created, it opens a server socket to listen for process creation requests.) This call replaces the old executable image with a fresh one, and enables the secure VM to be loaded with some existing libraries/jars, and with some new libraries/jars that implement, e.g., enterprise policy push, secure storage, and secure networking features. The new instance is not a share of Zygote or any other parent process, but rather is a completely new process with its own execution environment and added set of behaviors. Once the secure VM is loaded, the following steps can be performed to launch the application in the secure VM: (1) the newly created process performs an "attachment" operation; (2) once the `ActivityManagerService` receives the attach request from the newly created process, it sends the stored intent to it so that `ActivityThread` will look for the intent in the application's Manifest and will create that Activity; and (3) it then starts running the application. These three steps are the same as the last three steps ordinarily performed when an application is launched in Android. Android Runtime or any other compatible runtime can be loaded in the secure VM such that the application is compatible with the secure VM. This above process can be varied for use with other operating systems by those skilled in the art.

(461) An application can be configured or "marked" to use the secure/custom VM in various ways. For example, in the context of Android, the standard command "`adb shell pm enable (package name)`" can be used to set the "enabled" state or flag of the application package. As another example, the enterprise agent installed on the device can, upon installation, make a call to this API

and specify all of the applications that will run in the secure/custom VM. When such an application is later launched, the “enabled” flag can be checked (before Zygote is asked to create/fork a new process), and a new secure VM instance can be created based on the state of this flag. This process can be varied for use with other operating systems by those skilled in the art.

#### (462) Conclusion

(463) The secure mobile gateway **128** and the mobile device management system **126** may each be implemented by a computer system made up of one or more computing devices (e.g., physical servers, workstations, etc.), which may, but need not, be co-located. Each such computing device typically includes a processor (or multiple processors) that executes program instructions or modules stored in a memory or other non-transitory computer-readable storage medium or device. The secure mobile gateway **128** and mobile device management system **126** may be implemented on common hardware or on separate and distinct hardware.

(464) All of the methods and processes described above may be embodied in, and fully automated via, software code modules executed by one or more computing devices (e.g., smartphones, tablets, other types of mobile devices, physical servers, etc). Each such computing device typically includes a processor (or multiple processors) that executes program instructions or modules stored in a memory or other non-transitory computer-readable storage medium or device. The code modules may be stored in any type of computer-readable storage medium or other computer storage device. Some or all of the methods may alternatively be embodied in specialized computer hardware (e.g., ASIC's or FPGAs). Where a given software component (such as the enterprise agent or secure launcher) is herein described as performing or implementing a given function, it should be understood that the component, through executable instructions, instructs one or more processors (e.g., the processor of a mobile device) to perform or implement the function.

(465) Various modifications to the implementations described in this disclosure may be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other implementations without departing from the spirit or scope of this disclosure. Thus, nothing in this specification is intended to imply that any feature, characteristic, or attribute of the disclosed systems and processes is essential.

(466) Certain features that are described in this specification in the context of separate implementations also can be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation also can be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

(467) Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the implementations described above should not be understood as requiring such, separation in all implementations, and it should be understood that

the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

## Claims

1. A method comprising: generating, by an enterprise agent operable on a client device, a secure container in a first portion of a computer-readable storage of the client device, the secure container being encrypted and comprising a file system, wherein the first portion of the computer-readable storage is separate from a second portion of the computer-readable storage; verifying, by the enterprise agent, a user of the client device based upon one or more enterprise credentials associated with the user; establishing, by the enterprise agent, a secure tunnel between the enterprise agent and a server associated with an enterprise, the enterprise having one or more associated applications; receiving, by the enterprise agent, enterprise data from the server, the enterprise data received via the secure tunnel; and storing, by the enterprise agent, the enterprise data in the secure container in accordance with one or more data policies of the enterprise, wherein the secure container is only accessible by a verified user and by the one or more applications associated with the enterprise.
2. The method of claim 1, wherein access to the second portion of the computer-readable storage is provided independently of the one or more data policies of the enterprise.
3. The method of claim 1, wherein private data associated with the user is stored in the second portion of the computer-readable storage, the private data associated with activity of the user that is outside of a role of the user in the enterprise, the second portion of the computer-readable storage being inaccessible to the enterprise agent.
4. The method of claim 1, comprising: deleting, by the enterprise agent, the enterprise data in the secure container in accordance with the one or more data policies of the enterprise.
5. The method of claim 4, wherein, after the deleting, the second portion of the computer-readable storage is unmodified.
6. The method of claim 4, wherein deleting the enterprise data in the secure container in accordance with the one or more data policies of the enterprise comprises deleting the enterprise data based upon at least one of: an expiration of a period of time, a time at which access to the secure container is requested, a geographic location of the client device, an indication that the client device is compromised, a configuration setting of the client device, detected behavior of the user, an indication that the user no longer has associated valid enterprise credentials, a number of times the one or more enterprise credentials associated with the user cannot be verified, or receiving a command from the enterprise to wipe the secure container.
7. The method of claim 1, comprising: restricting access, by the enterprise agent, to the secure container based upon a geographic location of the client device.
8. The method of claim 1, comprising: preventing, by the enterprise agent, enterprise data in the secure container from being copied and stored in the second portion of the computer-readable storage.

9. The method of claim 1, wherein at least one of the one or more applications associated with the enterprise is downloaded to the client device from the server associated with the enterprise.
10. The method of claim 1, wherein at least one of the one or more applications associated with the enterprise is a remote application operating on the server associated with the enterprise.
11. The method of claim 1, wherein the server associated with the enterprise is a cloud server.
12. The method of claim 1, wherein the secure tunnel employs protocol encapsulation to send data over a network.
13. The method of claim 12, wherein storing the enterprise data in the secure container is based, at least in part, upon detecting by the enterprise agent that the enterprise data was received via the secure tunnel.
14. The method of claim 12, wherein the secure tunnel employs Remote Desktop Protocol (RDP).
15. The method of claim 1, comprising: operating the one or more applications associated with the enterprise in one or more secure virtual machines of the client device, each of the one or more secure virtual machines separate from a virtual machine operating an operating system of the client device.
16. The method of claim 1, wherein the enterprise data stored in the secure container comprises applications downloaded to the client device from the server associated with the enterprise.
17. The method of claim 1, wherein the enterprise data stored in the secure container comprises one or more of: one or more data files associated with the enterprise, one or more credentials associated with the user, one or more certificates associated with the enterprise, or one or more encryption keys.
18. The method of claim 1, comprising: establishing, by the enterprise agent, one or more secure connections to the server associated with the enterprise; and communicating over the one or more secure connections to maintain user authentication for access to the secure container.
19. The method of claim 1, comprising: establishing, by the enterprise agent, a connection from the client device to a secure application store associated with the enterprise; and downloading the one or more applications associated with the enterprise from the secure application store to the client device.
20. The method of claim 1, wherein the secure container is inaccessible to one or more applications not associated with the enterprise.
21. A method comprising: generating a secure container in a first portion of a computer-readable storage of a client device, the secure container being encrypted and comprising a file system, and being separate from a second portion of the computer-readable storage; verifying a user of the client device based upon one or more enterprise credentials associated with the user; establishing a secure tunnel between the client device and a server associated with an enterprise, the enterprise having one or more associated applications; and storing enterprise data in the secure

container in accordance with one or more data policies of the enterprise, the enterprise data received from the server via the secure tunnel, wherein the secure container is only accessible by a verified user and by the one or more applications associated with the enterprise.

22. The method of claim 21, wherein access to the second portion of the computer-readable storage is provided independently of the one or more data policies of the enterprise, and wherein private data associated with the user is stored in the second portion of the computer-readable storage, the private data associated with activity of the user that is outside of a role of the user in the enterprise, the second portion of the computer-readable storage being inaccessible to the one or more applications associated with the enterprise.

23. The method of claim 21, comprising: deleting the enterprise data in the secure container in accordance with the one or more data policies of the enterprise, wherein, after the deleting, the second portion of the computer-readable storage is unmodified.

24. The method of claim 21, comprising: preventing enterprise data in the secure container from being copied and stored in the second portion of the computer-readable storage.

25. The method of claim 21, comprising: operating the one or more applications associated with the enterprise in one or more secure virtual machines of the client device, each of the one or more secure virtual machines separate from a virtual machine operating an operating system of the client device.

26. The method of claim 21, comprising: establishing a connection from the client device to a secure application store associated with the enterprise; and downloading the one or more applications associated with the enterprise from the secure application store to the secure container of the client device.

27. A method comprising: establishing a secure tunnel between a client device and a server associated with an enterprise, wherein the secure tunnel is established for a verified user of the client device based upon one or more enterprise credentials associated with the user; determining one or more applications associated with the enterprise; transmitting enterprise data from the server to the client device via the secure tunnel, wherein the enterprise data is stored in a secure container of the client device in accordance with one or more data policies of the enterprise, wherein the secure container is located in a first portion of a computer-readable storage of the client device, the secure container being encrypted and comprising a file system, wherein the first portion of the computer-readable storage is separate from a second portion of the computer-readable storage, and wherein the secure container is only accessible by the verified user and by the one or more applications associated with the enterprise.